

BELZONA AMERICA INC -- 1024/0866, BELZONA 1111 BASE -- 8030-00-187-7747

=====
Product Identification
=====

Product ID:1024/0866, BELZONA 1111 BASE

MSDS Date:02/17/1992

FSC:8030

NIIN:00-187-7747

Kit Part:Y

MSDS Number: BTSMS

=== Responsible Party ===

Company Name:BELZONA AMERICA INC

Address:2000 NW 88 COURT

City:MIAMI

State:FL

ZIP:33172

Country:US

Info Phone Num:305-594-4994

Emergency Phone Num:305

-594-4994 OR 305-274-6512

Preparer's Name:J. PARTINGTON

CAGE:0PX05

=== Contractor Identification ===

Company Name:BELZONA INC.

Address:2000 N. W. 88 COURT

Box:City:MIAMI

State:FL

ZIP:33172

Country:US

Phone:305-594-4994

CAGE:0PX05

=====
Composition/Information on Ingredients
=====

Ingred Name:DGBA EPOXY RESINS

CAS:25068-38-6

RTECS #:SL6475000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:EPOXIDIZED PHENOL-FORMALDEHYDE NOVOLAC

CAS:28064-14-4

Fraction by

Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MODIFIED SILICA

CAS:92797-60-9

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN AND EYE IRRITATION.

CHRONIC: IRRITATION, SENSITIZATION AND DERMATITIS.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of O

verexposure:SKIN SENSITIZER AND SKIN IRRITATION.

Medical Cond Aggravated by Exposure:SKIN & EYE CONDITIONS.

=====
===== First Aid Measures =====

First Aid:INHALE-REMOVE SOURCE OF CONTAMINATION &/OR MOVE VICTIM TO FRESH AIR. IF RECOVERY IS DELAYED, OBTAIN MEDICAL ATTENTION.

EYE-FLUSH W/WATER FOR AT LEAST 15 MINS. IMMEDIATE FIRST AID IS

NEEDED TO PREVENT EYE DAMAGE. SEEK PHYSICIAN. SKIN-IMMEDIATELY

REMOVE EXCESS WITH A CLEAN CLOTH & WASH W/SOAP &

WATER. SEE

PHYSICIAN. INGEST-DO NOT INDUCE VOMITING. RINSE MOUTH WITH WATER & DRINK 1 CUP WATER. SEE DOC.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>392F,>200C

Lower Limits:NIA

Upper Limits:NIA

Extinguishing Media:WATER FOG (NOT A DIRECT STREAM OF WATER), FOAM, CARBON DIOXIDE & DRY CHEMICAL.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING & USE SELF-CONTAINED BREATHING APPARATUS. FULL BUNKER GEAR SHOULD BE WORN IN

EXTREME

CASES. USE SAND TO CONTAIN BURNING MATERIAL.

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE HAZARDOUS.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/AN INERT MATERIAL (E.G. EARTH/SAND) . SWEEP UP, PLACE INTO SUITABLE LABELLED CONTAINERS, SEAL & DISPOSE OF PROPERLY. FLUSH AREA W/DETERGENT & WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS SHOULD BE STORED UNDER COOL, DRY CONDITIONS. OVERHEATING MAY CAUSE CONTRS TO RUPTURE. EMPTY CONTRS WILL RETAIN RESIDUE & MAY BE DANGEROUS.
Other Precautions:CHECK ALL CONTAINERS FOR LEAKS AT REGULAR INTERVALS & BEFORE USE. AVOID BREATHING VAPORS & CONTACT W/SKIN & EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS OR WHERE GOOD NATURAL/MECHANICAL VENTILATION IS NOT AVAIL, LEADING TO RISK OF EXCEEDING TLV'S INDICATED, OR WHERE MACHINING/ABRADING OF CURED MATL LEADS TO PRODUCTION OF RESPIRABLE &/OR NUISANCE DUST, AN APPROVED RESPIRATOR WORN.
Ventilation:WHERE ADEQUATE NATURAL VENTILATION IS NOT AVAILABLE PROVIDE SUITABLE LOCAL EXHAUST VENTILATION.
Protective Gloves:IMPERMEABLE GLOVES (NEOPRENE OR PVC).
Eye Protection:SAFETY GLASSES OR GOGGLES.
Other Protective Equipment:WHERE THERE IS RISK OF CONTAM OF FOOTWEAR, SAFETY BOOTS SHOULD BE WORN & CLEANED THORO BEFORE REUSE.
Work Hygienic Practices:WHEN USING, DO NOT EAT, DRINK OR SMOKE. REMOVE CONTAMD CLTHG & LAUNDRER BEFORE REUSE. WASH HANDS W/SOAP & WATER.
Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:DECOMPOSES
Vapor Pres:NIA
Vapor Density:NIA
Spec Gravity:2.80
Evaporation Rate & Reference:N.AP
Solubility in Water:NEGLIGIBLE
Appearance and Odor:DARK GRAY PASTE WITH EPOXY ODOR.
Percent

Volatiles by Volume:N.AP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ACIDS, BASES AND AMINES.

Stability Condition to Avoid:NOT APPLICABLE.

Hazardous Decomposition Products:GASEOUS COMBINATION OF CARBON,
HYDROGEN, & OXYGEN MAY OCCUR AT ELEVATED TEMPERATURE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE &
FED

ERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.