

BAKER SEALANTS AND COATINGS CO -- WOOD FILLER -- 8010-00-598-5765

=====
Product Identification
=====

Product ID:WOOD FILLER

MSDS Date:06/11/1991

FSC:8010

NIIN:00-598-5765

MSDS Number: BTSPJ

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Info Phone Num:201-333-6986 / FAX 201-333-6955

Emergency Phone N

um:201-333-6986

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:CLAY

CAS:68953-58-2

Fraction by Wt: 2-3% %

Other REC Limits:NONE RECOMMENDED

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 15-18% %

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:500 PPM
ACGIH TLV:100 PPM; 9394

Ingred Name:TALC (CONTAINING ASBESTOS)
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 64-68% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.2 FIBERS/CC; 9394

Ingred Name:ALKYD RESIN
CAS:66070-60-8
Fraction by Wt: 15-18% %
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT AS A WHOLE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Re

ports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION, DERMATITIS. INHALATION OF VAPORS AND MISTS MAY IRRITATE MUCOUS MEMBRANES. MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION, COMA, UNCONSCIOUSNESS OR DEATH. SWALLOWING MAY CAUSE VOMITING. ASPIRATION MAY CAUSE CHEMICAL PNEUMONIA.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, DERMATITIS, UPPER RESPIRATORY TRACT IRRITATION, MUCOUS MEMBRANE IRRITATION, HEADACHES, NAUSEA, VOMITING, COMA, UNCONSCIOUSNESS, DEATH, CHEMICAL PNEUMONIA, PULOMOARY ED EMA/HEMORRAGE.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND/OR RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

Fir

st Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN HALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION.

===== Fire Fighting Measures =====

FI

ash Point:110F,43C

Lower Limits:0.8 %

Upper Limits:5.0 %

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:AVOID ACCUMULATION OF WATER BECAUSE THIS PRODUCT WILL FLOAT ON WATER AND MAY REIGNITE ON THE SURFACE OF THE WATER.

===== Accidental Release M

asures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. EVACUATE AREA. WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. CONTAIN SPILL. STOP LEAK IF CAN DO SO WITHOUT RISK. ABSORB LIQUID WITH SUITABLE ABSORBENT MATERIAL. COLLECT FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH

TEMPERATURES. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT USING.

Other Precautions:AVOID SKIN CONTACT. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation:LOCAL EXHAUST A

ND MECHANICAL (GENERAL) VENTILATION TO
MAINTAIN EXPOSURE LEVELS.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO AVOID
SKIN CONTACT. AN EMERGENCY EYE WASH STATION AND SHOWER SHOULD BE
AVAILABLE.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT
AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

EMPTY CONTAINERS RETAIN PRODUCT RESIDUE AND CAN BE DANGEROUS. DO NO
T

PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE SUCH
CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY OR OTHER
SOURCES O F IGNITION; THEY MAY EXPLODE.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:2.0

Vapor Density:4.83

Spec Gravity:1.59

Evaporation Rate & Reference:0.12 (BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OFF-WHITE PASTE,
ALIPHATIC ODOR

Percent Volatiles by Volume:20-22%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, OPEN FLAME, SPARKS

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT. D

DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR
LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.