

EZE PRODUCTS, INC -- EZE 458 -- 6850-01-235-0873

=====
===== Product Identification =====

Product ID:EZE 458
MSDS Date:08/21/1992
FSC:6850
NIIN:01-235-0873
MSDS Number: BTTVF
=== Responsible Party ===
Company Name:EZE PRODUCTS, INC
Address:603 HIGH TECH CT
Box:5744
City:GREER
State:SC
ZIP:29606
Country:US
Info Phone Num:803-879-7100
Emergency Phone Num:803-879-7100 OR 404-842-0430
CAGE:8Z357
=== Contra
ctor Identification ===
Company Name:EZE PRODUCTS, INC
Address:603 HIGH TECH CT
Box:5744
City:GREENVILLE
State:SC
ZIP:29606
Country:US
Phone:803-242-1002 OR 803-879-7100
CAGE:8Z357
Company Name:SILVER SALES
Address:5115 DOUGLAS FIR RD SUITE C
Box:City:CALABASES
State:CA
ZIP:91302
Country:US
Phone:818-591-0788 WAS IN TX
CAGE:0WG65

=====
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 10-20%
Other

REC Limits:NONE RECOMMENDED

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 1-7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9394

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Fraction by Wt: 1-7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 25 PPM
ACGIH TLV:C 25 PPM; 9394

Ingred Name:VOLATILE ORGANIC CONTENT: 266.4 GRAMS/LITER.
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
ion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITANT; SLIGHTLY TOXIC WHEN
INHALED OR INGESTED. CAN CAUSE BURNS TO EXPOSED TISSUE. CHRONIC:
SLIGHTLY TOXIC IF INHALED OR INGESTED.
Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF
0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES: IRRITATION,
CORNEA DAMAGE. SKIN: BURNS.
INHALED: HEADACHE, DIZZINESS, NAUSEA, IRRITATION OF UPPER
RESPIRATORY TRACT. INGESTED: NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures =====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES, LIFT LIDS. GET
MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP
& WATER. INHALED-REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF

SYMPTOMS PERSIST. INGESTED-DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE WATER TO DILUTE. SEEK MEDICAL ASSISTANCE. TARGET ORGANS: SKIN, EYES, RESPIRATORY SYSTEM, CNS.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:200F,93C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:DO NOT ENTER CONFINED SPACE WITHOUT SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COOL FIRE EXPOSE

D CONTAINERS. ALTHOUGH

NOT FLAMMABLE IN AQUEOUS STATE; IT WILL BURN IN THE PRESENCE OF A STRONG IGNITION SOURCE, AFTER WATER REMOVED.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN THE SPILL. ELIMINATE ANY IGNITION SOURCE. ABSORB SMALL SPILLS WITH SAND, DIRT OR CLAY. LARGE SPILLS MAY BE PUMPED INTO CONTAINERS FOR RECOVERY OR DISPOSAL.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE CONTAINERS IN A COOL PLACE, BUNG UP AND TIGHTLY CLOSED.

Other Precautions:HAVE EYE WASH STATION & SAFETY SHOWER, LAUNDRY FACILITIES AVAILABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE IF ENGINEERING CONTROLS FAIL OR EMERGENCY OCCURS. USE IAW 29 CFR 1910.134.

Ventilation:ADEQUATE-LOCAL EXHAUST.

Protective Gloves:RUBBER OR NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER AND LAUNDRY FACILITIES AVAILABLE. PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

CONTRACT NUMBER: SP0450-M-Z797.

===== Physical/Chemical Properties =====

HCC

:N1
Boiling Pt:B.P. Text:212F,100C
Melt/Freeze Pt:M.P/F.P Text:6F,-14C
Vapor Density:>1
Spec Gravity:0.98
pH:9.9
Solubility in Water:FORMS AN EMULSION
Appearance and Odor:OPAQUE VISCOUS LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING OR REDUCING AGENTS
Stability Condition to Avoid:AVOID TEMPERATURE EXTREMES AND
INCOMPATIBLE MATERIAL.
Hazardous Decomposition Products:BURNING CAN PRODUCE OXID
ES OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL
APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.
CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL OR WASTE MAY
BE INCINERATED. NO RCRA WASTE CODE IS APPLICABLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.