

ACCUTONE, INC -- CANON CX; SX; EPL; PC CARTRIDGE REPLACEMENT TONER --
6850-01-321-0640

===== Product Identification =====

Product ID:CANON CX; SX; EPL; PC CARTRIDGE REPLACEMENT TONER

MSDS Date:12/01/1990

FSC:6850

NIIN:01-321-0640

MSDS Number: BTTVS

=== Responsible Party ===

Company Name:ACCUTONE, INC

Address:200 PARK CENTRAL BLVD. SOUTH

City:POMPANO BEACH

State:FL

ZIP:33064

Country:US

Info Phon

e Num:305-970-8980

Emergency Phone Num:305-970-8980

CAGE:IO334

=== Contractor Identification ===

Company Name:ACCUTONE INC

Address:2800 NW 55TH CT

Box:City:FORT LAUDERDALE

State:FL

ZIP:33307

Country:US

Phone:800-237-9509

CAGE:IO334

Company Name:AMERICAN LASER PRODUCTS INC

Address:900-B E MIRICLE MILE

Box:City:MCALLEN

State:TX

ZIP:78501

Country:US

Phone:512-686-7404

CAGE:0K1B9

===== Composition/Information on Ingredients =====

Ingred Name:STYRENE ACRYLIC POLYMER

Fraction by Wt

: 55-65%

Ingred Name:MAGNETITE, MAGNETIC OXIDE

CAS:1309-38-2

RTECS #:OM4800000

Fraction by Wt: 25-65%

Ingred Name:BENZOIC ACID, 2-((2-CARBOXYPHENYL)AMINO)-4-CHLORO-,
DISODIUM SALT, CCA

CAS:64808-48-6

RTECS #:DG4975520

Fraction by Wt: 0.2-1.5%

Ingred Name:POLYWAX

Fraction by Wt: 3-6%

Ingred Name:POST ADDITIVES

Fraction by Wt: 0.5-1.0%

=====
===== Hazards Identification =====

LD50 LC50 Mixture:AMES TEST NEGATIVE.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: UNCOMFORTABLE BRONCHIAL SENSATION. EYE CONTACT-NO HAZARD. SKIN-NO KNOWN HAZARD.

Explanation of Carcinogenicity:NEGATIVE MUTAGENICITY (AMES TEST NEGATIVE)

Effects of Overexposure:INHALATION: COUGHING OR SNEEZING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT-WASH EYES AS WITH ANY MATERIAL THAT IRRITATES.

SKIN-WASH WITH COLD WATER AND SOAP.

=====
===== Fire Fighting Measures =====

Extinguishing Media:CO2, WATER, DRY CHEMICAL EXTINGUISHER.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:POSSIBLE CONDITIONS COULD CREATE A DRY DUST EXPLOSION; AVOID SOURCES OF IGNITION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID INHALATION. SWEEP MATERIAL UP & DISPOSE OF PR

OPERLY.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP OUT OF REACH OF CHILDREN. KEEP FROM CONTACT W/OXIDIZING MATERIALS. AVOID DUSTING.
Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED DURING PRINTING CYCLE. AVOID DIRECT HEAVY INHALATION OF PRODUCT.
Ventilation:GOOD GENERAL VENTILATION.
Protective Gloves:NONE REQUIRED.
Eye Protection:NONE REQUIRE
D. AVOID AIRBORNE PARTICLES.
Other Protective Equipment:NONE REQUIRED.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1
Melt/Freeze Pt:M.P/F.P Text:100-140C
Vapor Pres: