

LHB INDUSTRIES -- 392CB70 SO SURE STENCIL INK WHITE 37875 /394-

=====  
MSDS Safety Information  
=====

FSC: 7510  
NIIN: 00-419-9564  
MSDS Date: 12/01/1992  
MSDS Num: BTVQX  
Product ID: 392CB70 SO SURE STENCIL INK WHITE 37875 /394-370/  
MFN: 01  
Responsible Party  
Cage: OFTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
C  
City: ST LOUIS MO 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 314-522-3141  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: OFTT5  
Assigned Ind: Y  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: BERKELEYS MO 63134

=====  
Contractor Summary  
=====

=====  
Cage: 58536  
Name: GSA/FEDERAL COMMERCIAL ITEM DESCRIPTION  
Address: PROMULGATED BY GENERAL SERVICES ADMIN.  
City: WASHINGTON DC 00000  
Phone: UNKNOWN  
Cage: OFTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: BERKELEYS MO 63134  
Phone: 314-423-4333

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: INK,MARKING STENCIL  
Specification Number: A-A-208A  
Unit

of Issue: PT  
UI Container Qty: 1

=====  
Ingredients  
=====

Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE, DIMETHYLBENZENE, XYLOL  
% Wt: &lt;1.86  
Other REC Limits: 100 PPM  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM, SKIN  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

Cas: 64742-89-8  
Name: LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE  
% Wt: 5.58  
OSHA PEL: 300 PPM  
ACGIH  
TLV: 300 PPM  
-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE  
% Wt: 20.24  
Other REC Limits: 375 MG/CUM  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

Cas: 67-64-1  
RTECS #: AL3150000  
Name: ACETONE; DIMETHYL KETONE; 2-PROPANONE  
% Wt: 24.65  
OSHA PEL: 1000 PPM  
ACGIH TLV: 750 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

Cas: 74-98-6  
RTECS #: TX2275000  
Name: PROPANE  
% Wt: 18.

88

Other REC Limits: 1800 MG/CUM

OSHA PEL: 1000 PPM

ACGIH TLV: 1000 PPM

-----  
Cas: 75-28-5

RTECS #: TZ4300000

Name: ISOBUTANE, 2-METHYLPROPANE

% Wt: 7.43

Other REC Limits: 1000 PPM

OSHA PEL: 1800 MG/CUM

ACGIH TLV: 800 PPM

-----  
Cas: 106-97-8

RTECS #: EJ4200000

Name: BUTANE, N-BUTANE

% Wt: 4.64

Other REC Limits: 800 PPM

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

-----  
RTECS #: 9999999VO

Name: VOLATILE ORGANIC COMPOUNDS: 644 G/L

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: IRRITATION TO EYES/THROAT/RESPIRATORY TRACT. MAY CAUSE HEADACHES/NAUSEA/VOMITING. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS HAVE

BEEN ASSOCIATED W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATION OF VAPORS ARE ANESTHETIC IN CONFINED AREAS. HAMFUL IF SWALLOWED.

SEVERE EYE IRRITATION. (SEE SUPP)

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: IRRITATION, HEADACHES, NAUSEA, VOMITING, LIGHT-HEADNESS, STAGGERING GAIT, GIDDINESS.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

First Aid: SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRE

SH AIR. GIVE CPR IF NECESSARY.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Handling and Disposal  
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION & VENTILATE AREA.  
MOP W/INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.  
DISCARD EMPTY CAN IN TRASH PICK UP. DON'T PLACE IN HOME TRASH COMPACTOR.

Handling And

Storage Precautions: DON'T STORE >120F. USE W/GOOD  
VENTILATION.

Other Precautions: DON'T PUNCTURE/INCINERATE. KEEP OUT OF REACH OF CHILDREN.  
AVOID BREATHING SPRAY/MIST/VAPOR. AVOID CONTACT W/EYES/SKIN. INTENTIONAL  
MISUSE BY DELIBERATELY CONCENTRATING/INHALING/SWALLOWING CONTENTS MAY BE  
HARMFUL/FATAL.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Text: -5F

Lower Limit

ts: 1.8

Upper Limits: 9.5

Extinguishing Media: CO2, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE/MAY BE USED TO COOL FIRE  
EXPOSED CONTAINERS. WEAR SCBA. USE SHIELDING TO PROTECT AGAINST  
BURSTING/RUPTURING/VENTING OF CONTAINERS.

Unusual Fire/Explosion Hazard: AVOID SPREADING ANY BURNING LIQUID W/WATER  
SPRAY. DON'T SPRAY NEAR OPEN FLAME. CONTAINERS MAY VENT/RUPTURE/BURST AT  
TEMPS >120F. AUTOIGNITION TEMP: 874F.

=====  
Control Measures  
=====

Respiratory Protection: USE NIOSH/MSHA APPROVED MASK >TLV.

Ventilation: LOCAL EXHAUST PREFERRED. MECHANICAL/GENERAL IS ACCEPTABLE AT POINT  
OF MIST/SPRAY RELEASE.

Protective Gloves: REQUIRED

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: IMPERVIOUS CLOTHING & EYE WASH STATION.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.  
DON'T EAT, DRINK/SM

OKE WHILE USING PRODUCT.

Supplemental Safety and Health: HEALTH HAZARDS CONT'D: OVEREXPOSURE MAY RESULT IN LIGHT-HEADNESS, STAGGERING GAIT, GIDDINESS & POSSIBLE NAUSEA.

=====  
Physical/Chemical Properties  
=====

Vapor Pres: 60

Vapor Density: >1.5

Spec Gravity: 0.978

Solubility in Water: INSOLUBLE

Appearance and Odor: WHITE PAINT  
=====

Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: TEMPS >120F, EXTREME HEAT, IGNITION SOURCES, PROLONGED EXPOSURE TO SUN.

Hazardous Decomposition Products: CO & HYDROGEN CHLORIDE.

Hazardous Polymerization Indicator: NO  
=====

Toxicological Information  
=====

Ecological Information  
=====

MSDS Transport Information  
=====

Regulatory Information  
=====

Other Information  
=====

=====  
HAZCOM Label  
=====

Product ID: 392CB70 SO SURE STENCIL INK WHITE 37875 /394-370/

Cage: OFTT5

Assigned IND: Y

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: BERKELEYS MO

Zipcode: 63134

Health Emergency Phone: 314-522-3141

Label Required IND: Y

Date Of Label Review: 08/25/1994

Status Code: C

Label Date: 08/25/1994

Origination Code: F

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND

: YES  
Signal Word: DANGER  
Respiratory Protection IND: YES  
Health Hazard: Severe  
Contact Hazard: Slight  
Fire Hazard: Severe  
Reactivity Hazard: Slight

Hazard And Precautions: IRRITATION TO EYES/THROAT/RESPIRATORY TRACT. MAY CAUSE HEADACHES/NAUSEA/VOMITING. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS HAVE BEEN ASSOCIATED W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATION OF VAPORS ARE ANESTHETIC IN CONFINED AREAS. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING GAIT, GIDDINESS & POSSIBLE NAUSEA. TARGET ORGAN S: BRAIN, NERVOUS SYSTEM & GI TRACT. N/K

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.