View NSN Online: https://aerobasegroup.de/nsn/6505-01-183-4861

BRISTOL-MYERS SQUIBB, PHARMACEUTICAL GRP -- KINEVAC 5 UG/VIAL -- 6505-01-183-4861

Product ID:KINEVAC 5 UG/VIAL

MSDS Date:03/04/1993

FSC:6505

NIIN:01-183-4861

MSDS Number: BTVRX === Responsible Party ===

Company Name: BRISTOL-MYERS SQUIBB, PHARMACEUTICAL GRP

Address: 5 GORDIS RD BLDG 124

Box:191

City:NEW BRUNSWICK

State:NJ ZIP:08903 Country:US

Info Phone Num:800-3 32-2056/908-519-2385

Emergency Phone Num:201-519-2885/609-921-4081

**CAGE:BRIST** 

=== Contractor Identification ===

Company Name: BRISTOL-MYERS SQUIBB PHARMACEUTICAL GROUP

Box:191

City:NEW BRUNSWICK

State:NJ ZIP:08903 Country:US

Phone:908-519-2385

**CAGE:BRIST** 

Company Name: ER SQUIBB MEDATOPE DIV

Address:5 GORDIS RD BLDG 124

Box:191

City:NEW BRUNSWICK

State:NJ ZIP:08903 Country:US

Phone:609-921-4081

**CAGE:4T649** 

====== Composition/Information on Ingredients ========

Ingred Name:SINCALIDE

CAS:25126-32-3 Fraction by Wt: 0.01% Ingred Name: SODIUM CHLORIDE CAS:7647-14-5 RTECS #: VZ4725000 Fraction by Wt: 99.99% Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IF PRODUCT BECOMES AEROSOLIZED & INHALED, IT MAY PRODUCE EFFECTS SEEN AFTER INJECTION. SODIUM CHLORIDE MAY CAUSE MILD SKIN IRRITATION & MODERATE EYE IRRITATION KINEVAC CONTAINS SINCALIDE, A DRUG THAT IS USED TO STIMULATE/EVACUATE THE GALLBLADDER. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: IRRITATION, NAUSEA, ABDOMINAL PAIN, DISCOMFORT, URGE TO DEFECATE, DIZZINESS, FLUSHING Medical Cond Aggravated by Exposure: INJECTION OF THERAPEUTIC DOSES OF KINEVAC MAY CAUSE SMALL GALLBLADDER STONES TO BE EVACUATED, LEADING TO BLOCKAGE OF THE BILE DUCT. **First** 

Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15-20 MINS. SKIN: WASH W/SOAP & WATER FOR 15-20 MINS. INHALATION: REMOVE TO FRESH AIR. IF DIFFICULTY IN BREATHING ADMINISTER OXYGEN. IF NOT BREATHING, ATTEMPT CPR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

============= Fire Fighting Measures ========================

Extinguishing Media:WATER

Fire Fighting Procedures: EVACUATE AREA. USE A SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING. USE WATER TO KEEP FIRE-E

| Unusual Fire/Explosion Hazard:FINE DUST SUSPENDED IN AIR IN SUFFICIENT CONCENTRATION & IN THE PRESENCE OF AN IGNITION SOURCE MAY POSE A POTENTIAL EXPLOSION HAZARD.  |
|--|
| ======== Accidental Release Measures ==========  |
| Spill Release Procedures:WEAR PROTECTIVE CLOTHING & A NIOSH-APPROVED DUST/MIST RESPIRATOR. SPILLED POWDER MAY BE WETTED TO MINIMIZE DUST GENERATION. SWEEP MATERIAL ONTO PAPER & PLACE INTO AN APPROPRIATE FIBE                          |
| R DRUM FOR DISPOSA L. VENTILATE & DECONTAMINATE AREA AFTERCLEAN-UP.  |
| ========== Handling and Storage ============   |
| Handling and Storage Precautions:SHOULD BE STORED AT ROOM TEMPERATURE, 59-86F. AVOID INHALATION OF THE POWDER. CHEMICAL SAFETY GOGGLES & LATEX GLOVES SHOULD BE USED WHEN HANDLING. Other Precautions:AVOID SKIN & EYE CONTACT W/POWDER. |
| ====== Exposure Controls/Personal Protection ========  |
| Respiratory Protection:NIOSH-APPROVED DUST/MIST RESPIRATOR. Protective Gloves:LATEX Eye Protection:CHEMICAL SAFETY GOGGLES Other Protective Equipment:GOWN   |
| Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.   |
| Supplemental Safety and Health SPEC. FIRE PROC CONT'D: FIGHT FIRE FROM MAXIMUM SAFE DISTANCE/USE AN UNMANNED MONITOR. MOVE CONTAINERS OF CHEMICALS FROM FIRE AREA W/O RISK. DIVERT RUNOFF TO A SAFE AREA.                                |
| ======== Physical/Chemical Properties ==========   |
| Solubility in Water:COMPLETE App   |
| earance and Odor:VIALS CONTAINING WHITE POWDER.  |
| ======== Stability and Reactivity Data =========   |
| Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HIGH TEMPERATURES, TEMPS >86F & TEMPS  |

XPOSED CONTAINERS COOL. (SEE SUPP)