

DOALL CO -- GAGE BLOCK PRESERVATIVE (AEROSOL) -- 8030-01-014-5065

=====
Product Identification
=====

Product ID:GAGE BLOCK PRESERVATIVE (AEROSOL)

MSDS Date:03/29/1991

FSC:8030

NIIN:01-014-5065

MSDS Number: BTWBY

=== Responsible Party ===

Company Name:DOALL CO

Address:254 N LAUREL AVE

City:DES PLAINES

State:IL

ZIP:60016-4321

Country:US

Info Phone Num:708-803-7272

Emergency Phone Num:708-803-7272

C

AGE:18056

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:DOALL CO

Address:254 NO LAUREL AVE

Box:City:DES PLAINES

State:IL

ZIP:60016

Country:US

Phone:847-803-7366

CAGE:18056

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fr

action by Wt: 35%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:350 PPM
ACGIH TLV:350 PPM/450STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM; Z-2
ACGIH TLV:50 PPM, A2; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 8%
Other REC Limits:NONE RE
COMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9394

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC
CAS:64742-88-7
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY
PARAFFINIC
CAS:64742-65-0
RTECS #:PY8038500
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:5 MG/M3 (OIL

MIST)

Ingred Name:2-BUTOXYETHANOL (SARA III)

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9394

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 10 G/KG

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION-BREATHING DIFFICULTY. EYE CONTACT-IRRITATION. SKIN

-DEFATTING AND/OR IRRITATION.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:INGESTION-NAUSEA AND/OR DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION-REMOVE PERSON TO FRESH AIR. IF NECESSARY, SUPPORT BREATHING. GET MEDICAL ATTENTION. EYE-FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN CONTACT-WASH EXP O

SED AREA WITH MILD SOAP AND WARM WATER ONLY. DO

NOT USE HARSH SOAP OR SOLVENT. GET MEDICAL ATTENTION.

INGESTION-KEEP PERSON WARM AND QUIET. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Lower Limits:1.9

Upper Limits:9.5

Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WATER STREAM OR SPRAY, TO COOL CONTAINERS TO PREVENT VAPOR FORMATION AND IGNITION, MAY SPREAD FIRE. FOG NOZZLES ARE PREFERRED IF WATER

USED. WEAR SCBA GEAR.

Unusual Fire/Explosion Hazard:AEROSOL CANS WILL RUPTURE EXPLOSIVELY ON OVERHEATING.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL-USE ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE DRY IN A CLOSED CONTAINER IN A COOL PLACE AWAY FROM ANY FIRE SOURCES.

Other Precautions:DO NOT INGEST. AVOID BREATHING VAPOR. DO NOT SMOKE WHILE USING OR USE NEAR AN OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:GENERAL MECHANICAL VENTILATION SHOULD BE ADEQUATE. PROVIDE LOCAL VENTILATION IF VAPOR BUILDUP BECOMES EXCESSIVE.

Protective Gloves:NEOPRENE GLOVES.

Eye Protection:SAFETY GOGGLES OR FACE SHIELD.

Other Protective Equipment:AN EMERGENCY SHOWER AND EYEWASH SHOULD BE AVAILABLE IN THE WORK AREA.

Work Hygienic Practices:PRA

CTICE REASONABLE PERSONAL HYGIENE. WASH EXPOSED SKIN WITH MILD SOAP AND WARM WATER ONLY.

Supplemental Safety and Health

OILSOAKED CLOTHING SHOULD BE CHANGED PROMPTLY AND LUANDERED BEFORE RE-WEARING.

===== Physical/Chemical Properties =====

HCC:V2

Vapor Density:>AIR

Spec Gravity:1.060

Evaporation Rate & Reference:>1

Solubility in Water:INSOLUBLE

Appearance and Odor:COILORLESS LIQUID. SOLVENT ODOR.

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: AVOID OPEN FLAMES AND HOT SURFACES.

Hazardous Decomposition Products: OXIDES OF CARBON, AND CHLORINE
COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods: TREAT AS AN OILY WASTE AND DISPOSE OF IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.