

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL ALKYD, SEMI GLOSS LO VOC CT GRAY 26492, ID 775655 -- 8010-00-104-8377

=====
===== Product Identification =====

Product ID:ENAMEL ALKYD, SEMI GLOSS LO VOC CT GRAY 26492, ID 775655

MSDS Date:01/06/1994

FSC:8010

NIIN:00-104-8377

MSDS Number: BTZVH

==== Responsible Party ====

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WI

CHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

==== Contractor Identification ====

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF7

350000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

7
RTECS #:XR2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:SILICA, AMORPHOUS HYDRATED (PIGMENT)
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TALC (PIGMENT)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3; 20 MPPCF
ACGIH TLV:2 MG/M3; 15 MPPCF

Ingred Name:SILICA, CRYSTALLINE
CAS:14808-60-
7
RTECS #:VV7330000
Fraction by Wt: AIR
Spec Gravity:1.4
pH:4-7
Viscosity:67 - 77 KU
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT IN WATER
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:41

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES
OF

IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL LAWS OR REGULATIONS. THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS WASTE BASED ON ITS IGNITABILITY CHARACTERISTIC (FLASH POINT 140F OR LESS). PROPER RCRA CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.