

DEL PAINT MFG -- ENAMEL, WHITE 17886 -- 8010-00-901-8035

=====  
Product Identification  
=====

Product ID:ENAMEL, WHITE 17886

MSDS Date:08/30/1993

FSC:8010

NIIN:00-901-8035

MSDS Number: BVBGP

=== Responsible Party ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:

ONEY FLEMING

CAGE:39934

=== Contractor Identification ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM DISTILLATES

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 27.66%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:XYLENE (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0

.24%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:NON-HAZARDOUS INGREDIENTS  
Fraction by Wt: 72.10%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 3.25 LB/GAL; 390 G/L  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazard

Acute and Chronic:EYE CONTACT: IRRITATION, REDNESS,  
TEARING, AND BLURRED VISION. SKIN CONTACT: PROLONG OR REPEATED  
EXPOSURE CAN CAUSE MODERATE IRRITATION, DEFATTING, AND DERMATITIS.  
INHALATION: NASAL AND RESPIRATORY IRRITATION, DIZZINESS, NAUSEA,  
& HEADACHE. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION,  
NAUSEA, VOMITING, DIARRHEA.

Effects of Overexposure:IF TLV'S ARE EXCEEDED SKIN CONTACT PRODUCES  
REDNESS. EYE CONTACT PRODUCES REDNESS AND PAIN. INHALATION GIVES

LABORED BREATHING, DULLNESS, DROWSINESS, INGESTION CAN CAUSE  
ABDOMINAL PAIN AND NAUSEA.

Medical Cond Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH CLEAN, WARM WATER FOR AT LEAST 15  
MINUTES, OCCASIONALLY LIFTING EYELIDS. SEEK MEDICAL ATTENTION. SKIN  
CONTACT: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED SKIN AREAS  
WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH  
AIR, ADMINISTER  
OXYGEN IF NECESSARY, SEEK MEDICAL ATTENTION. INGESTION: KEEP PERSON  
WARM, QUIET AND GET MEDICAL ATTENTION. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:115F,46C  
Autoignition Temp:Autoignition Temp Text:540F  
Lower Limits:1  
Upper Limits:6  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM. WATER MAY  
SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO  
FIRE.  
Fire Fi

ighting Procedures:SCBA RECOMMENDED FOR FIRE FIGHTERS. WATER  
SPRAY MAY BE USED FOR COOLING CONTAINERS TO PREVENT PRESSURE BLDUP  
& AUTOIGNITION OR EXPLOSION WITH EXTREME HEAT.

Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR. MAY TRAVEL ALONG  
GROUND OR MOVED BY VENT & IGNITED BY PILOT LIGHT, OTHER FLAMES,  
SPARKS, HEATERS, SMOKING, & OTHER REMOTE IGNIT SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE THE AREA. COVE  
R SPILL WITH INERT  
ABSORBENT MATERIAL AND SHOVEL WITH NON-SPARKING TOOLS INTO  
CONTAINER. REMOVE CONTAINER TO A SAFE AREA AND SEAL.  
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY  
FROM FOOD PRODUCTS. KEEP AWAY FROM SPARKS, FIRE AND REMOTE IGNITION  
SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM  
CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED T  
O REDUCE STATIC  
ELECTRICITY HAZARD. USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV OF THE PRODUCT OR ANY COMPONENT IS  
EXCEEDED, USE A RESPIRATOR WITH APPROPRIATE CARTRIDGES (NIOSH  
APPROVED). ENGINEERING OR MANAGEMENT CONTROLS SHOULD BE IMPLEMENTED  
TO REDUCE EXPOSURE.

Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR  
CONCENTRATIONS BELOW THE TLV LIMIT.

Protective Gloves:CHEMICAL RESI  
STANT GLOVES

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:SOURCE OF CLEAN WATER SHOULD BE AVAILABLE IN  
WORK AREA FOR FLUSHING EYES & SKIN. WEAR IMPERVIOUS CLOTHING AS  
NEEDED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F,149C

Decomp Temp:Decomp Text:752F,400C

Vapor Pres:2.58

Vapor Density:> AIR

Spec Gravity:1.23 (WATER=1)

Viscosity:77-86 KU

Evaporation Rate & Reference:SLOW

ER THAN ETHER

Solubility in Water:NO

Appearance and Odor:WHITE LIQUID WITH MILD ODOR

Percent Volatiles by Volume:45.97

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES, OPEN  
FLAMES OR IGNITION SOURCES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE  
WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATORY CONTROLS.  
HAZARDOUS WASTE CHARACTERISTIC: IGNITABILITY. EPA HAZARDOUS WASTE  
CODE: NONE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.