

GRIGGS PAINT -- TT-E-529F TY II COMP L #26250, #700A130 -- 8010-01-107-4943

=====
Product Identification
=====

Product ID:TT-E-529F TY II COMP L #26250, #700A130

MSDS Date:01/01/1993

FSC:8010

NIIN:01-107-4943

MSDS Number: BVBLN

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:80

0-424-9300 CHEMTREC

Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES (VAPOR PRESSURE 15.0 MM HG
@ 100F)

CAS:

8030-30-6

RTECS #:DE3030000

Fraction by Wt: 4%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 5.1 MM HG @ 68F)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III) (VAPOR PRESSURE 23.0 MM HG @ 68F)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PE

L:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:RESIN SOLUTION

Fraction by Wt: 45%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MELAMINE RESIN

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (VAPOR PRESSURE
3.7 MM @ 68F)

CAS:108-65-6

RTECS #:AI89

25000
Fraction by Wt: