

E. I. DUPONT DE NEMOURS AND COMPANY -- HALON 1301 FIRE EXTINGUISHANT --
5340-01-346-0895

===== Product Identification =====

Product ID:HALON 1301 FIRE EXTINGUISHANT

MSDS Date:12/01/1985

FSC:5340

NIIN:01-346-0895

MSDS Number: BVFTX

=== Responsible Party ===

Company Name:E. I. DUPONT DE NEMOURS AND COMPANY

Address:FREON PRODUCTS DIVISION

City:WILMINGTON

State:DE

ZIP:19898

Info Phone Num:302-999-3847

302-999-4338

Emergency Phone Num:800-441-3637/800-424-9300(CHEMTREC)

Preparer's Name:T.D.ARMSTRONG

CAGE:73925

=== Contractor Identification ===

Company Name:DU PONT E I DE NEMOURS AND CO INC PETROCHEMICALS DEPT

Address:1251 BRANDYWINE BLDG

Box:City:WILMINGTON

State:DE

ZIP:19898

Phone:302-773-5676

CAGE:73925

===== Composition/Information on Ingredients =====

Ingred Name:TRIFLUOROBROMOMETHANE (HALON 1301) (SARA III)

CAS:75-63-8

RTECS #:PA5425000

Fraction by Wt: 100%

Other

REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9394

Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 INHAL RAT IS >800,000PPM(V/V)/4HRS

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HALON IS HEAVIER THAN AIR AND REDUCES
OXYGEN AVAILABLE TO SUPPORT LIFE(AND COMBUSTION).EYE:POSSIBLE
FROSTBITE.SKIN:POSSIBLE

FROSTBITE.INHAL:POSSIBLE
ASPHYXIATION.INGEST:UNLIKELY ROUTE OF EXPOSURE.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:BELOW 10%, FEELING OF MILD INTOXICATION. ABOVE 10%, MAY LEAD TO CARDIAC IRREGULARITIES,NARCOSIS,UNCONSCIOUSNESS AND POSSIBLY DEATH.AVOID EXPOSURE TO CONCENTRATIONS ABOVE 15%.
Medical Cond Aggravated by Exposure:CARDIAC PROBLEMS MAY BE AGGRAVATED BY EXPOSURE.

=====
===== First Aid Measures =====

First Aid:REMOVE VICTIM TO FRESH AIR. RESCUSCITATE BY MOUTH-TO-MOUTH;GIVE OXYGEN. GIVE SYMPTOMATIC AND SUPPORTIVE CARE. GET MEDICAL ATTENTION. NOTE: ADRENALIN IS CONTRAINDICATED IN THE TREATMENT OF OVEREXPOSUR E TO HALON 1301.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fight
ing Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.CONTAINERS HAVE A PRESSURE RELIEF VALVE BUT CAN STILL RUPTURE UNDER INTENSE HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID HOTMETAL SURFACES.USE LOCAL EXHAUST FOR LARGE SPILLS.USE MECHANICAL VENTI LATION IN LOW PLACES.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID CONTAINER DAMAGE.
Other Precautions:DETERMINE THAT PIPING IS EMPTY BEFORE DOING MAINTENANCE WORK.CHECK FOR ADEQUATE OXYGEN BEFORE ENTERING CONFINED SPACES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

:PROVIDE A SELF CONTAINED BREATHING APPARATUS

AFTER:15 MINUTES OF 7%;1 MINUTE OF 7-10%;30 SECONDS OF 10-15% OR
WHEN CONCENTRATION IS >15 PERCENT.

Ventilation:USE LOCAL EXHAUST FOR LARGE SPILLS.USE MECHANICAL
VENTILATION IN LOW PLACES.

Protective Gloves:NOT NEEDED IN NORMAL SERVICE.

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. USE PROPER CARE WHEN HANDLING AND STORING.

Supp

lemental Safety and Health

NOTE TO PHYSICIAN: PRODUCT IS AN ASPHYXIANT AND MAY INDUCE CARDIAC
MUSCLE SENSITIZATION TO EPENIPHRINE-LIKE COMPOUNDS. DO NOT
ADRENALIN OR SIMILAR SYMPATHOMIMETIC DRUGS.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-72F,-58C

Decomp Temp:Decomp Text:1000F,538C

Vapor Pres:11370

Spec Gravity:1.538

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GAS, COLORLESS, SWEET ETHEREAL ODOR.

Percent Volatiles by Volume

:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACTIVE METALS, FIRES OF METAL HYDRIDES, AND MATERIALS CONTAINING OWN
OXYGEN.

Stability Condition to Avoid:HIGH HEAT ABOVE 1000F, OPEN FLAMES.

Hazardous Decomposition Products:HYDROBROMIC, HYDROCHLORIC, AND
HYDROFLUORIC ACIDS, POSSIBLE FREE HALIDES AND CARBONYL HALIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF

IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS. RECLAIM WHERE POSSIBLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume
responsibility for the suitability of this information to their
particular situation.