

EASTMAN KODAK COMPANY -- 142 4654 FLEXICOLOR BLEACH III, PROCESS C-41, PART A --
6750-01-022-8410

===== Product Identification =====

Product ID:142 4654 FLEXICOLOR BLEACH III, PROCESS C-41, PART A

MSDS Date:11/22/1996

FSC:6750

NIIN:01-022-8410

MSDS Number: BVFYK

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info P

hone Num:716-477-3194/MSDS 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Infor

mation on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 65-70%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM ACETATE (SARA III)
CAS:631-61-8
RTECS #:AF3675000
Fraction by Wt: 15-20%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BROMIDE
CAS:12124-97-9
RTECS #:BO9170000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (SARA III)
CAS:64-19-7
RTECS #:AF122500
0
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT): NOT GIVEN
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD
FOR RECOMMENDED HANDLING. MAY CAUSE TRANSIENT EYE IRRIT

ATION. LOW

SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW
INGESTION HAZARD.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.

Effects of Overexposure:EYE IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. G
ET MEDICAL

ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH
WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH
SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR.
INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION.
NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:USE

APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY PRODUCE
HAZARDOUS DECOMPOSTION PRODUCTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS
OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT
MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WA
STE. CLEAN

SURFACE TO REMOVE RESIDUA L CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. WASH
THOROUGHLY AFTER HANDLING. KEEP FROM CONTACT WITH OXIDIZING
MATERIALS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:KEEP AWAY FROM INCOMPATIBLE MATERIALS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Pro

tection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. KEY1:C3.

===== Physical/Chemical Properties =====

HCC:C1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.108

pH:4.7

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID, STRONG VINEGAR ODOR

Percent Volatiles

by Volume:65-70%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:HYDROGEN BROMIDE, AMMONIA, CHLORAMINE, NITROGEN OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATI

ONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH
< 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person
utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.