View NSN Online: https://aerobasegroup.de/nsn/6750-01-022-8410

EASTMAN KODAK COMPANY -- 142 4654 FLEXICOLOR BLEACH III, PROCESS C-41, PART A -- 6750-01-022-8410

Product ID:142 4654 FLEXICOLOR BLEACH III, PROCESS C-41, PART A MSDS Date:11/22/1996 FSC:6750 NIIN:01-022-8410 MSDS Number: BVFYK === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info P hone Num:716-477-3194/MSDS 800-242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======== Composition/Infor

mation on Ingredients =========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 65-70% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM ACETATE (SARA III) CAS:631-61-8 RTECS #:AF3675000 Fraction by Wt: 15-20% Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BROMIDE CAS:12124-97-9 RTECS #:BO9170000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF122500 0 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:ORAL LD50 (RAT): NOT GIVEN Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY CAUSE TRANSIENT EYE IRRIT ATION. LOW SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW **INGESTION HAZARD.** Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure: EYE IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. G ET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. Flash Point:NONFLAMMABLE Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSTION PRODUCTS. Spill Release Procedures: FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WA STE. CLEAN SURFACE TO REMOVE RESIDUA L CONTAMINATION. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED. Other Precautions: KEEP AWAY FROM INCOMPATIBLE MATERIALS.

Respiratory Pro

tection:NONE SHOULD BE NEEDED.
Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.
Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR
USING TOILET FACILITIES.
Supplemental Safety and Health REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. KEY1:C3.

HCC:C1 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.108 pH:4.7 Evaporation Rate & amp; Reference:NOT GIVEN Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID, STRONG VINEGAR ODOR Percent Volatil es by Volume:65-70%

Stability Indicator/Materials to Avoid:YES BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:HYDROGEN BROMIDE, AMMONIA, CHLORAMINE, NITROGEN OXIDES

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATI

ONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.