View NSN Online: https://aerobasegroup.de/nsn/5915-01-085-1762

EASTMAN KODAK COMPANY -- 165 1900 INDUSTREX DEVELOPER REPLENISHER, WORKING SOLUTION -- 6750-01-085-1762

Product ID:165 1900 INDUSTREX DEVELOPER REPLENISHER, WORKING SOLUTION MSDS Date:11/18/1992 FSC:6750 NIIN:01-085-1762 MSDS Number: BVFYS === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650-111 5 Country:US Info Phone Num:716-477-3194 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

======= Composition/Information on Ingredients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 85-90% Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM S

ULFITE CAS:10117-38-1 RTECS #:WT3530000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA III) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9394 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:ACETIC ACID,POTASSIUM SALT/POTASSIUM ACETATE CAS:127-08-2 RTECS #:AJ3325000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE CAS:111-30-8 RTECS #:MA2450000 Fr action by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:C 0.2 PPM ACGIH TLV:C 0.2 PPM; 9394

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE: CAUSES IRRITATION. SKIN: CAUSES IRRITATION. MAY CAUSE ALLERGIC REACTION. INHALED: EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. HOWEVER GLUTERALDEHYDE IS A RESPIRATORY IRRITANT AND MAY AGGRA VATE ASMATIC DISORDERS. INGESTED: EXPECTED TO BE A LOW INGESTION HAZARD. Explanation of Carcinogenicity:MFR LISTED NO INFORMATION ABOUT THE CARCINOGENICITY OF THIS MATERIAL. HMIS DOES NOT EXPECT IT TO BE CARCINOGENIC. Effects of Overexposure: EYE: IRRITATION. SKIN: IRRITATION. MAY CAUSE ALLERGIC REACTION. INHALED: EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. MAY AGGRAVATE ASMATIC DISORDERS. INGESTED: EXPECTED TO BE A LOW INGESTION HAZ ARD. Medica

I Cond Aggravated by Exposure:PRE-EXISTING ASTHMATIC DISORDERS.

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. GET IMMEDIATE MEDICAL ATTENTION. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. GET MEDICAL CARE FOR ANY SKIN REACTION. I NHALED:REMOVE TO FRESH AIR. IF SYMPTOMSPERSIST, GET MEDICAL CARE. INGESTED:DRINK 1-2 GLASSES OF WATER AND GET IMMEDIATE MEDICAL ATTENT

ION.

Flash Point:NONE Extinguishing Media:NOT RELEVANT Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. Neutralizing Agent: NO INFORMATION GIVEN BY MFR ON MSDS.

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED.KEEP AWAY FROM INCOMPAITBLE SUBSTANCES.AVOID CONTACT W/EYES, SKIN, AND CLOTHING USE WITH ADEQUATEVENTILATION.
Other Precautions:WASH THOROUGHLY AFTER HANDLING. USE NONALKALINE (ACID) TYPE HAND CLEANER,REGULAR CLEANING OF WORKING SURFACES,GLOVES ETC, WILL HELP MINIMIZE THE POSSIBILITY OF SKIN REACTION. NO SPECIAL
PRECAUTIONS SH OULD BE NEEDED UNDER NORMAL CONDITIONS.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPROVED ORGANIC VAPOR RESPIRATOR MUST BE WORN. IF RESPIRATORS ARE WORN, COMPLY WITH OSHA STANDARD 29CFR1910.134. Ventilation: USE PROCESS ENCLOSURES, LOCAL EXHAUST OR OTHER ENGINEERING

CONTROLS TO MAINTAIN EXPOSURE BELOW RECOMM

ENDED LIMITS.
Protective Gloves: IMPERVIOUS GLOVES
Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES
Other Protective Equipment: WEAR PROTECTIVE CLOTHING APPROPRIATE FOR THE RISK OF EXPOSURE. EYE BATH, WASHING FACILITIES & SAFETY SHOWER.
Work Hygienic Practices: MFR: ? HMIS: USE STRICT CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY EXPOSURE. WASH THOROUGHLY BEFORE EATING OR DRINKING.
Supplemental Safety and Health THIS MSDS COVERS THE 200 GALLONS OF WORKING SOLUTION MADE FROM P/N IND

A.

HCC:N1 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:18 MM Vapor Density:0.6 Spec Gravity:1.09 pH:10.4 Solubility in Water:COMPLETE Appearance and Odor:YELLOW ORANGE LIQUID, SLIGHT ODOR Percent Volatiles by Volume:85

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:HIGH TEMPERATURES AND FLAMES

Hazardous Decomposition Products:SULFUR DIOXIDE Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United Stat es of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.