View NSN Online: https://aerobasegroup.de/nsn/8030-00-247-2525

Product ID:GASKET SEALANT NO. 1, CDA 150 MSDS Date:11/12/1993 FSC:8030 NIIN:00-247-2525 MSDS Number: BVGJB === Responsible Party === Company Name: CHEMENCE, INC Address:6425 INDUSTRIAL WAY **City:ALPHARETTA** State:GA ZIP:30201 Country:US Info Phone Num:404-664-6624 Emergency Phone Num:404-664-6624 Pre parer's Name: JAY TATE CAGE:CLEME === Contractor Identification === Company Name: CHEMENCE, INC Address:6425 INDUSTRIAL WAY City:ALPHARETTA State:GA ZIP:30201 Country:US Phone:404-664-6624 CAGE:CLEME Company Name: VERSATILE INDUSTRIAL PRODUCTS, INC CAGE:6Z186

Ingred Name:CLAY CAS:1332-58-7 RTECS #:GF1670500 Fraction by Wt: 50-55% Other REC Limits:NONE RECOMMENDED

Ingred Name:ROSIN CAS:8050-09-7 Fraction by Wt: 20-25% Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOPROPYL ALCOHOL CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED OSHA PEL:400 PPM;STEL 500 PPM ACGIH TLV:400 PPM;STEL 500 PPM

Ingred Name:VEGETABLE OIL CAS:68439-93-0 Fraction by Wt: 5-10% Other REC Limits:* 5 MG/M3(MIST RESP) OSHA PEL:15 MG/M3(MIST DUST)* ACGIH TLV:10 MG/M3 (MIST)

Ingred Name:SOYBEAN DERIVATIVE CAS:8002-43-5 Fraction by Wt: 1-3% Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE CAS:1309-37-1 RTECS #:NO7400000 Fraction by Wt: 0.1-0.5% Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC COMPOUND (EPA METHOD 24): 231 GRAMS PER LITER RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:MODERATELY TOXIC BY INGESTION. EYE IRRITANT. Effects of Overexposure:VAPOR ABOVE TLV IS IRRITATING TO EYES, NOSE,

AND THRO

AT AND CAN CAUSE HEADACHE, DIZZINESS, NAUSEA
Medical Cond Aggravated by Exposure:SKIN, EYE, AND RESPIRATORY
DISORDERS.

First Aid:INGESTION: INDUCE VOMITING. OBTAIN MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN MEDICAL ATTENTION. SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH AT LEAS T 15 MINUTES WITH WATER. OBTAIN MEDICALATTENTION.

====== Fire

Flash Point Method:TCC Flash Point:60.0F,15.6C Lower Limits:2 Upper Limits:12 Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL Fire Fighting Procedures:IRRITATING ORGANIC VAPORS Unusual Fire/Explosion Hazard:FORMS IRRITATING ORGANIC VAPOR BY FIRE OR THERMAL DECOMPOSITION.

Spill Release Procedures:REMOVE SOURCES OF IGNITION. MAINTAIN ADEQUATE VENTILATION. SCRAPE UP AS MUCH AS POSSIBLE AND STORE IN A CLOSED CONTAINERS UNTIL DISPOSAL. RESIDUE MAY CLEANED WITH ISPROPYL ALCOHOL.

Handling and Storage Precautions:STORE AWAY FROM HEAT AND FLAME. Other Precautions:AVOID PROLONGED BREATHING OF VAPORS. KEEP AWAY FROM EYES.

======= Exposure Controls/Personal Protection ==========

Ventilation:MUST BE ADEQUATE TO AVOID EXCEEDING TLV. Protective Gloves:RUBBER OR PLASTIC GLOVES Eye Pr otection:SAFETY GLASSES OR GOGGLES. Supplemental Safety and Health

HCC:F2 Boiling Pt:B.P. Text:180F,82C Vapor Pres:33 @ 68F Vapor Density:2.07 Spec Gravity:1.5 @ 77F Evaporation Rate & amp; Reference:7.7 (ETHER=1) Solubility in Water:PARTIAL Appearance and Odor:RED-BLACK PASTE; ALCOHOLIC ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazard ous Decomposition Products:NONE

Waste Disposal Methods: INCINERATE FOLLOWING EPA AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any perso n utilizing this document should seek competent professional advice to verify and

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.