View NSN Online: https://aerobasegroup.de/nsn/7930-00-298-1947

INDUSTRIAL FLOOR FINISHES -- WAX, GENERAL PURPOSE, SOLVENT TYPE -- 7930-00-298-1947

Product ID:WAX, GENERAL PURPOSE, SOLVENT TYPE MSDS Date:06/13/1994 FSC:7930 NIIN:00-298-1947 MSDS Number: BVGLF === Responsible Party === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRINGS ROAD City:BEDFORD State:MA ZIP:01730 Country:US Info Phone Num:508-667-5161 Emergenc y Phone Num:800-255-3924 Preparer's Name: TPITROLFFY CAGE:INDUS === Contractor Identification === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRINGS RD City:BEDFORD State:MA ZIP:01730 Country:US Phone:1-617-667-5161 CAGE:INDUS Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 79% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM

ACGIH TLV:100 PPM

======= Hazards Identificati

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE IRRITATION, DRYING OF SKIN, DIZZINESS, NAUSEA. VAPORS MAY BE NARCOTIC. CHRONIC: RESPIRATORY TRACT IRRITATION, COULD DAMAGE LIVER AND KIDNEY. Effects of Overexposure: IRRITATION AND REDNESS OF SKIN, DIZZY FEELING, PALE AND NAUSEOUS. Medical Cond Aggravated by Exposure: KIDNEY, LIVER AND LUNG PROBLEMS ================= First Aid: EYE & SKIN CONTACT: FLUSH WITH PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR, BEGIN ARTIFICIAL RESPIRATION IF NEEDED. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION. Flash Point Method:TCC Flash Point:103F,39C Autoignition Temp: Autoignition Temp Text: 510 F Lower Limits:0.7 Upper Limits:6.0 Extinguishing Media:CO2, FOAM, DRY CHEMIC AL Fire Fighting Procedures: COOL CONTAINERS WITH WATER, USE SELF-CONTAINED BREATHING APPARATUS, BURNING PRODUCT IS TOXIC. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS, OPEN FLAME. Spill Release Procedures: COLLECT MATERIAL INTO METAL CONTAINER. AVOID SPARKS, FLAME, HOT SURFACES. WIPE OFF RESIDUE WITH RAG. =================== Handling and Storag Handling and Storage Precautions: COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE ADEQUATE VENTILATIONS. AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINERS CLOSED. Other Precautions: STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY KEEP OUT OF REACH OF CHILDREN. 

Respiratory Protection: USE SELF-CONTAINED BREATHING APPARATUS FOR CONCENTRATION ABOVE THRESHOLD LIMIT

VALVE.
Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL: ASSURE FRESH AIR CIRCULATION.
Protective Gloves:RECOMMENDED: RUBBER
Eye Protection:RECOMMENDED: GOGGLES
Other Protective Equipment:EYE BATH AND SHOWER.
Work Hygienic Practices:DO NOT EAT/DRINK OR SMOKE NEXT TO MATERIAL.
WASH HANDS/FACE AFTER WORK.
Supplemental Safety and Health

Boiling Pt:B.P. Text:320F,160C Melt/Freeze Pt:M.P/F.P Text:130F,54C Vapor Pres:2.0 Vapor Density:4.7 Spec Gravity:0.8 (WATER=1) Evaporation Rate & amp; Reference:0.21 (BU AC=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:WAXY PASTE, SOLVENT ODOR Percent Volatiles by Volume:72-80

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

\_\_\_\_\_

Waste Disposal Methods:RECYCLE, INCINERATE, OF USE HAZARDOUS WASTE MANAGEMENT FACILITY FOR DISPOSAL ACCORDING TO STATE AND FEDERAL REGULATIONS. EPA WASTE NO D001 (IGNITABLE WASTE).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information t o be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.