

LENMAR, INC -- Y-850 MIL-P-23377F, PRIMER COATINGS, COMP B

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 01-312-1169  
MSDS Date: 07/30/1993  
MSDS Num: BVGRR  
Product ID: Y-850 MIL-P-23377F, PRIMER COATINGS, COMP B  
MFN: 02  
Kit Part: Y  
Responsible Party  
Cage: 36489  
Name: LENMAR, INC  
Address: 150 SOUTH CALVERTON  
ROAD  
City: BALTIMORE MD 21223  
Info Phone Number: 401-947-2300  
Emergency Phone Number: 401-358-5524/401-947-2300  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: OBDY9  
Name: LENMAR, INC.  
Address: 150 SOUTH CALVERTON ROAD  
City: BALTIMORE MD 21223  
Phone: 410-947-2300/410-358-5524  
Cage: 36489  
Name: LENMAR, INC  
Address: 150 SOUTH CALVERTON ROAD  
City: BALTIMORE MD 21223  
Phone: (301) 94  
7-2300

=====  
Item Description Information  
=====

Item Name: PRIMER COATING  
=====

=====  
Ingredients  
=====

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (METHYLBENZENE) (SARA III) (VAPOR PRESSURE 22 MM HG @ 20C)  
% Wt: 35-45  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 100 PPM  
E

PA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----  
Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE (DIMETHYLBENZENE) (SARA III) (VAPOR PRESSURE 10 MM HG @ 20C)  
% Wt: 26-36  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----  
Cas: 71-36-3  
RTECS #: EO1400000  
Name: N-BUTANOL (1-BUTANOL) (VAPOR PRESSURE 5.5 MM HG @ 20C)  
% Wt: 5-15  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 50 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS

-----  
Cas: 68410-23-1  
Name: POLYAMIDE RESIN  
% Wt: 14-24  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Effects of Exposure: INHAL: ANESTHETIC, RESPIRATORY TRACT IRRITATION OR ACUTE NE

ROUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS, COMA). SKIN OR EYE: PRIMARY IRRITANT. REPORTS ASSOCIATE REPEATED/PROLONGED EXPOSURE W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. CONCENTRATING & INHALING PRODUCT-HARMFUL/FATAL.

Signs And Symptions Of Overexposure: NOTE TO PHYSICIAN: IF MORE THAN 2.0 ML/KG HAS BEEN INGESTED & VOMITING HAS NOT OCCURRED, IMPLEMENT EMESIS W/SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF

SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS BEFORE EMESIS, CONSIDER GASTRIC LAVAGE USING A CUFFED ENDOTRACHEAL TUBE.

Medical Cond Aggravated By Exposure: NONE KNOWN

First Aid: INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT.

CALL DR. EYES: FLUSH IMMEDIATELY W/RUNNING WATER FOR AT LEAST 15 MINUTES. SEE DR FOR DEFINITIVE MED TREATMENT. SKIN: WASH PROMPTLY W/WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE. CONSULT DR. INGESTION: CAL

L

PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. IF CONSCIOUS GIVE 1-2 GLASSES WATER. DON'T INDUCE VOMITING.

=====  
Handling and Disposal  
=====

Spill Release Procedures: REMOVE IGNITION SOURCES. MOP UP SPILLS/ADD ABSORBENT. USE NON-SPARK TOOLS. USE ADEQUATE VENT. MOVE LEAKING CONTAINERS OUTDOORS, OBSERVING PRECAUTION W/REGARD TO FIRE, SPARK, FLAME HZD. RUNOFF TO WATER WAY CREATES FIRE HZ

D. NOTIFY FIRE & HLTH AGENCIES.

Waste Disposal Methods: RECLAIM MATEIAL, INCINERATE OR USE SANITARY LANDFILL METHOD OF DISPOSAL, IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. SEAL DRUMS TIGHTLY.

Handling And Storage Precautions: STORE IN VENTED WAREHOUSE.KEEP OUT OF DIRECT SUNLIGHT/OTHER HEAT SOURCE.KEEP CNTNR CLSD.NO SMOKING.DON'T EAT(HARMFUL/FATAL).GROUND CNTNR WHEN POURING.

Other Precautions: AVOID FREE FALL OF LIQ >FEW INCHES. C LOSE CNTNR AFTER

USE. DON'T TRANSFER TO BOTTLES OR UNLABELED CNTNRS.AVOID CONTACT W/SKIN & BREATHING VAPORS.EXTINGUISH PILOT LIGHTS.USE NON-SPARK TOOLS & EXPLOSION PROOF EQUIP. KEEP FROM HEAT, SPARK, \*

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: SCC

Flash Point Text: 53.0F,11.7C

Lower Limits: 1.0

Extinguishing Media: FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED CLSD CNTNRS.AVOID EXPOSURE TO FUMES; GET IMMED MED AID FOR PERSON EXPOSED. WEAR SCBA WHEN IN ENCLOSED AREAS.

Unusual Fire/Explosion Hazard: TOXIC GAS EVOLVED. KEEP CNTNRS CLSD. KEEP FROM HEAT/IGNIT SOURCES. CLSD CNTNR MAY EXPLODE W/HEAT. DON'T APPLY TO HOT SRFCs. DON'T STORE/MIX W/STRONG OXIDANTS.

=====  
Control Measures  
=====

Respiratory Protection: IN OPEN AREAS, USE MECHANICAL FILTER. IN RESTRICTED VENT AREA, USE CHEM/MECHAN FILTER. IN CONFINED AREAS, USE AIRLINE-TYPE RESPRTRS OR HOODS. WEAR FITTED RESPIRATOR DURING & AFTER APPLICATION UNLESS A IR MONITORING SHOWS VAPOR BELOW TLV/PEL.

Ventilation: USE SPRAY BOOTH. GENERAL DILUTION OR LOCAL EXHAUST TO KEEP CONCENTRATION OF MOST HAZARDOUS INGREDIENT BELOW TLV.

Protective Gloves: REQUIRED FOR PROLONGED/REPEATED CONTACT

Eye Protection: SPLASH PROOF GOGGLES

Other Protective Equipment: NONE REQUIRED

Work Hygienic Practices: NONE REQUIRED

Supplemental Safety and Health: \* PRECAUTIONS CONT'D: & OPEN FLAME. DO NOT APPLY TO HOT SURFACES. USE W/ADEQUATE VENTILATION. HANDLE IN ACCORD W/POTENTIALITIES OF BOTH RESIN COMPONENT & CURING AGENT WHEN MIXED. EMPTY CONTAINER RETAI N RESIDUE-DANGEROUS. DON'T PRESSURIZE,CUT,WELD,BRAZE,SOLDER,DRILL,ETC. DONT ATTEMPT TO CLEAN. FOR TANKER SEE ANSI Z49.1.

Physical/Chemical Properties

HCC: F3

B.P. Text: 231 TO 281F

Vapor Density: > AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 83

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: TEMPERATURES IN EXCESS OF 150F IN CLOSED CO

NTAINER. EXPOSURE TO HEAT, SPARKS, OPEN FLAMES AND HOT SURFACES.

Materials To Avoid: OXIDIZING AGENTS

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE.

Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information  
=====

=====  
Responsible Party Cage: 36489  
Trans ID NO: 124329  
Product ID: Y-850 MIL-P-23377F, PRIMER COATINGS, COMP B  
MSDS Prepared Date: 07/30/1993  
Review Date: 09/26/1994  
MFN: 2  
Multiple KIT Number: 0  
Kit Part IND: Y  
Review IND: Y  
=====

=====  
Detail DOT Information  
=====

DOT PSN Code: LFD  
DOT Proper Shipping Name: PAINT  
DOT PSN Modifier: INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHEL  
LAC SOLUTIONS,  
VARNISH, POLISH, LIQUID FILLER, AND LIQUID LACQUER BASE  
Hazard Class: 3  
UN ID Num: UN1263  
DOT Packaging Group: II  
Label: FLAMMABLE LIQUID  
Special Provision: B52,T7,T30  
Packaging Exception: 150  
Non Bulk Pack: 173  
Bulk Pack: 242  
Max Qty Pass: 5 L  
Max Qty Cargo: 60 L  
Vessel Stow Req: B  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: LCP  
IMO Proper Shipping Name: PAINT OR PAINT RELA

TED MATERIAL

IMO PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT THINNING OR REDUCING COMPOUND) o

IMDG Page Number: 3268

UN Number: 1263

UN Hazard Class: 3.2

IMO Packaging Group: I/II \*

Subsidiary Risk Label: -

EMS Number: 3-05

MED First Aid Guide NUM: 310

=====  
Detail IATA Information  
=====

IATA PSN Code: SXI

IATA UN ID Num: 1263

IATA Proper Shipping Name: PAINT

IATA PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE)

IATA UN Class: 3

IATA Label: FLAMMABLE LIQUID

UN Packing Group: II

Packing Note Passenger: 305

Max Quant Pass: 5L

Max Quant Cargo: 60L

Packaging Note Cargo: 307

Exceptions: A7, A72

=====  
Detail AFI Information  
=====

AFI PSN Code: SXI

AFI Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL

AFI PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT THINNING OR REDUCING COMPOUNDS)

AFI Hazard Class: 3

AFI UN ID NUM: UN1263

AFI Packing Group: II

Special Provisions: P5

Back Pack Reference: A7.3

=====  
HAZCOM Label  
=====

=====

Product ID: Y-850 MIL-P-23377F, PRIMER COATINGS, COMP B

Cage: 36489

Company Name: LENMAR, INC

Street: 150 SOUTH CALVERTON ROAD

City: BALTIMORE MD

Zipcode: 21223

Health Emergency Phone: 401-358-5524 NIGHT/401-947-2300 DAY

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: INHAL: ANESTHETIC, RESPIRATORY TRACT IRRITATION OR ACUTE NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS, COMA). SKIN OR EYE: PRIMARY IRRITANT. REPORTS ASSOCIATE REPEATED/PROLONGED EXPOSURE W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. CONCENTRATING & INHALING PRODUCT-HARMFUL/FATAL. NOTE TO PHYSICIAN: IF MORE THAN 2.0 ML/KG HAS BEEN INGESTED & VOMITING HAS NOT OCCURRED, IMPLEMENT EMESIS W/SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS BEFORE EMESIS, CONSIDER GASTRIC LAVAGE USING A CUFFED ENDOTRACHEAL TUBE.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.