

HACH CO. -- LIMESTONE -- 6630-00-133-0697

=====
Product Identification
=====

Product ID:LIMESTONE
MSDS Date:09/12/1993
FSC:6630
NIIN:00-133-0697
Kit Part:Y
MSDS Number: BVGYN
=== Responsible Party ===
Company Name:HACH CO.
Box:389
City:LOVELAND
State:CO
ZIP:80539
Country:US
Info Phone Num:800-227-4224
Emergency Phone Num:800-227-4224 OR 303-623-5716
CAGE:91224

=== Contractor Identification ===

Com
pany Name:HACH CO
Address:5600 LINDBERGH DR
Box:389
City:LOVELAND
State:CO
ZIP:80539
Country:US
Phone:970-669-3050/ 303-623-5716
CAGE:91224
Company Name:HACH COMPANY
Address:100 DAYTON RD.
Box:907
City:AMES
State:IA
ZIP:50010
Country:US
Phone:800-227-4224
CAGE:4T252

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EXPOSURE MAY CAUSE EYE &
RESPIRATORY TRACT IRRITATION. EXCESSIVE ORAL DOSES MAY CAUSE
ALKALOSIS. CHRONIC: NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF
0.1% OR GREATER IS LISTED AS A
CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES: BURNS, TEARING, PAIN, BLURRED VISION,
REDNESS. INHALED: COUGHING, SNEEZING.
Medical Cond Aggravated by Exposure:NONE REPORTED.

=====
===== First Aid Measures =====
=====

First Aid:EYE/SKIN CONTACT-IMMEDIATELY FLUSH EYES WITH WATER FOR 15
MINUTES. CALL PHYSICIAN. FLUSH SKIN WITH LOTS OF WATER. REMOVE
CONTAMINATED CLOTHES. INGESTED-IF CONSCIOUS, GIVE 1-2 GLASSES OF
WATER. DO NOT INDUCE VO
MITING! CALL PHYSICIAN IMMEDIATELY.
INHALED: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====
=====

Extinguishing Media:NOT APPLICABLE. DLA-HMIS: MEDIA APPROPRIATE FOR
SURROUNDING FIRE.
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:
FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING
POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:MAY EMIT TOXIC FUMES OF CALCIUM OXIDE AND
CARB
ON DIOXIDE IN FIRE.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:SWEEP UP SPILL. AVOID BREATHING MATERIAL.
DISSOLVE IN WATER. FLUSH DOWN DRAIN WITH EXCESS OF WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A COOL, DRY
PLACE.
Other Precautions:AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER
HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:PROVIDE ADEQUATE VENTILATION.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:LAB GRADE GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:

EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

KEY1=B3. CHANGE: 8745.

===== Physical/Chemical Properties =====

HCC:C1

Melt/Freeze Pt:M.P/F.P Text:1517F,825C

Decomp Temp:Decomp Text:1517F,825C

Spec Gravity:2.711

Evaporation Rate & Reference:N/K (N-BUTYL ACETATE=1)

Solubility in Water:

SLIGHT

Appearance and Odor:WHITE, ODORLESS POWDER.

Corrosion Rate:0.0 IPY

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG MINERAL ACIDS, FLUORINE, MAGNESIUM WITH HYDROGEN.

Stability Condition to Avoid:CONTACT WITH STRONG MINERAL ACIDS, FLUORINE, MAGNESIUM WITH HYDROGEN.

Hazardous Decomposition Products:CALCIUM OXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal

Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.