View NSN Online: https://aerobasegroup.de/nsn/5970-00-682-8999

MINNESOTA MINING & MFG CO -- SCOTCHCAST BRAND 4 ELECTRICAL INSULATING RESIN PART B -- 5970-00-682-8999

Product ID:SCOTCHCAST BRAND 4 ELECTRICAL INSULATING RESIN PART B MSDS Date:08/19/1992 FSC:5970 NIIN:00-682-8999 Kit Part:Y **MSDS Number: BVHDW** === Responsible Party === Company Name: MINNESOTA MINING & MFG CO Address:3M CTR 224-2S-25 City:ST. PAUL State:MN ZIP:551 44-1000 Country:US Info Phone Num:612-733-1110 Emergency Phone Num:612-733-1110 CAGE:76381 === Contractor Identification === Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381

Ingred Name:NONYLPHENOL CAS:25154-52-3 RTECS #:SM5600000 Fraction by Wt: 35-40% Other REC Limits:NONE RECOMMENDED

Ingred

Name:AMINE/EPOXY RESIN ADDUCT CAS:70776-37-3 Fraction by Wt: 25-35% Other REC Limits:NONE RECOMMENDED

Ingred Name:EXTRACTS, HEAVY NAPHTHENIC DISTILLATE SOLVENT CAS:64742-11-6 RTECS #:PY8042000 Fraction by Wt: 13-16% Other REC Limits:NONE RECOMMENDED OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:AROMATIC HYDROCARBONS, C12-20 CAS:70955-17-8 Fraction by Wt: 3-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:N-AMINOETHYLPIPERAZINE CAS:140-31-8 RTECS #:TK8050000 Fraction by Wt: 10-13% Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL CAS:90-72-2 RTECS #:SN3500000 Fraction by Wt: 2-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 0.1-1.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9394

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES

OSHA:NO Health Hazards Acute and Chronic:ACUTE: MAY IRRITATE SKIN, EYES, OR RESPIRATORY SYSTEM. INGESTION MAY CAUSE GI TRACT IRRITATION. INHALATION AND INGESTION MAY CAUSE (UNLIKELY) KIDNEY/LIVER/CNS EFFECTS. CHRONIC: PROLONGED OR REPEATED E XPOSURE MAY CAUSE SKIN SENSITIZATION.

Explanation of Carcinogenicity:CARBON BLACK IS LISTED BY IARC (3) AS HAVING INSUFFICIENT DATA/UNCLASSIFIABLE TO CARCINOGENICITY. Effects of Overexposure:INHALED/INGESTED: BLOOD IN URINE, BACK PAIN,

YELLOW SKIN, TENDERNESS OF UPPER ABDOMEN, EMOTIONAL CHANGES, LOSS OF COORDINATION, TREMORS AND SENSORY LOSS. INHALATION: COUGHING, WHEEZING, SHORTNESS OF B REATH. EYES: REDNESS, TEARING, ITCHING.SKIN: RENESS, RASH, ITCHING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE: FLUSH EYE 15 MINUTES WITH PLENTY OF WATER. SKIN: WASH SOAP & WATER. INHALED: REMOVE TO FRESH AIR. GIVE ARTIFICIAL

RESPIRATION OR OXYGEN AS REQUIRED. INGESTED: IF CONSCIOUS GIVE TWO GLASSES WATER, INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY ALL CASES IF SYMPTOMS PERSIST.

Flash Point Method:PMCC Flash Point:230F,110C Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEMICALS Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:NO UNUSUAL FIRE OR EXPOSION HAZARDS ARE ANTICIPATED.

Spill Release Procedures: ABSORB SPILL WITH ABSORBENT, PLACE IN CLOSABLE CONTAINER FOR DISPOSAL. Neutralizing Agent: NONE

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED AREAS. STORE IN A COOL, DRY PLACE. Other Precautions:NONE SPECIFIED BY MANUFACTURER.

======== Exposure Controls/Personal Prote

ction ===========

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER. NONE NORMALLY REQUIRED. IF REGULATORY LIMITS EXCEEDED; USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. Ventilation:USE ADEQUATE MECHANICAL VENTILATION. Protective Gloves:NONE NORMALLY REQUIRED. Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOT HING BEFORE REUSE. Supplemental Safety and Health PART B OF TWO-PART A/B KIT. UPDATE PER 3M MSDS DOC #00-617-3082 DATED 19AUG1992. KEY1: N1.

HCC:N1 Spec Gravity:0.98 Viscosity:3500 CPS Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK LIQUID; AMINE ODOR Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES NOT APPLICABLE. Stabi lity Condition to Avoid:NOT APPLICABLE.

Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN

Waste Disposal Methods: INCINERATE OR BURY IN SECURE LANDFILL IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoeve r, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.