

SHELL OIL COMPANY -- SHELL TELLUS OIL 68 -- 9150-00-966-8835

=====
Product Identification
=====

Product ID:SHELL TELLUS OIL 68

MSDS Date:11/16/1992

FSC:9150

NIIN:00-966-8835

MSDS Number: BVHFT

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:1 SHELL PLAZA

Box:2463

City:HOUSTON

State:TX

ZIP:77001

Country:US

Info Phone Num:713-241-4819

Emergency Phone Num:713-473-9461 (24 HOUR EMERGENCY)

CAGE:54527

=== Contractor Identification ===

Company Name:SHELL OIL COMPANY

Box:2463

City:HOUSTON

State:TX

ZIP:77210

Country:US

Phone:800-231-6950

CAGE:54527

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD), HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 0-99% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:MINERAL OIL, PET

ROLEUM DISTILLATE, SOLVENT DEWAXED (MILD),
HEAVY PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Fraction by Wt: 0-99% %

Other REC Limits:NONE RECOMMENDED

Ingred Name:MINOR ADDITIVES

Fraction by Wt: < 2%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV 5 MG/M3 OIL MIST.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRACTICALL

Y NON-IRRITATING TO THE

EYES. PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS. VAPORS
MAY IRRITATE THE NOSE, THROAT AND UPPER RESPIRATORY TRACT.

INGESTION MAY CAUSE GI DISTURBANCES. ACCIDENTAL RELEASE UNDER HIGH
PRESSURE APPLICATIONS MAY RESULT IN INJECTION OF OIL INTO THE SKIN
CAUSING LOCAL NECROSIS.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.

Effects of Over

exposure:EYE IRRITATION, SKIN IRRITATION, DERMATITIS,

UPPER RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING, DIARRHEA.
NECROSIS MAY BE EVIDENCED BY DELAYED ONSET OF PAIN AND TISSUE
DAMAGE A FEW HOURS FOLLOWING HIGH PRESSURE INJECTION.

Medical Condition Aggravated by Exposure:PRE-EXISTING SKIN AND/OR

RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS
PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MIN

UTES WHILE HOLDING EYELIDS

OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING.

WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL
ATTENTION. IF MATERIAL IS INJECTED UNDER THE SKIN, GET MEDICAL
ATTENTION PROMPTLY. INHALATION: REMOVE TO FRESH AIR. RESTORE
BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE
VOMITING. CONTACT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:37

0F,188C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM. DO NOT USE A DIRECT STREAM OF WATER.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT AND CAN BE REIGNITED. TOXIC GASES ARE RELEASED DURING COMBUSTION.

=====
Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. EVACUATE AREA. WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. CONTAIN SPILL. STOP LEAK IF CAN DO SO WITHOUT RISK. ABSORB LIQUID WITH SUITABLE ABSORBENT MATERIAL. COLLECT FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

Other Precautions:AVOID SKIN CONTACT. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE LEVELS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO AVOID SKIN CONTACT. AN EMERGENCY EYE WASH STATION AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====
Physical/Chemical Properties =====

=====

HCC:V6

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:-5F,-21C

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:0.8729

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CREAM WHITE LIQUID, SLIGHT HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, OPEN FLAME

Hazardous Decomposition Products:CAR

BON MONOXIDE, CARBON DIOXIDE,
UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.