

MINNESOTA MINING & MFG CO INDUSTRIAL CHEM PRODUCTS -- FC-206CF, LIGHT WATER BRAND
AQUEOUS FILM FORMING FOAM -- 4210-01-056-0883

=====
Product Identification
=====

Product ID:FC-206CF, LIGHT WATER BRAND AQUEOUS FILM FORMING FOAM

MSDS Date:04/14/1995

FSC:4210

NIIN:01-056-0883

MSDS Number: BVHGS

=== Responsible Party ===

Company Name:MINNESOTA MINING & MFG CO INDUSTRIAL CHEM PRODUCTS

Address:3M CTR

C

City:ST PAUL

State:MN

ZIP:55144

Country:US

Info Phone Num:612-733-5454

Emergency Phone Num:612-733-5454

CAGE:28112

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO PERFORMANCE CHEM AND FLUIDS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501

CAGE:28112

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 78-81%

Other REC Limits:NONE SPECIFIED

PECIFIED

Ingred Name:DIETHYLENE GLYCOL MONOBUTYL ETHER

CAS:112-34-5

RTECS #:KJ9100000

Fraction by Wt: 10 +/-5%

Other REC Limits:NONE SPECIFIED

Ingred Name:FLUOROALKYLAMIDE DERIVATIVE

Fraction by Wt: 1 - 2%

Other REC Limits:NONE SPECIFIED

Ingred Name:ALKYL SULFATE SALTS

Fraction by Wt: 1 - 5%

Other REC Limits:NONE SPECIFIED

Ingred Name:1H-BENZOTRIAZOLE,METHYL-

CAS:29385-43-1

RTECS #:DM1300000

Fraction by Wt: 0 - 0.1%

TRIETHANOLAMINE)
CAS:102-71-6
RTECS #:KL9275000
Fraction by Wt: 0.1-1.0%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:5 MG/M3

Ingred Name:UREA
CAS:57-13-6
RTECS #:YR6250000
Fraction by Wt: 3 - 7%
Other REC Limits:NONE SPECIFIED

Ingred Name:PERFLUOROALKYL SULFONATE SALTS
Fraction by Wt: 0.1 - 1%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO
OSHA:NO

Health Hazards Acute and Chronic:MODERATE EYE IRRITATION. MILD SKIN IRRITATION. SKIN MAY ABSORB HARMFUL AMOUNTS. SINGLE OVEREXPOSURE, MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION & IRRITATION (UPPER RESPIRATORY), BLOOD DISORDERS, BONE MARROW DEPRESSION, KIDNEY EFFECTS, LIVER EFFECTS, PULMONARY EDEMA. INGESTION IS NOT A LIKELY ROUTE EXPOSURE.

Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT CARCINOGENICITY. HMIS FOUND NO LISTING & DOES NOT EXPECT IT TO BE CARCINOGENIC.

Effects of Overexposure:EYE:REDNESS, SWELLING, PAIN, TEARING & HAZY VISION. SKIN:REDNESS, SWELLING, & ITCHING. INHALATION:HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS & UNCONSCIOUSNESS. SORENESS OF THE NOSE & THROAT, COUGHING AND SNEEZING.

Medical Cond Aggravated by Exposure:GET IMMEDIATE MEDICAL ATTENTION.

=====
===== First Aid Measures =====

First Aid:EYES:IMMEDI

ATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

GET MEDICAL ATTENTION. SKIN:FLUSH SKIN WITH LARGE AMOUNTS OF WATER.

IF IRRITATION PERSISTS, GET IMMEDIATE MEDICAL ATTENTION.

INHALATION:REMOV E PERSON TO FRESH AIR. IF SYMPTOMS CONTINUE, CALL

A PHYSICIAN. INGESTION:DRINK TWO GLASSES OF WATER. CALL A PHYSICIAN

IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:NONE

Extinguishing Media:PRODUCT IS A FIRE EXTINGUISH
ING AGENT.

Unusual Fire/Explosion Hazard:SEE HAZARDOUS DECOMPOSITION PRODUCTS
SECTION FOR PRODUCTS OF COMBUSTION.

===== Accidental Release Measures =====

Spill Release Procedures:OBSERVE PRECAUTIONS FROM OTHER SECTIONS. COVER
WITH ABSORBENT MATERIAL. COLLECT SPILLED MATERIAL. CLEANUP RESIDUE
WITH WATER. PLACE IN APPROVED METAL CONTAINER.

Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

===== Handling and Storage =====

==

Handling and Storage Precautions:STORE IN A COOL PLACE. STORE AWAY FROM
HEAT. STORE OUT OF DIRECT SUNLIGHT. KEEP CONTAINER DRY. KEEP
CONTAINER IN WELL-VENTILATED AREA.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID BREATHING OF VAPORS, MISTS OR SPRAY.

SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON
AIRBORNE CONCENTRATION OF CONTAMINANTS & I/A/W OSHA REGULATIONS

:

HALF MASK ORGANIC VAPOR RESP IRATOR WITH DUST/MIST PREFILTER.

Ventilation:USE WITH ADEQUATE DILUTION VENTILATION.

Protective Gloves:BUTYL RUBBER GLOVES RECOMMENDED.

Eye Protection:WEAR VENTED GOGGLES.

Other Protective Equipment:MFR GAVE NO INFORMATION ON MSDS.

Work Hygienic Practices:MFR:?. HMIS:USE GOOD CHEMICAL HYGIENE

PRACTICES. AVOID CONTACT IF AT ALL POSSIBLE. WASH THOROUGHLY AFTER
HANDLING.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

=====

HCC:N1

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:30.400 MM

Vapor Density:0.62

Spec Gravity:1

pH:8.50

Evaporation Rate & Reference:< 1 (BUTYL ACETATE = 1)

Solubility in Water:MISCIBLE

Appearance and Odor:CLEAR, AMBER COLORED LIQUID

Percent Volatiles by Volume:90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomp

osition Products:CARBON MONOXIDE, CARBON DIOXIDE,

OXIDES OF NITROGEN, OXIDES OF SULFUR, HYDROGEN CYANIDE, HYDROGEN
FLUORIDE, AMMONIA.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:SLOWLY DISCHARGE SPENT SOL & SMALL AMOUNTS (