

CHEM-TREND INC -- BRITEMOR 600 -- 6850-01-268-6706

=====  
Product Identification  
=====

Product ID:BRITEMOR 600

MSDS Date:02/01/1994

FSC:6850

NIIN:01-268-6706

MSDS Number: BVHKKH

=== Responsible Party ===

Company Name:CHEM-TREND INC

Address:3205 E GRAND RIVER

City:HOWELL

State:MI

ZIP:48843-8552

Country:US

Info Phone Num:517-546-4520

Emergency Phone Num:517-546-4520

CAGE:2W738

=== Contractor Identific

ation ===

Company Name:CHEM-TREND INC

Address:1445 W. MCPHERSON PARK DR

Box:860

City:HOWELL

State:MI

ZIP:48844-0860

Country:US

Phone:800-727-7730

CAGE:2W738

Company Name:DUNN R G ASSOCIATES INC

Address:15104 LEE RD SUITE 203-B

Box:City:HUMBLE

State:TX

ZIP:77396-2078

Country:US

Phone:281-441-2001/FAX: 281-441-7772

CAGE:0A272

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE

CAS:64742-96-7

Fraction by Wt: 0-25%

Other REC Limits:NONE R

ECOMMENDED

Ingred Name:MINERAL OIL

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 0-25%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:EMULSIFIER BLEND

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PHTHALATE ESTER BLEND

Fraction by Wt: 15-25%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PHOSPHATE ESTER BLEND

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-

3

RTECS #:QJ0525000

Fraction by Wt: 212F,>100C

Lower Limits:1

Upper Limits:6

Extinguishing Media:USE FOAM, CARBON DIOXIDE OR DRY CHEMICAL. DO NOT USE WATER.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIRE FIGHTING IN A CONFINED SPACE.

Unusual Fire/Explosion Hazard:USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES. WRONG APPLICATION OF WATER MAY CAUSE BOIL OVER.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL

SPILLS: SOAK UP WITH ABSORBENT MATERIAL.

LARGE SPILLS: ELIMINATE ALL SOURCES OF IGNITION. VAPORS ARE HEAVIER THAN AIR AND MAY SPREAD LONG DISTANCES OR COLLECT IN LOW SPOTS. DIKE AREA TO PREVENT RUNOFF, RECOVER LIQUID, SOAK UP LIQUID.

===== Handling and Storage =====

Handling and Storage Precautions:GROUND ALL EQUIPMENT PUMPING THE PRODUCT. PROTECT FROM STATIC ELECTRICAL SPARKS OR OTHER IGNITION SOURCES. KEEP CONTAINERS OF PRODUCT CLO

SED.  
Other Precautions:PRODUCT MAY STAIN OR SOFTEN RUBBERS AND ORGANIC COATINGS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF THE USE OF A RESPIRATOR IS NECESSARY USE ONLY A MSHA/NIOSH-APPROVED AIR-SUPPLIED RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR.

Ventilation:RECOMMEND THAT ENGINEERING CONTROLS (SUCH AS LOCAL AND/OR MECHANICAL VENTILATION) BE USED TO REDUCE CONCENTRATIONS.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:SAFE

TY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:APPROPRIATE CLOTHING TO AVOID SKIN CONTACT.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING THIS MATERIAL.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:459F,237C

Vapor Pres:1

Vapor Density:>1

Spec Gravity:0.91

Evaporation Rate & Reference: