

MIDWEST FLOOR CARE, INC -- FLOOR STRIPPER WITH AMMONIA--LB 170 -- 7930-01-379-5184
===== Product Identification =====

Product ID:FLOOR STRIPPER WITH AMMONIA--LB 170

MSDS Date:08/09/1993

FSC:7930

NIIN:01-379-5184

MSDS Number: BVNJM

=== Responsible Party ===

Company Name:MIDWEST FLOOR CARE, INC

Address:200 SOUTH 38TH STREET

City:LINCOLN

State:NE

ZIP:68510

Country:US

Info Phone Num:816-471-2560

Emerg

ency Phone Num:816-234-3000

Preparer's Name:TA

CAGE:0YLF6

=== Contractor Identification ===

Company Name:MIDWEST FLOOR CARE, INC

Box:City:LINCOLN

State:NE

ZIP:68503

Country:US

Phone:402-477-2701

CAGE:0YLF6

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIA (SARA III) (VAPOR PRESSURE 545.0 MM HG @ 20C)

CAS:7664-41-7

RTECS #:BO0875000

Fraction by Wt: 1.0%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:35MG/M3;STEL 27MG/M3

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LB

S

Ingred Name:POTASSIUM HYDROXIDE (VAPOR PRESSURE 39.0 MM HG @ 20C)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TRIETHANOLAMINE 99 (VAPOR PRESSURE 0 MM HG @ 20C)
CAS:102-71-6
RTECS #:KL9275000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:15 MG/M3

Ingred Name:SODIUM METASILICATE (VAPOR PRESSURE 0 MM HG @ 20C)
CAS:6834-92-0
RTECS #:VV9275000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENE GLYCOL BUTYL ETHER (SARA III) (SKIN) (VAPOR PRESSURE 0.1 MM HG @ 20C)
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:25 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYE:IRRITATION, EXTREMELY CORROSIVE.
SKIN:HARMFUL IF ABSORBED THRU SKIN. PROLONGED/REPEATED
CONTACT:SEVERE BURNS. ULCERATION & ULTIMATE SCARRING.
INHAL:UNLIKELY. IRRITATING TO MUCOUS MEMBRANES. INGEST :IRRITATION.
CONCENTRATE EXTREMELY CORROSIVE TO MOUTH & THROAT. SEVERE & RAPID
BURNING OF GI TRACT.SEVERE PAIN & VOMIT.
Medical Cond Aggravated by Exposure:NONE REPORTED

===== First Aid Measures =====

First Aid:EYES:IMMED FLUSH W/WATER 15 MIN, LIFTING EYELIDS
OCCASIONALLY. GET MED AID. SKIN:IMMED WASH W/LRG AMOUNTS OF WATER.
REMOVE CONTAMINATED CLOTHING & SHOE

S. WASH BEFORE REUSE. GET MED

AID IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. GIVE
ARTIF RESPRTN IF NOT BREATHING. INGESTION: DON'T INDUCE VOMITING. IF
CONSCIOUS, GIVE LOTS OF WATER/MILK THEN DRINK DILUTED VINEGAR, LEMON
JUICE, GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 140F, 60C

Lower Limits: 1.1

Upper Limits: 25.0

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, WATER FOG

Fire Fighting Procedure

s: FIREFIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard: EXTINGUISH ALL NEARBY SOURCES OF IGNITION
SINCE FLAMMABLE HYDROGEN GAS WILL BE LIBERATED FROM CONTACT WITH
SOME METAL (ALUMINUM, MAGNESIUM, ETC).

===== Accidental Release Measures =====

Spill Release Procedures: WEAR APPROPRIATE PROTECTIVE AND RESPIRATORY
EQUIPMENT. PREVENT SPILLS FROM ENTERING SEWERS, OR ANY UNAUTHORIZED
WATER SYST

EMS. SWEEP UP AND DISPOSE OF IN DOT APPROVED WASTE
CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL-VENTILATED
PLACE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions: ALWAYS OBEY ALL HAZARD WARNINGS AND HANDLE EMPTY
CONTAINERS AS IF THEY WERE FULL.

===== Exposure Controls/Personal Protection =====

Ventilation: SUFFICIENT VENTILATION IN VOLUME AND PATTERN SHOULD BE
PROVI

DED TO KEEP AIR CONTAMINATION < PEL/TLV.

Protective Gloves: HEAVY RUBBER GLOVES NEEDED.

Eye Protection: CHEM GOGGLES W/SIDESHIELD OR FACE SHIELD

Other Protective Equipment: EYE WASH, SAFETY SHOWER AVAILABLE

Work Hygienic Practices: WASH AFTER EACH USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 80 TO 644F

Vapor Density: > AIR

Evaporation Rate & Reference: IS SLOWER THAN ETHER

Solubility in Water: COMPLETE

Appearance and

Odor:BLUE, AMMONIA ODOR
Percent Volatiles by Volume:87.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS MAY PRODUCE VIOLENT REACTION.
Stability Condition to Avoid:PROLONGED CONTACT WITH ALUMINUM, COPPER,
TIN, LEAD OR ZINC MAY LIBERATE FLAMMABLE HYDROGEN GAS.
Hazardous Decomposition Products:NONE KNOWN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH APPROPRIATE FEDERAL,
STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for
the suitability of this information to their
particular situation.