

DEL PAINT MFG -- TT-E-2784 -- 8010-01-381-0243

===== Product Identification =====

Product ID:TT-E-2784  
MSDS Date:10/01/1994  
FSC:8010  
NIIN:01-381-0243  
MSDS Number: BVZSC  
=== Responsible Party ===  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431  
Emergency Phone Num:800-424-9300 CHEMTREC  
Preparer's Name:ONEY FLEMING  
CAGE:39  
934

=== Contractor Identification ===  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:EKTASOLVE EEH SOLVENT  
CAS:1559-35-9  
RTECS #:KK9625000  
Fraction by Wt: 3.32%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BENZYL ALCOHOL  
CAS:100-51-6  
RTECS #:DN3150000  
Fraction by Wt: 3.32%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYL

AMINOETHANOL LOW VOE

CAS:108-01-0

RTECS #:KK6125000

Fraction by Wt: 0.38%

Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 92.98%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 1.8 LB/GL; 211 G/LTR

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and C

Chronic:CAN CAUSE IRRITATION OF RESPIRATORY

PASSAGES.

Effects of Overexposure:INHALATION OF VAPOR OR MIST CAN CAUSE HEADACHES, NAUSEA, IRRITATION OF NOSE, THROAT, AND LUNGS. EYE CONTACT CAN CAUSE SLIGHT IRRITATION. PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISEASE MAY BE AGGRAVATED BY EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LARGE

AMOUNTS OF WATER FOR 15

MINUTES, CONSULT PHYSICIAN IF IRRITATION PERSISTS. SKIN CONTACT: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. INGESTION: IF SWALLOWED, GIVE 2 GLASSES OF WATER TO DRINK, CONSULT PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>212F,>100C

Autoignition Temp:Autoignition Temp Text:216 F

Lower Limits:NONE

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting P

rocedures:WEAR SELF CONTAINED BREATHING APPARATUS  
(PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL  
PROTECTIVE GEAR.  
Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 100C. POLYMER  
FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY,  
USE CARE TO AVOID FALLING. CONTAIN SPILLS WITH INERT MATERIALS  
(SAND, EARTH). TRANSFER LIQUIDS AND SOLID DIKING MATERIAL TO

SEPARATE SUITABLE CONTAINERS FO R RECOVERY/DISPOSAL.  
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.  
Other Precautions:DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE  
SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION.

Ventilation:NORMAL,  
SUCH AS A FAN

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:EYE WASH STATION.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:351F,177C

Vapor Pres:NONE

Vapor Density:> AIR

Spec Gravity:1.01 (WATER=1)

pH:9 MAX

Viscosity:77-95 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIG

HT  
Appearance and Odor:GRAY LIQUID WITH SLIGHT ODOR  
Percent Volatiles by Volume:60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
THERE ARE NO KNOWN MATERIALS WHICH ARE INCOMPATIBLE WITH THIS PRODUCT.  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD  
ACRYLIC MONOMERS.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP SPILLS AND CLEANING RUN OFF OUT OF  
MUNICIPAL SEWERS AND OPEN BODIES OF WATER. CONSULT FEDERAL, STATE,  
OR LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING  
HEALTH AND ENVIRONMENT

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.