

OCTAGON PROCESS INC. -- VV-L-800C AM. 1 (OCTOIL 90-2), PRODUCT CODE 3012301 --
9150-00-273-2389

===== Product Identification =====

Product ID:VV-L-800C AM. 1 (OCTOIL 90-2), PRODUCT CODE 3012301

MSDS Date:06/19/1998

FSC:9150

NIIN:00-273-2389

MSDS Number: BWCBW

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Info Phone

Num:201-945-9400/313-1187

Emergency Phone Num:201-945-9400

Preparer's Name:J. J. BURGARD

Chemtec Ind/Phone:(800)424-9300

CAGE:82925

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

Contract Num:SP045099MB065

CAGE:82956

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=

=====
Composition/Information on Ingredients
=====

Ingred Name:OIL MIST
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES-MAY CAUSE MILD IRRITATION AND
REDNESS. SKIN-MILD TO MODERATE IRRITATION
WITH PROLONGED OR
REPEATED CONTACT. INHALATION-NO ADVERSE EFFECTS EXPECTED.
INGESTION-PRACTICALLY NON-TOXIC. MAY CAUSE SLIGHT IRRITATION TO
THE GASTROINTESTINAL TRACT.
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS CARCINOGENS (NTP,
IARC, OR OSHA): NO.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
First Aid Measures
=====

First Aid:EYE: FLOOD WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION
PERSISTS, GET MEDICAL ATTENTION. SKIN: WASH WITH WATER AND MILD
SOAP. INHALATION: NONE NORMALLY REQUIRED. INGESTION: GIVE LIQUIDS
AND INDUCE VOMITING UNLESS VICTIM IS CONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:=-160.C, 320.F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:WATER FOG, CHEMICAL FOAM, DRY CHEMICAL OR CARBON
DIOXIDE.
Fire Fi

ighting Procedures:KEEP FIRE-EXPOSED CONTAINERS COOL WITH WATER
FOG. DO NOT USE DIRECT WATER STREAM. PRODUCT WILL FLOAT & CAN BE
REIGNITED ON SUFACE OF WATER.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL. DO NOT ALLOW MATERIAL
TO ENTER DRAINS, SEWERS OR WATERWAYS. RECOVER FREE LIQUID IF
POSSIBLE. ABSORB REMAINING PRODUCT WITH INERT MATERIAL AND PLACE
INTO PROPER CONTAINER

RS FOR DISPOSAL. COMPLY WITH HAZPOWER (29 CFR
1910.120).

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP
CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:USE THIS PRODUCT ONLY AS DIRECTED - SEE MANUFACTURERS
DIRECTION. CLEAN CONTAMINATED EQUIPMENT BEFORE STARTING ANY REPAIR
WORK.

===== Exposure Controls/Personal Protection =====

Respirat

ory Protection:IF WORKING IN A CONFINED AREA OR MISTING IS
OCCURRING, USE NIOSH-APPROVED RESPIRATORY PROTECTION (REFER TO 29CFR
1910.134).

Ventilation:USE FORCED VENTILATION TO MINIMIZE VAPOR CONCENTRATIONS..

Protective Gloves:RUBBER OR NEOPRENE

Eye Protection:ALWAYS WEAR SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:PROVIDE LOCAL EMERGENCY SHOWERS AND EYE WASH
STATIONS.

Work Hygienic Practices:WASH HANDS AND FACE AFTER HANDLING MATERIAL.
LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISPOSE OF OIL SOAKED
FOOTWEAR.

Supplemental Safety and Health

ALL USERS SHOULD CONSULT MSDS BEFORE HANDLING THIS MATERIAL.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:287.8C, 550.F

Vapor Pres:< 0.01

Vapor Density:N.D.

Spec Gravity:0.92

Evaporation Rate & Reference: