

FARWEST PAINT MFG CO -- GOLD SEMI-GLOSS ENAMEL 27038 BLACK -- 8010-00-844-4792

=====
Product Identification
=====

Product ID:GOLD SEMI-GLOSS ENAMEL 27038 BLACK

MSDS Date:09/17/1991

FSC:8010

NIIN:00-844-4792

MSDS Number: BWCFC

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emerg

ency Phone Num:206-244-8844

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 27.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: THIS MATERIAL MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR MISTS CAN RESULT IN HEADACHE, DIZZINESS, N AUSEA AND LOSS OF CONSCIOUSNESS.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO KNOWN CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY ACGIH, OSHA, NTP, IARC.

Effects of Overexposure:SOME REPORTS ASSOCIATE REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.

Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS. SEE SECTION ON CONTROL MEASURES.

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP & WATER. REMOVE & WASH ANY CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH WITH WATER 15 MINUTES & GET MEDICAL AID. INGEST: DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET. GET MEDICAL AID. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHAL: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, GET MEDICAL AID AT ONCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:10

7F,42C

Lower Limits:0.7

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG, OR CLASS B EXTINGUISHING AGENTS. WATER MAY BE UNSUITABLE, USE TO KEEP CONTNRS COOL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARK, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. VENT AREA. ABSORB SPILL W/ABSORBENT (SAWDUST, VERMICULITE, SAND). PLACE INTO CLOSED CONTAINER. IF LARG SPILL, DIKE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATER SYSTEMS/SE WERS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED INHALATION OF HEATED VAPOR/SPRAY MIST. KEEP AWAY FROM HEAT/OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION. DONT WELD ON CNTNRS.

Other Precautions:DONT GET IN EYES, ON SKIN OR CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. KEEP CONTAINERS CLOSED WHEN NOT IN USE, AND PROPERLY LABELED. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS OR SP RAY MISTS WHEN TLV OR PEL EXCEEDED.

Ventilation:GENERAL VENT REQ'D DURING NORMAL USE. LOCAL VENT MAY BE REQ'D DURING SOME OPERATIONS TO KEEP EXPOSURE BELOW TLV/PEL.

Protective Gloves:CHEM RESIST, NITRILE, NEOPRENE, RUBBER

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOHTING TO PREVENT SKIN CONTACT. EYE WASH STATION & SAFETY SHOWERS SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety
and Health

US EPA RCRA HOTLINE 800-424-9346 OR 202-382-3000.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:307 TO 389F

Vapor Pres:2.6 @ 20C

Vapor Density:> AIR

Spec Gravity:11.4 LBS/GAL

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:WHITE OR COLORED LIQUID, MILD PLESANT ODOR.

Percent Volatiles by Volume:46.0

===== Stability and Reactivity Data =====

Stability Indicator

/Materials to Avoid: YES

IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Stability Condition to Avoid: HEAT, SPARKS AND OPEN FLAME.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

Conditions to Avoid Polymerization: HEAT, SPARKS AND OPEN FLAMES.

===== Disposal Considerations =====

Waste Disposal Methods: TREAT AS HAZARDOUS WASTE (IGNITABLE). DISPOSAL OF MAT'L/CNTNR REQUIRES COMPLIANCE W/LABELING, PACKAGING, RECORDKEEPING STANDARDS. DISPOSE IN ACCORD W/FEDERAL & STATE AGENCIES. GRND HANDLING EQUIPMENT TO PREVENT SPARKS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.