

S. L. GILLMAN PAINT CO -- SEMI GLOSS ENAMEL -- 8010-00-290-4135

=====  
Product Identification  
=====

Product ID:SEMI GLOSS ENAMEL

MSDS Date:11/01/1988

FSC:8010

NIIN:00-290-4135

MSDS Number: BWCWR

=== Responsible Party ===

Company Name:S. L. GILLMAN PAINT CO

Address:2250 MORELAND AVE, SE

City:ATLANTA

State:GA

ZIP:30315

Country:US

Info Phone Num:404-622-1326

Emergency Phone Num:404-622-1326

CAGE:LO191

=== Contractor Identification ===

Company Name:GILLMAN PAINT CO.

Address:2250 MORELAND AVE., S.E.

City:ATLANTA

State:GA

ZIP:30315

Country:US

Phone:404-622-1326

CAGE:GILLM

Company Name:S. L. GILLMAN PAINT COMPANY

Address:2250 MORELAND AVENUE, SE

City:ATLANTA

State:GA

ZIP:30311

Country:US

Phone:800-621-5808

CAGE:LO191

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM&P NAPHTHA

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 40-45%

Other REC Limits:NONE RECOMMEN

DED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM; 9394

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN-PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.  
SWALLOWING-ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.  
Explanation of Carcinogenicity:NOT CARCINOGENIC.  
Effects of Overexposure:EYES-CAN CAUSE SEVERE IRRITATION, REDNESS, BLURRED VISION. BREATHING-EXCESSIVE INHALATION CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS & EVEN ASPHYXIATION.  
SWALLOWING-CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA.  
Medical Cond Aggravated by Exposure:NONE EXPECTED.

===== First Aid Measures =====

First Aid:SKIN-WASH EXPOSED AREA WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. SEE DOCTOR FOR IRRITATION. EYE-FLUSH WITH LARGE AMOUNTS OF WATER. SEE DOCTOR. SWALLOWED-DO NOT INDUCE VOMITING. KEEP WARM, QUIET, & GET DOCTOR. ASPIRATION OF MATERIAL INTO LUNGS CAN BE FATAL. BREATHED-REMOVE TO FRESH AIR. IF BREATHING IS HARD, GIVE OXYGEN OR IF STOPS, GIVE CPR. KEEP WARM, QUIET & GET A DOCTOR.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point :105F,41C  
Lower Limits:1.0  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. WATER SPRAY MAY BE INEFFECTIVE.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND MODE OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.  
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION & IGNITED BY PILOT LIGHTS, SPARKS, SMOKING, ELECTRIC MOTORS, STATIC, ETC

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB LIQUID ONTO PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

===== Handling and Storage =====

Handling and Storage Precautions: AVOID STORING IN HIGH TEMPERATURE OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN & AWAY FROM HEAT.  
Other Precautions: DO NOT WELD OR FLAME CUT AND EMPTY DRUM. DRUMS OF THIS MATERIAL SHOULD BE G  
ROUNDED & BONDED WHEN POURING. AVOID BREATHING SANDING DUST. KEEP CLOSURE TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE. DO NOT STORE OR USE NEAR HEAT, SPARKS, ETC.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS.

Ventilation: PROVIDE SUFFICIENT MECHANICAL GENERAL AND OR LOCAL EXHAUST

VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: NITRILE RUBBER, NEOPRENE.

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices: AVOID REPEATED CONTACT WITH SKIN, WASH HANDS BEFORE EATING OR USING WASHROOM, SMOKE IN SMOKING AREA ONLY.

Supplemental Safety and Health

SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPORS, LIQUIDS AND OR SOLIDS), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 300F, 149C

Vapor Density: >AIR

Percent Volatiles by Volume: 65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: AVOID HIGH TEMPERATURES, OPEN FLAMES AND SPARKS.

Hazardous Decomposition Products: MAY FOR

M TOXIC MATERIALS SUCH AS:  
CARBON DIOXIDE, CARBON MONOXIDE AND VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants thi  
s information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.