View NSN Online: https://aerobasegroup.de/nsn/8030-00-526-1605

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- TECTYL 846, 50010175 8030-00-526-1605 Product ID:TECTYL 846, 50010175 MSDS Date:02/13/1991 FSC:8030 NIIN:00-526-1605 MSDS Number: BWCXQ === Responsible Party === Company Name: VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. Address:200 E MAIN ST Box:14000 City:LEXINGTON State:KY ZIP:40512 Country:US Info Phone Num:606-264-7000/7616;FAX 601-429-0537 Emergency Phone Num:800-ASHLAND/800-274-5263 CAGE:72527 === Contractor Identification === Company Name: CONVOY OIL CORP Address:1410 N FRONT STREET Box:29366 City:PHILADELPHIA State:PA ZIP:19125 Country:US Phone:215-739-5281 CAGE:6A438 Company Name: STEVEN INDUSTRIES Address:39 AVENUE C Box:8 **City:BAYONNE** State:NJ ZIP:07002-3417 Country:US Phone:201-437-6501 CAGE:33150 Company Name: VALVOLINE OIL CO Address:3499 BLAZER PKY Box:14000 City:LEXINGTON State:KY ZIP

:40512 Country:US Phone:606-357-7206 / 800-274-5263 CAGE:72527

Ingred Name:MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 30-60% Other REC Limits:100 PPM (MFR)

LD50 LC50 Mixture:ORAL LD50 (RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute an

d Chronic:ACUTE-EYE:SEVERE IRRITATION.

PROLONGED/REPEATED SKIN CONTACT:MODERATE IRRITATION. INHALED:NASAL AND RESPIRATORY IRRITATION, CNS EFFECTS INCLUDING, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCON SCIOUSNESS, DEATH. INGESTED:G/I IRRITATION, NAUSEA, VOMITING, DIARRHEA. ASPIRATION HAZARD. CHRONIC-CNS EFFECTS.

Explanation of Carcinogenicity:MFR LISTED NO INFORMATION ABOUT THE CARCINOGENICITY OF THIS MATERIAL. HMIS DOES NOT EXPECT IT TO BE CARCINOGENIC.

Eff

ects of Overexposure:EYE:IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN:IRRITATION, DEFATTING, DERMATITIS. INHALATION:NASAL AND RESPIRATORY IRRITATION, CNS EFFECTS, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCO NSCIOUSNESS, DEATH. INGESTION:G/I IRRITATION, NAUSEA, VOMITING, DIARRHEA. ASPIRATION INTO LUNGS CAN BE FATAL.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

:EYE:FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. LAUNDER CLOTHING BEFORE REUSE. INHALED:MOVE TO FRESH AIR. AID OR RESTORE BREATHING AS NEEDED. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET. GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS.

Flash Poi nt:100F,38C
Lower Limits:0.6
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SCBA,FULL FACEPIECE,IN PRESSURE DEMAND MODE. WATER/FOAM MAY CAUSE FROTHING IF SPRAYED DIRECTLY INTO HOT,BURNING LIQUID, THUS ENDANGERING FIRE FIGHTERS.
Unusual Fire/Explosion Hazard:NEVER USE WELDING/CUTTING TORCH ON/NEAR DRUM (EVEN EMPTY),PRODUCT/RESIDUE CAN IGNITE EXPLOSIVELY.VAPORS MAY TRAVEL LONG DISTANCE TO IGNITION SOURCE & BACKFLASH.

\_\_\_\_\_

Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT AND TRANSFER TO HOOD. Neutralizing Agent: NO INFORMATION GIVEN BY MFR ON MSDS.

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND OPEN FLAME. USE/STORE ONLY WITH ADEQUATE VENTILATION. DO NOT TRANSFER TO UNLABELED CONTAINER. PROTECT FROM PHYSICAL DAMAGE.
Other Precautions:CONTAINERS
MAY BE HAZARDOUS WHEN EMPTY. EMPTY
CONTAINERS MAY RETAIN RESIDUE LIQUID, VAPORS, SOLIDS. OBSERVE ALL
PRECAUTIONS ON THIS MSDS. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN WH EN EMPTY).

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IN THE ABSENCE OF ENVIRONMENTAL CONTROLS. OSHA REGULATIONS PERMIT OTHER RESPIRATORS UNDER SPECIFIED CONDITIONS. IMPLEMENT ADMINISTRA TIVE & ENGINEERING CONTROLS TO REDUCE EXPOSURES. Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves:WEAR RESISTANT GLOVES. Eye Protection:CHEMICAL SPLASH GOGGLES OR OTHER OSHA Other Protective Equipment:TO PREVENT REPEATED/PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS. Work Hygienic Practices:MFR: ? HMIS:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY EXPOSURE. WASH THOROU GHLY BEFORE EATING OR DRINKING Supplemental Safety and Health NONE

HCC:F4 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:302F,150C Vapor Pres:1 (AIR=1) Spec Gravity:0.866-0.876 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Appearance and Odor:LIQUID. APPEARANCE NOT SPECIFIED. Percent Volatiles by Volume:40-55

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NO INFORMATION GIVEN BY MFR ON MSDS. Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS; CARBON DIOXIDE, CARBON MONOXIDE, VARIOUS HYDROCARBONS, SULFUR COMPOUNDS. Conditions to Avoid Polymerization:CANNOT OCCUR.

Waste Disposal Methods: ALLOW VOLITILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK.

## DISPOSE OF REMAINING MATERIAL I/A/W APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibili ty for the suitability of this information to their

particular situation.