

PRATT AND LAMBERT INC -- LACQUER CAMOUFLAGE, DARK GULL GRAY 32631, 787611 --
8010-00-515-1568

=====
===== Product Identification =====

Product ID:LACQUER CAMOUFLAGE, DARK GULL GRAY 32631, 787611

MSDS Date:10/13/1994

FSC:8010

NIIN:00-515-1568

MSDS Number: BWDVY

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Ph

one Num:316-733-1361

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SOLVENT) (LFL 2.0; UFL 11.0)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 P

PM; 700 MG/M3
ACGIH TLV:150 PPM; 700 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SOLVENT) (VAPOR PRESSURE 33 MM HG @ 20C)
(LFL 3.0; UFL 13.0)

CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM;STEL 500 PPM
ACGIH TLV:400 PPM;STEL 500 PPM

Ingred Name:NITROCELLULOSE (RESIN)

CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOBUTYL ALCOHOL (SOLVENT) (VAPOR PRESSU

RE 10 MM HG @ 20C)

(LFL 1.0; UFL 11.0)

CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1) (SKIN)

CAS:108-88-3
RTECS #:XS525000

0

Fraction by Wt: 15%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:50 PPM; 147 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE (PIGMENT)

CAS

:14464-46-1

RTECS #:VV7325000

Fraction by Wt: