View NSN Online: https://aerobasegroup.de/nsn/8030-00-903-6545

## ITW DEVCON -- PLASTIC STEEL PUTTY (A) RESIN -- 8030-00-903-6545

============= Product Identification ==============

Product ID:PLASTIC STEEL PUTTY (A) RESIN

MSDS Date:04/21/1992

FSC:8030

NIIN:00-903-6545

Kit Part:Y

MSDS Number: BWDZG === Responsible Party === Company Name:ITW DEVCON Address:30 ENDICOTT ST

City: DANVERS

State:MA ZIP:01923 Country:US

Info Phone Num:508-777-1100

Emergency Phone Num:508-777-1100/800-42

4-9300(CHEMTREC)

CAGE:0RZG3

=== Contractor Identification === Company Name:ITW DEVCON Address:30 ENDICOTT ST

City: DANVERS

State:MA

ZIP:01923-3712

Country:US

Phone:978-777-1100

CAGE:0RZG3

Company Name: ITW PHILADELPHIA RESINS

Address:130 COMMERCE DR Box:City:MONTGOMERYVILLE

State:PA ZIP:18936 Country:US

Phone:215-855-8450

CAGE:20420

======= Composition/Information on Ingredients ========

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOLYMER

CAS:25068-38-6 RTECS #:SL6475000

Fraction by W

t: 10-30% %

Other REC Limits: NONE RECOMMENDED

Ingred Name: NON-HAZARDOUS INGREDIENTS

Fraction by Wt: BALANCE

Other REC Limits: NONE RECOMMENDED

============ Hazards Identification =========================

LD50 LC50 Mixture:ORAL LD50 (RAT): 11400 MG/KG-EPOXY RESIN

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: MAY BE MILDLY IRRITATING TO THE EYES.

METAL FILLER PARTICLES COULD SCRATCH CORNEA.

SKIN CONTACT MAY CAUSE

MINIMAL TO MILD IRRITATION IN MOST PEOPLE. APPROXIMATELY 1% OF WORKERS MAY BECOME SENSITIZED B Y TOO MUCH SKIN CONTACT WITH EPOXY RESINS; ITCHING, SWELLING, OR RASHES MAY THEN RESULT FROM FURTHER CONTACT.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, ITCHING, SWELLING OF SKIN, RASHES.

M

edical Cond Aggravated by Exposure:PRE-EXISTING ALLERGIES, ECZEMA, SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN HALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTI

ON. INGESTION: DO NOT INDUCE VOMITING. DILUTE WITH TWO GLASSES OF WATER. GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>400F,>204C Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN

Extinguishing Media: FOAM, DRY CHEMICAL, CARBON DIOXIDE

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY M

