

JOHNSON MATTHEY CATALOG COMPANY -- 11414 SILVER NITRATE -- 6505-00-140-5000

=====
Product Identification
=====

Product ID:11414 SILVER NITRATE

MSDS Date:01/06/1989

FSC:6505

NIIN:00-140-5000

MSDS Number: BWMNT

=== Responsible Party ===

Company Name:JOHNSON MATTHEY CATALOG COMPANY

Address:30 BOND STREET

City:WARD HILL

State:MA

ZIP:01835-0747

Country:US

Info Phone Num:508-521-6300

Emergency Phone Num

:508-521-6300(CHEMTREC 800-424-9300)

CAGE:0JVJ1

=== Contractor Identification ===

Company Name:JOHNSON MATTHEY CATALOG CO INC ALFA AESAR

Address:30 BOND ST

Box:City:WARD HILL

State:MA

ZIP:01835-0747

Country:US

Phone:978-521-6300

CAGE:0JVJ1

=====
Composition/Information on Ingredients
=====

Ingred Name:SILVER NITRATE (SARA III)

CAS:7761-88-8

RTECS #:VW4725000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.01 MG (AG)/M3

ACGIH TLV:0.01 MG (AG)/M3;9394

EPA Rpt

Qty:1 LB
DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY BE POISONOUS IF INGESTED.
MAY CAUSE SEVERE IRRITATION OR BURNS ON SKIN OR EYE CONTACT.
INHALATION MAY CAUSE RESPIRATORY IRRITATION. CHRONIC: PROLONGED OR
REPEATED EXPOSURE MAY CAUSE DISCOLO RATION OF SKIN, CONJUNCTIVA &
MUCOUS MEMBRANE
S, MAY CAUSE LUNG DISEASE.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:SKIN: BLUISH TINT TO SKIN, IRRITATION, PAIN.
EYES: PAIN, IRRITATION, EYE DAMAGE. INGESTION: PAIN, BURNING IN
MOUTH, BLACKENING OF SKIN/MUCOUS MEMBRANES/THROAT/ABDOMEN,
SALIVATION, VOMITING, DIARRHEA, COLLAPSE, SHOCK, COMA, DEATH.
INHALED: COUGHING, SORE THROAT, SHORTNESS OF BREATH.

Medical Con

d Aggravated by Exposure:NO DATA.

=====
===== First Aid Measures =====

First Aid:INGESTED-OBTAIN MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED
CLOTHES. FLOOD WITH WATER. IF IRRITATION PERSISTS, SEEK MEDICAL
ATTENTION. EYES-IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15
MINUTES. SEEK M EDICAL ATTENTION. INGESTED-OBTAIN MEDICAL
ATTENTION.

=====
===== Fire Fighting Measures =====

Extinguishing Media:DRY SAND OR DRY DOLOMITE
, WATER, CARBON DIXOIDE,
DRY CHEMICAL.

Fire Fighting Procedures:NO SPECIAL FIREFIGHTING PROCEDURES NEEDED.
FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR FULL PROTECTIVE CLOTHING & RESPIRATORY
PROTECTION. ELIMINATE ALL SOURCES OF IGNITION. COVER SPILL WITH DRY
SAND OR

DRY GROUND VERMICULITE, MIX WELL AND CAREFULLY TRANSFER TO A WELL MARKED CONTAINER. CLOSE CONTAINER TIGHTLY. DISPOSE OF PROPERLY.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. STORE IN A COOL, DRY, WELL-VENTILATED PLACE. WASH THOROUGHLY AFTER USE.

Other Precautions: USE PROPER PROTECTIVE CLOTHING & EQUIPMENT WHEN USING. USE PROPER FACILITIES WHEN USING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation: LABORATORY FUME HOOD IS ACCEPTABLE. A GLOVE BOX, BAG WITH DRY, INERT ATMOSPHERE IS PREFERRED.

Protective Gloves: RUBBER.

Eye Protection: ANSI APPROVED SAFETY GLASSES.

Other Protective Equipment: LAB COAT & APRON. FLAME & CHEMICAL RESISTANT COVERALLS, EYE WASH STATION & SAFETY SHOWER, HYGENIC WASH FACILITIES.

Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: 831F, 444C

Melt/Freeze Pt: M.P/F.P Text: 414F, 212C

Decomp Temp: Decomp Text: 831F, 444C

Vapor Density: 4.4

Spec Gravity: 4.352

Evaporation Rate & Reference: 0 (N-BUTYL ACETATE=1)

Solubility in Water: APPRECIABLE

Appearance and Odor: COLORLESS OR WHITE CRYSTALS; ODORLESS.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

ALKALIS, ANTIMONY

SALTS, ARSENITES, BROMIDES, CARBONATES, CHLORIDES, IODIDES, THIOCYANATES, FERROUS SALTS, OILS, CRESOL, ETHANOL, ..

Stability Condition to Avoid: THERMAL DECOMPOSITION.

Hazardous Decompos

ition Products:WHEN HEATED TO THERMAL DECOMPOSITION;
NITROGEN OXIDES, EXPOSIVE SILVER CMPOUNDS & OTHER TOXIC FUMES.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:RCRA CODE: DO11 (SILVER) AND/OR D003 (REACTIVE).
TSCA REGISTERED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is
formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.