

DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE -- SD AL POLY #16081 GRAY, P/C
822X405 -- 8010-01-078-9281

===== Product Identification =====

Product ID:SD AL POLY #16081 GRAY, P/C 822X405

MSDS Date:02/12/1992

FSC:8010

NIIN:01-078-9281

Kit Part:Y

MSDS Number: BWNMZ

=== Responsible Party ===

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

City:BERKELEY

State:CA

ZIP:94710

Country:US

Info Phone Num:818-549-7823

Emergency Phone Num:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

=== Contractor Identification ===

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

Box:City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

===== Composition/Information on Ingredients =====

Ingred Name:POLYESTER RESIN (VAPOR PRESSURE 0 MM HG)

CAS:68797-54-6

Fraction by Wt: 30%

Other

REC Limits:NONE RECOMMENDED

Ingred Name:METHYL ISOBUTYL KETONE (SARA 313) (CERCLA) (VAPOR PRESSURE
15 MM HG)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM; STEL 75 PPM

ACGIH TLV:50 PPM; STEL 75 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BUTYL ACETATE (CERCLA) (VAPOR PRESSURE 8.4 MM HG)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STE

L 200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SARA 313) (CERCLA) (VAPOR PRESSURE
74.9 MM HG)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 15%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM;STEL 300 PPM

ACGIH TLV:200 PPM;STEL 300 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE (VAPOR PRESSURE 0 MM HG) (LISTED AS REQ'D,
FULLY ENCAPSULATED, NOT HAZARDOUS UNDER NORMAL CONDITIONS)

CAS:13463-67-7

RTECS #:XR2275000

Fractio

n by Wt: 20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3 (TOTAL)

ACGIH TLV:10 MG/M3

Ingred Name:IRON OXIDE (VAPOR PRESSURE 0 MM HG)

CAS:1332-37-2

RTECS #:NO7380000

Fraction by Wt: 10%

Other REC Limits:* 8 HR;5 MG/M3 FUME

OSHA PEL:10 MG/M3 (TOTAL) *

ACGIH TLV:5 AS FE MG/M3

Ingred Name:CARBON BLACK (LISTED AS REQ'D, FULLY ENCAPSULATED, NOT
HAZARDOUS UNDER NORMAL CONDITIONS) (VAPOR PRESSURE 0 MM HG)

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: