

NILES CHEMICAL PAINT CO -- N-1981A WHITE H.S. EPOXY PRIMER -- 8010-01-309-0327

=====  
Product Identification  
=====

Product ID:N-1981A WHITE H.S. EPOXY PRIMER

MSDS Date:10/21/1994

FSC:8010

NIIN:01-309-0327

Kit Part:Y

MSDS Number: BWQDB

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

E

mergency Phone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====  
Composition/Information on Ingredients  
=====

Ingred Name:EPOXY RESIN

CAS:25036-25-3

Fraction by Wt: 28%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:5 MG/M3

Ingred Name:METHYL ISOBUTYL KETONE (SARA 313) (CERCLA) (

VAPOR PRESSURE  
15 MM HG @ 20C)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 14%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; STEL 75 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BARIUM SULFATE

CAS:7727-43-7

RTECS #:CR0600000

Fraction by Wt: 12%

Other REC Limits:NONE RECOMMENDED

Ingred Name:BUTYL ACETATE (CERCLA) (VAPOR PRESSURE 10 MM HG @ 20C)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM

ACGIH TL

V:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BUTYL ALCOHOL (SARA 313) (CERCLA) (VAPOR PRESSURE 4.4 MM HG  
@ 20C)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM (SKIN)

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ZINC PHOSPHATE (SARA III)

CAS:7779-90-0

RTECS #:TD0590000

Fraction by Wt: 4%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY INGREDIENTS (MFR STATES UNIDENTIFIED)

INGREDIENTS ARE NOT CONSIDERED HAZARDOUS UNDER FED HZD COMMUNICATN  
REG)

Fraction by Wt: BALANCE

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 3.33 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:72.0F,22.2C

Lower Limits:1.4

Upper Limits:11.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:WEAR SCBA W/FULL FACPIECE (POSITIVE PRESSURE  
MODE) &

FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO  
PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.VAPOR >AIR,TRAVEL ON GRND  
TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR MAY EXPLODE W/HEAT.APPLIC  
TO HOT SRFC REQ SPCL CAUTION.DECOMP PRODCT-HLTH HZD

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Tex

t:242 TO 262F

Vapor Density:> AIR

Spec Gravity:1.456

Viscosity:100+F4

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume:48.52

Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS

Stability Condition to Avoid:HIGH TEMPERATURES

Disclaimer (provided with this information b

y the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.