

NILES CHEMICAL PAINT CO -- N-5839 GLOSS YELLOW SILICONE ENAMEL 13538 --  
8010-01-349-9005

===== Product Identification =====

Product ID:N-5839 GLOSS YELLOW SILICONE ENAMEL 13538

MSDS Date:10/13/1994

FSC:8010

NIIN:01-349-9005

MSDS Number: BWRGS

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-68

3-3377

Emergency Phone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

===== Composition/Information on Ingredients =====

Ingred Name:HIGH SOLIDS SILICONE (VAPOR PRESSURE 1.5 MM HG @ 20C)

Fraction by Wt: 36%

Other REC Limits:NONE RECOMMENDED

Ingred Name:GROUND LIMESTONE

CAS:1317-65

-3  
RTECS #:EV9580000  
Fraction by Wt: 28%  
Other REC Limits:NONE RECOMMENDED

Ingrid Name:# 100 SOLVENT (VAPOR PRESSURE 4.4 MM HG @ 20C)  
CAS:64742-95-6  
Fraction by Wt: 24%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE:SEVERE IRRIT, TEARING, REDNESS,  
BLURRED VISION. SKIN  
:REDNESS, IRRIT, DEFATTING (LEADING TO  
DERMATITIS). INHAL:NASAL & RESPIRATORY IRRIT, CNS DEPRESSION  
(DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, C ONFUSION)  
NAUSEA,HEADACHE,VERTIGO,UNCONSCIOUSNESS,ASPHYXIATION. INGEST:GI  
IRRIT,ABDOMINAL PAIN,NAUSEA,VOMITING,DIARRHEA.  
Effects of Overexposure:CHRONIC: LIVER, KIDNEYS, CNS. PROLONGED  
EXPOSURE TO SOLVENTS MAY CAUSE CHRONIC HEALTH EFFECTS.

TARGET ORGANS: L IVER KIDNEY, CNS, SKIN, EYES, RESPIRATORY  
SYS  
TEM, CNS.  
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR IMMED.IF BREATH STOPPD,GIVE ARTIF  
RESPRTN.GET MED AID ASAP.SKIN:IMMED FLUSH W/PLENTY H2O.IF MAT'L  
PENETRATES CLOTH,IMMED REMOVE CONTAM CLOTH & FLUSH SKIN W/H2O.GET  
MED AID.WASH CLOTH & DECONTAM SHOES BEFORE REUSE.EYE:IMMED FLUSH  
W/LRG AMT H2O 15 MIN,LIFT UPPER/LOWER LIDS.GET MED AID  
IMMED.INGEST:DRINK 1-2 GLASS H2O.  
DON'T INDUCE VOMIT.SEE DR/POISON  
CTR IMMED.TREAT SYMPTOMS.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:107F,42C  
Lower Limits:0.8  
Upper Limits:0.0  
Extinguishing Media:DRY CHEMICAL, FOAM, CO2  
Fire Fighting Procedures:WEAR SCBA W/FULL FACPIECE (POSITIVE PRESSURE  
MODE) & FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO  
PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.  
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.VAPOR

HEAVY,TRAVEL ON

GRND TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR EXPLODE W/HEAT.APPLIC  
TO HOT SRFCS REQ SPCL CAUTN.DECOMP PRODUCT-HEALTH HZD.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGNIT SOURCE.MINIMIZE BREATHING OF  
VAPOR.AVOID SKIN CONTACT.SMALL:ABSORB W/INERT MAT'L  
(CLAY,SOIL,COMMERCL ABSORB) SHOVEL RECLAIMED LIQ & ABSORBNT INTO  
RECOVERY/SALVAGE DRUMS FOR DISPOSAL.LRG:DIK E,RECLAIM INTO  
RECOVERY/SALVAGE DRUMS/TAN  
K TRUCK.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE AREA  
OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE.  
AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN  
EMPTY. DO NOT WELD OR FLAME CUT ON EMTPY DRUMS. SHOCK FROM DROPPING  
MAY SPLIT CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Prot

ection:WEAR AN APPROPRIATE PROPERLY FITTED HALF-MASK OR  
FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLICATION  
UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW  
APPLICABLE LIMITS. FOL LOW RESPIRATOR MFR'S DIRECTIONS FOR USE.

Ventilation:KEEP AIR CONC BELOW TLV/PEL.REMOVE DECOMP PRODCT FORMED  
DURING WELD/FLAME CUT COATED SRFCS.VENT VAPOR FROM BAKING FINISH

Protective Gloves:CHEM RESISTANT (NITRILE/VITON) GLOVES

Eye Protection:CHEM GOGGLES,SAFETY GLASSES,FAC  
E SHIELD

Other Protective Equipment:DON'T WEAR CONTACT LENSES WHILE WORKING WITH  
PRODUCT.

Work Hygienic Practices:WASH PROMPTLY WHEN SKIN BECOMES CONTAMINATED.  
REMOVE ANY CLOTHING THAT BECOMES WET (AVOID FLAMMABILITY HAZARD) \*

Supplemental Safety and Health

\* WASH BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING  
RESTROOM.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:285 TO 398F

Vapor Density:> AIR

Spec Gravity:1.256

Viscosity:100

KU MAX  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Solubility in Water: SLIGHT  
Appearance and Odor: LIQUID, ODOR OF SOLVENTS  
Percent Volatiles by Volume: 38.28  
Corrosion Rate: MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDIZERS, STRONG ACIDS  
Stability Condition to Avoid: HIGH TEMPERATURES  
Hazardous Decomposition Products: CAN PRODUCE CARBON MONOXIDE AND/OR  
CARBON DIOXIDE.  
Conditions to Avoid Polymerization:  
n: HIGH TEMPERATURES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL,  
STATE, AND FEDERAL REGULATION. EPA HAZARDOUS WASTE CODE: D001  
(IGNITABLE)

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.