View NSN Online: https://aerobasegroup.com/nsn/8010-01-170-7583

DYNAMATION RESEARCH INC -- MIL-C-46168D TYP II, 36231, PC:03GY236, PART

\_\_\_\_\_\_

MSDS Safety Information

\_\_\_\_\_

FSC: 8010

NIIN: 01-170-7583 MSDS Date: 09/30/1994 MSDS Num: BWRLX

Product ID: MIL-C-46168D TYP II, 36231, PC:03GY236, PART A

MFN: 01 Kit Part: Y

Responsible Party Cage: 0AMA0

Name: DYNAMATION RESEARCH INC

Address: 2301 PONTIUS AVE

City: LOS ANGELES CA 90064 Info Phone Number: 310-477-1224

Emergency Phone Number: 310-477-1224

Preparer's Name: NORM GAUL

Proprietary Ind: Y Review Ind: Y Published: Y

\_\_\_\_\_

Preparer Co. when other than Responsible Party Co.

\_\_\_\_\_

Cage: 0AMA0

Name: DYNAMATION RESEARCH INC

Address: 2301 PONTIUS AVE City: LOS ANGELES CA 90064

\_\_\_\_\_

Con

tractor Summary

\_\_\_\_\_\_

Cage: 0AMA0

Name: DYNAMATION RESEARCH INC

Address: 2301 PONTIUS AVE City: LOS ANGELES CA 90064

Phone: 310-477-1224

\_\_\_\_\_

Item Description Information

\_\_\_\_\_

Item Manager: GSA

Item Name: POLYURETHANE COATING Specification Number: MIL-C-46168

Type/Grade/Class: TY II

Unit of Issue: KT UI Container Qty: 0 Type of Container: KIT,Q

| UART                                   |     |
|--|-----|
| ====================================== | === |
| None of *** DDODDICTADY ***            | -== |

Name: \*\*\* PROPRIETARY

\_\_\_\_\_

Health Hazards Data

\_\_\_\_\_\_

LD50 LC50 Mixture: UNKNOWN Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: INHAL:RESP TRACT IRRI T,ACUTE CNS DEPRESSION. SKIN/EYE:SKIN

IRRIT.LIQ/AEROSOLS/VAP IRRIT EYES. SKIN ABSORPTION:PROLONG/REPEAT CONTACT CAN CAUSE MODERATE IRRIT,DRYING,DEFATTING. INGEST:IRRIT & POSSIBLE CORR

ACTION IN MOUTH/STOMACH TISSUE/DIGESTIVE TRACT. VOMITING MAY CAUSE ASPIRATION OF SOLVENT RESULTING IN CHEM PNEUITIS.

Explanation Of Carcinogenicity: PER MSD:CARCINOGENICITY:NTP/IARC/

OSHA:NO.CONTAINS CHEM KNOW TO STATE OF CA TO CAUSE CANCER(DIATOMACEOUS EARTH).

Signs And Symptions Of Overexposure: HEADA

CHE, DIZZ, STAGGERING

GAIT, CONFUSION, UNCONSC, COMA. SKIN SWELLING, REDNESS, RASH. EYE TEARING, REDNESS, SWELLING, STINGING SENSATION. SKIN CRACKS. DIFFICULT BREATHING, LOSS OF CONSCIOUSNESS. SKIN SENSITIZATION, ASTHMA, OTHER ALLERGIC RESPONSES MAY DEVELOP.

Medical Cond Aggravated By Exposure: ASTHMA & DISORDERS. SKIN ALLERGIES, ECZEMA, DERMATITIS.

First Aid: INHAL:MOVE AWAY FRM EXPO.RESTORE BREAZTH.ASTHMATIC TYP SYMPTOMS DEVELOP IMMED/DELAYED HRS.GET MED ATTN.SKIN:REMOVE C

ONTAMIN CLOTH.WASH SKIN

WELL W/SOAP/WATER.EYE:FLUSH W/CLEAN LUKEWARM WATER(LOW PRESS URE)@LEAST 15MINS OPENING EYELIDS.GET MED ATTN.INGEST:DO NOT INDUCE VOMIT.DO NOT GIVE ANYTHING TO UNCONSC PERSON.GET MED ATTN.

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_\_

Spill Release Procedures: EVACUATE ALL NONESSENTIAL PERSONNEL.REMOVE ALL IGN SOURCES(FLAME/SPARK SOURCES/HOT SURFACES).VENTILATE AREA.CONTAIN & DESCRIPTION OF THE PROPERTY OF

; REMOVE

W/INERT ABSORBENT & amp; NON-SPARKING TOOLS. CONTAINS SARA 313,PROP 65(CALIFORNI A) CHEMICALS.

Waste Disposal Methods: WASTE MUST BE DISPOSED OF IAW FED/STAT/LOC ENVIRON CNTRL REGS.EMPTY CNTNRS MUST BE HANDLED W/CARE DUE TO PRODUCT RESIDUE & ELAMM VAP.DO NOT INCINERATE CLSD CNTNRS.EPA HAZ WEASTE NO:D001,F003,F005.HAZ WASTE CHARACTERISTICS:IGNITABILITY/REACTIVITY.

Handling And Storage Precautions: STORE IN BLD DESIGNED TO COMPLY W/OSHA 1910.106 & DESIGNED TO COMPLY W/OSHA

STORING NEAR HI TEMP/FIRE/OPN

FLAMES/SPARK SOURCES.STORE IN TIGHTLY CLSD CNTNRS

Other Precautions: KEEP CNTNRS TIGHTLY CLSD& UPRIGHT TO

PREVENTLEAKAGE.PREVENT PROL VAP/SPRAY MIST BREATH.PRLONGED OVEREXPO MAY CAUSE

ALLERGI RX.AVOID CONTACT W/SKIN/EYES.DON'T TAKE INTERNALLY.READ/UNDERSTAND MFG'S SAF P RECAUTIONS BEF HANDLING.

\_\_\_\_\_

Fire and Explosion Hazard Information

\_\_\_\_\_

Flash Point Method: TCC

Flash Point Text: 60.0F,15.6C

Lower Limits: 1.00 Upper Limits: 8.00

Extinguishing Media: FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER

FOG, WATER SPRAY.

Fire Fighting Procedures: FULL FIRE FIGHTING EQPMT W/SCBA & DESCRIPTION OF SHOULD BE WORN BY FIREFIGHTERS.WATER MAY BE USED TO COOL CLSD CNTNRS TO PREVENT PRESSURE BUILDUP/AUTOIGN/EXPLO

Unusual Fire/Explosion Hazard: CLSD CNTNR EXPO TO EXTREME HEAT MAY EXPLO.HOT SURFACES APPLICATION REQURIES SPECIAL PRECAUT.DUR

ING EMERGY CONDITION

OVEREXPO TO DECOMP PROD HEALTH HAZ, DELAY SYM

\_\_\_\_\_

## **Control Measures**

\_\_\_\_\_

Respiratory Protection: WEAR RESP RECOMMENDED/APPROVED FOR USE IN ORG VAP ENVIRO(AIR-PURIFYING OR FRESHAIR SUPPLIED). OBSERVE OSHA REGS FOR RESP USE.PROVIDE VENTI TO KEEP EXPO LEVELS BELOW OSHA PEL.NOT AIR SUPP RES REQUIRED I F TLV MAINTAIN/DOCUMENTED BELOW(SUPPLEM)

Ventilation: EXHAU VENTI SUFFI

| CIENT TO KEEP AIRBORNE SOLVENT VAP/MIST CONC BELOW TLV MUST BE UTILIZED.REMOVE ALL IGNITION SOURCES. Protective Gloves: COTTON,NEOPRENE,RUBBER,POLYETHYLENE Eye Protection: SPLASH GUARDS/SIDESHIELDS,CHEM GOGG,FACE Other Protective Equipment: LONG SLEEVE/LONG LEG CLOTH RECOMMENDED. Work Hygienic Practices: WASH CONTAMIN CLOTHING THOROUGHLY BEFORE REUSE.WASH HANDS BEF EAT/SMOKE/TOILET.SMOKE IN SMOKING AREAS ONLY. Supplemental Safety and Health: RESP PROT:OSHA/ACGIH LIMITS AIR SUPPLIED RESP NO T REQUIRED.OTHER OSHA/NISOH APPROVED RESP MAY BE USED. PART A OF 2 COMP KIT;SEE PNIND:B FOR PART B. |
|--|
| Physical/Chemical Properties   |
| HCC: F3 B.P. Text: 241F,116C Vapor Density: >AIR Spec Gravity: 1.38535 Viscosity: SEE APPEA/ODO Evaporation Rate & Reference: 0.83 X N-BUTYL ACETATE Solubility in Water: INSOLUBLE Appearance and Odor: GRAY LIQ W/SOLVENT ODOR, THIN LIQ TO HEAVY VISCO US MATERIAL. Percent Volatiles by Volume: 61.8   |
| ======================================   |
| Stability Indicator: YES Stability Condition To Avoid: HIGH TEMPERATURES, SPARKS, OR OPEN FLAMES. ISOLATE FROM ELECTRICAL EQPMT. Materials To Avoid: STRONG OXIDIZING AGENTS Hazardous Decomposition Products: ABY HIGH HEAT/TEMP:CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN. Hazardous Polymerization Indicator: NO  |
| ======================================   |
| ======================================   |
| ======================================   |
| ======================================   |

Other Information \_\_\_\_\_\_ Transportation Information \_\_\_\_\_\_ Responsible Party Cage: 0AMA0 Trans ID NO: 112799 Product ID: MIL-C-46168D TYP II, 36231, PC:03GY236, PART A MSDS Prepared Date: 09/30/1994 Review Date: 04/13/1995 MFN: 1 Net Unit Weight: 2.9 LBS Multiple KIT Number: 0 Kit Part IND: Y Review IND: Y Unit Of Issue: KT Container QTY: 0 Type Of Container: KIT,QUART Additional Data: PER TIR:KIT OF COMP A:1QT, COMP B:1/2 PINT. PER MSDS:MATL WHEN PKG IN CNTNRS 1LITER OR LESS QUALIFIE S AS PAINT IN LIMITED QTY CLASS 3. \_\_\_\_\_\_ **Detail DOT Information** \_\_\_\_\_ DOT PSN Code: LFD DOT Proper Shipping Name: PAINT **DOT PSN Modifier: IN** CLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER, AND LIQUID LACQUER BASE Hazard Class: 3 UN ID Num: UN1263 DOT Packaging Group: II Label: FLAMMABLE LIQUID Special Provision: B52,T7,T30 Packaging Exception: 150 Non Bulk Pack: 173

Bulk Pack: 242 Max Qty Pass: 5 L Max Qty Cargo: 60 L Vessel Stow Req: B

\_\_\_\_\_\_

**Detail IMO Information** 

\_\_\_\_\_

IMO PSN Code: LCP

IM

O Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL

IMO PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT

THINNING OR REDUCING COMPOUND) o

IMDG Page Number: 3268

UN Number: 1263 UN Hazard Class: 3.2 IMO Packaging Group: I/II \* Subsidiary Risk Label: -EMS Number: 3-05

MED First Aid Guide NUM: 310

**Detail IATA Information** 

=========

\_\_\_\_\_

IATA PSN Code: SXI IATA UN ID Num: 1263

IATA Proper Shipping Name: PAINT IATA PSN Modifier: (INCLUDING

PAINT, LACQUER, ENAMEL, STAIN, SHELLAC, VARNISH, POLISH, LIQUID FILLER AND LIQUID

LACQUER BASE) IATA UN Class: 3

IATA Label: FLAMMABLE LIQUID

UN Packing Group: II

Packing Note Passenger: 305

Max Quant Pass: 5L Max Quant Cargo: 60L Packaging Note Cargo: 307

Exceptions: A7.A72

\_\_\_\_\_\_

**Detail AFI Information** 

\_\_\_\_\_\_

AFI PSN Code: SXI

AFI Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL

AFI PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC

SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING

PAINT THINNING OR REDUCING COMPOUNDS)

AFI Hazard Class: 3 AFI UN ID NUM: UN1263 AFI Packing Group: II Special Provisions: P5 Back Pack Reference: A7.3

**HAZCOM Label** 

=

\_\_\_\_\_\_

Product ID: MIL-C-46168D TYP II, 36231, PC:03GY236, PART A

Cage: 0AMA0

Company Name: DYNAMATION RESEARCH INC

Street: 2301 PONTIUS AVE City: LOS ANGELES CA

Zipcode: 90064

Health Emergency Phone: 310-477-1224

Label Required IND: Y

Date Of Label Review: 04/13/1995

Status Code: C

Label Date: 04/13/1995
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate Contact Hazard: Moderate

Fire Hazard: Severe Reactivity Hazard: None

Hazard And Precautions: INHAL:RESP TRACT IRRIT, ACUTE CNS

DEPRESSION.SKIN/EYE:SKIN IRRIT.LIQ/AEROSOLS/VAP IRRIT EYES.SKIN ABSORPTION:PROLONG/REPEAT CONTACT CAN CAUSE MODERATE

IRRIT, DRYING, DEFATTING. INGEST: IRRIT, POSSIBLE CORR ACTION IN MOUTH/STOMACH TISSUE/DI TRACT. VOMIT MAY CAUSE ASPIRATION OF SOLVENT RESULTING IN CHEM

PNEUITIS.TARGET ORGANS:EYE/SKIN/CNS/GI/LUNGS.1STAID:INHAL:REMOVE FROM

EXPO.RESTORE BREATH.ASTHMATI

C TYP SYMPTOMS DEVELOP IMMED/DELAYED HRS.GET MED

ATTN.SKIN:REMOVE CONTAMIN CLOTH.WASHSKIN WELL W/SOAP/WATER.EYE:FLUSH W/WATER @LEAST 15MINS OPENING EYELIDS.GET MED ATTN.INGEST:DO NOT INDUCE VOMIT.DO NOT GIV E ANYTHING TO UNCONSC PERSON.GET MED ATTN.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in

no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice

## to verify

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.