

EASTMAN KODAK COMPANY -- 825 4237 T-MAX RS DEVELOPER AND REPLENISHER, PART A --  
6750-01-388-7764

===== Product Identification =====

Product ID:825 4237 T-MAX RS DEVELOPER AND REPLENISHER, PART A

MSDS Date:10/16/1996

FSC:6750

NIIN:01-388-7764

Kit Part:Y

MSDS Number: BWRNF

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:

US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Compos

ition/Information on Ingredients =====

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX

CAS:63149-47-3

Fraction by Wt: 50-55%

Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 40-45%

Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9394

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SODIUM BISU

LFITE (SASA III)

CAS:7631-90-5

RTECS #:VZ2000000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PENTETIC ACID, PENTASODIUM SALT

CAS:140-01-2

Fraction by Wt: 212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:293F,145C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.21

pH:8.9

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:TAN LI

QUID, AMINE ODOR  
Percent Volatiles by Volume:> 40%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID TEMPERATURES ABOVE 113F.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,  
OXIDES OF SULFUR, OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT  
TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH  
< 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. A  
ny person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.