

LHB INDUSTRIES -- SO SURE CORROSION PREVENTIVE, COMPOUND AEROSO

=====
MSDS Safety Information
=====

FSC: 8030
NIIN: 01-347-0980
MSDS Date: 07/19/1994
MSDS Num: BWRYL
Product ID: SO SURE CORROSION PREVENTIVE, COMPOUND AEROSOL P/N 942E800
MFN: 01
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHE
R PLACE
City: ST. LOUIS MO 63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: GREGORY MCGOWAN
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contra
tor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: CORROSION PREVENTIVE COMPOUND
Unit of Issue: CN
Quantitative Expression: 00000000014OZ
UI Container Qty: 0
=====

=====

Ingredients

=====

Cas: 67-63-0
RTECS #: NT8050000
Name: ISOPROPANOL (SARA III)
% Wt: <19.10
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 400 PPM
ACGIH TLV: 400 PPM

Cas: 8030-30-6
RTECS #: DE3030000
Name: NAPHTHA
% Wt: <8.35
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM

Cas: 107-98-2
RTECS #: UB7700000
Name: PROPYLENE GLYCOL METHYL ETHER
% Wt:
7.41
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM

Cas: 8030-30-6
RTECS #: DE3030000
Name: VM&P NAPHTHA
% Wt: 14.66
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM

Cas: 97-85-8
RTECS #: NQ5250000
Name: ISOBUTYL ISOBUTYRATE
% Wt: 1.11
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 108-88-3
RTECS #: XS52500

00

Name: TOLUENE (SARA III) (CERCLA)

% Wt: <5.19

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 200 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Cas: 78-83-1

RTECS #: NP9625000

Name: ISOBUTYL ALCOHOL (CERCLA)

% Wt: 9.27

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 100 PPM

ACGIH TLV: 50 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Cas: 71-36-3

RTECS #: EO1400000

Name: N-BUTYL ALCOHOL (SARA 313) (CERCLA)

% Wt:

<4.45

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 50 PPM

ACGIH TLV: 50 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

% Wt: 13.79

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 1000 PPM

ACGIH TLV: 1000 PPM

RTECS #: 9999999VO

Name: VOC: 76%

Other REC Limits: NONE RECOMMENDED

=====
Health Hazards Data
=====

=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL.REPORTS ASSOCIATE REPEATED & PROLONGED OVEREXPOSURE W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.IN CONFINED AREAS,HIGH CONCENTRATIONS ANESTHETIC.IR RITATION TO SKIN & RESPIRATORY TRACT.LIGHT HEADEDNESS,STAGGERING,GIDDINESS,NAUSEA.HARMFUL IF SWALLOWED.SEVERE EYE IRRIT.

Signs And Symptoms Of Overexposure: IRRITATION TO EYES, THROAT, RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH SOAP & WATER; WASH CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES & CONTACT A PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR

& GIVE ARTIFICIAL RESPIRATION IF NECESSARY & GET MEDICAL AID. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS. DO NOT PUNCT

URE, INCINERATE OR STORE > 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH PICKUP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CAUTION - CONTENTS UNDER PRESSURE. DO NOT STORE WHERE TEMPERATUERS MAY EXCEED 120F.

Other Precautions: AVOID BREATHING SPRAY, MIST OR VAPOR. AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LA

BEL DIRECTIONS. CONCENTRATING & INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: NR

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED CONTAINERS.WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, R

UPTURING, OR VENTING OF CNTNRS.

Unusual Fire/Explosion Hazard: DON'T SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURES (>120F) CONTAINERS MAY VENT, RUPTURE, OR BURST. AEROSOL CONTAINER: DO NOT EXPOSE TO TEMPERATURES >120F.

=====
Control Measures
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL)

: ACCEPTABLE AT

POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

Vapor Pres: 65 @ 68F

Vapor Density: 1.522

Spec

Gravity: 0.840 (WATER=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: DARK BLUE LIQUID, SOLVENT ODOR

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====

Other Information

=====

=====

HAZCOM Label

=====

Product ID: SO SURE CORROSION PREVENTIVE, COMPOUND AEROSOL P/N 942E800

Cage: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12

/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL.REPORTS ASSOCIATE REPEATED & PROLONGED OVEREXPOSURE W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.IN CONFINED AREAS,HIGH CONCENTRATIONS ANESTHETIC.IR RITATION TO SKIN & RESPIRATORY TRACT.LIGHT HEADEDNESS,STAGGERING,GIDDINESS,NAUSEA.HARMFUL IF SWALLOWED.SEVERE EYE IRRIT.IRRITATION TO EYES, THROAT, RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.