

TOSCO REFINING COMPANY -- UNLEADED REGULAR GASOLINE-87 OCTANE -- 9130-00-148-7102

=====  
Product Identification  
=====

Product ID:UNLEADED REGULAR GASOLINE-87 OCTANE

MSDS Date:12/15/1991

FSC:9130

NIIN:00-148-7102

MSDS Number: BWSMY

=== Responsible Party ===

Company Name:TOSCO REFINING COMPANY

Address:2300 CLAYTON RD, SUITE 1100

City:CONCORD

State:CA

ZIP:94520

Country:US

Info Phone Num:510-228-1220

E

mergency Phone Num:510-228-1220

Chemtrec Ind/Phone:(800)424-9300

CAGE:TXSCX

=== Contractor Identification ===

Company Name:TOSCO CORP (FORMERLY LION OIL IN PORTLAND,OR)

Address:11400 NW ST HELENS RD

Box:03416

City:PORTLAND

State:OR

ZIP:97203

Country:US

CAGE:3R733

Company Name:TOSCO REFINING CO

Address:2300 CLAYTON RD

Box:City:CONCORD

State:CA

ZIP:94520

Country:US

Phone:800-424-9300 (CHEMTREC)

CAGE:TXSCX

=====  
Composition/Information on Ingredients  
=====

Ingred Name:GASOLINE

(INCLUDING THE FOLLOWING INGREDIENTS)

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: 95-99.9%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM/500STEL;9495

Ingred Name:BENZENE (SARA 313) (CERCLA)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 1 - 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE 1910.1028

ACGIH TLV:10 PPM; A2; 9495

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2 - 8%

Other REC L

imits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0 - 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:O-XYLENE (O-DIMETHYLBENZENE) (SARA 313) (CERCLA)

CAS:95-47-6

RTECS #:ZE2450000

Fraction by Wt: 0 - 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH

TLV:100 PPM/150STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:M-XYLENE (M-DIMETHYLBENZENE) (SARA 313) (CERCLA)

CAS:108-38-3

RTECS #:ZE2275000

Fraction by Wt: 1 - 7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:P-XYLENE (P-DIMETHYLBENZENE) (SARA 313) (CERCLA)

CAS:106-42-3

RTECS #:ZE2625000

Fraction by Wt: 0 - 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL

;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANE (SARA 313) (CERCLA)

CAS:110-82-7

RTECS #:GU6300000

Fraction by Wt: 0 - 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM, 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA 313)

CAS:95-63-6

RTECS #:DC3325000

Fraction by Wt: 1 - 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:25 PPM

ACGIH TLV:25 PPM; 9495

Ingred Name:NAPHTHALENE (SARA 313) (CERCLA)

CAS:91-20-3

RTECS

#:QJ0525000

Fraction by Wt: 0 - 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9495

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:CUMENE (SARA 313) (CERCLA)

CAS:98-82-8

RTECS #:GR8575000

Fraction by Wt: 0 - 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 50 PPM; 9495

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS >5,000 MG/KG.

Routes

of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. ACUTE- CAUSES EYE AND SKIN IRRITATION. DOES NOT PENETRATE SKIN. INHALATION CAUSES IRRITATION, DIZZINESS, HEADACHE, NAUSEA. INGESTION CAN CAUSE IRRITATION, VOMITING. MAY CAUSE LUNG DAMAGE IF ASPIRATED. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:CONTAINS B [71-43-2] WHICH IS LISTED BY NTP A

ND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE AND RESPIRATORY TRACT IRRITATION, BURNING OF MOUTH AND UPPER GASTROINTESTINAL TRACT, EDEMA OF LUNG, HEADACHE, DIZZINESS, DROWSINESS, DEFATTING WITH DRYING SKIN, VOMITING

Medical Cond Aggravated by Exposure:BENZENE: INDIVIDUALS WITH LIVER, KIDNEY AND BLOOD DISEASES. PETROLEUM SOLVENT: THOSE WITH EXISTING DERMATITIS, OTHER SKIN DISORDERS, RESPIRATORY DISEASES

===== First Aid Measures =====

=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:-40F,  
-40C

Autoignition Temp:Autoignition Temp Text:850F

Lower Limits:1.4

Upper Limits:7.6

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL. WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:FLOWING GASOLINE CAN BE IGNITED BY SELF-GENERATED STATIC ELECTRICITY. VAPORS ENTERING SEWERS OR CONFINED SPACES MAY CREATE AN EXPLOSION HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. ELIMINATE SOURCES OF IGNITION. USE EXPLOSION-PROOF TOOLS. SHUT OFF FUEL SOURCE. DIKE SPILL. PREVENT LIQUID FROM ENTERING SEWERS/WATERWAYS. RECOVER FREE LIQUID. ADD SAND, EARTH/OTHER ABSORBENTS. TRANSFER TO CONTAINER.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN ACCORDANCE WITH NATIONAL FIRE PROTECTION ASSOCIATION REGULATIONS. KEEP CONTAINERS CLOSED.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, SOLDER, DRILL OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS. THEY MAY EXPLODE AND CAUSE INJURY/DEATH. AVOID REPEATED OR PROLONGED CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection

=====

Respiratory Protection:IF HIGH VAPOR CONCENTRATION IS EXPECTED, WEAR  
NIOSH-APPROVED ORGANIC RESPIRATOR. USE IN WELL VENTILATED AREA.

Ventilation:LOCAL/MECHANICAL (GENERAL) VENTILATION - EXPLOSION PROOF,  
WELL GROUNDED EQUIPMENTS

Protective Gloves:NITRILE-BUTADIENE FOR FREQUENT USERS

Eye Protection:CHEMICAL SPLASH GOGGLES IF SPLASING

Other Protective Equipment:IMPERVIOUS CLOTHING TO AVOID SKIN AND EYE  
CONTACT. EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:AV

OID CONTACT WITH EYES, SKIN OR CLOTHING. WASH  
HANDS AFTER USING PRODUCT. AVOID BREATHING VAPORS OR MISTS.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME  
NSN.

===== Physical/Chemical Properties =====

HCC:F1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>90F,>32C

Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN

Vapor Pres:>350

Vapor Density:3.4 - 4.0

Spec Gravity:0.71 - 0.78

Evaporation Rate & Reference:>1.0 (   
ETHER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS LIQUID - GASOLINE ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, SPARKS, STATIC ELECTRICITY,  
OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:FUMES, CARBON MONOXIDE, CARBON DIOXIDE  
AND OTHER DECOMPOSITION PRODUCTS MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods: RECYCLE AS MUCH AS POSSIBLE. TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. WASTE NUMBER: D001. RCRA EMERGENCY HOTLINE NUMBER IS 800-424-9346. REPORT SPILLS AS REQUIRED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of

Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.