

EASTMAN KODAK COMPANY -- 121 1804 VNF-1/RVNP LIQUID FIXER & REPLENISHER,  
CONCENTRATE -- 6750-01-083-4302

===== Product Identification =====

Product ID:121 1804 VNF-1/RVNP LIQUID FIXER & REPLENISHER, CONCENTRATE

MSDS Date:04/09/1997

FSC:6750

NIIN:01-083-4302

MSDS Number: BWZMD

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Cou

ntry:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== C

Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE  
CAS:7783-18-8  
RTECS #:XN6465000  
Fraction by Wt: 50-55%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 40-45%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM SULFITE (CERCLA)  
CAS:10196-04-0  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BISULFITE (CERCLA)  
CAS:10192-30-0  
RTECS #:W  
T3595000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM ACETATE (CERCLA)  
CAS:631-61-8  
RTECS #:AF3675000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. EYES:NO SPECIFIC HAZARD KNOWN.MAY CAUSE TRANSIENT IRRITATION. SKIN:LOW HAZARD FOR RECOMMENDED HANDLING. INGEST:EXPECTED TO BE LOW INGESTION HAZARD.

Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY CLASSIFICATION:IARC/ACGIH/NTP/OSHA:NONE.

Effects of Overexposure:TRANSIENT EYE IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====

First Aid Measures =====

First Aid:INHAL:IF SYMPTOMATIC MOVE TO FRESH AIR. GET MED ATTN IF SYMPTONS PERSIST. EYES:ANY MATL THAT CONTACTS EYE SHOULD BE WASHED OUT IMMED W/WATER. GET MED ATTN IF SYMPTOMS OCCUR. SKIN:WASH W/SOAP & WATER. GET MED ATTN IF SYMPTOMS OCCUR. INGEST:DRINK 1-2 GLASSES OF WATER. SEEK MED ATTN. NEVER GIVE ANYTHING BY MOUTH IF UNCONSC.

===== Fire Fighting Measures =====

Flash Point:NONE,NON-COMBUST

Autoi

gnition Temp:Autoignition Temp Text:NP

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER W/LG AMTS OF WATER.OTHERWISE ABSORB W/VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE W/ADEQUATE VENTIALTION.KEE FROM CONTACT W/OXIDIZING MATLS.KEEP CNTNR TIGHTLY CLSD.KEEP AWAY FROM INCOMPATIBLE SUBSTANCES.

Other Precautions:PROPERTIES:MOD BIOCHEM OXY DEMAND,MAY CAUSE OXY DEPLETION IN AQU SYS,LOW POT TO AFFECT AQ

U ORGN,LOW POT TO AFFECT  
2ND WASTE TREAT MICROBIAL METABOLISM,LOW POT TO AFFECT GERM &/OR  
EARLY GROWTH OF SOME PLANTS,LOW POT TO PERSIST IN ENVIRO(SUP)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.  
Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR)  
SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS  
Protective Gloves:IMPERVIOUS GLOVES.  
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS, GOG  
GLES.  
Other Protective Equipment:EYEBATH, WASHING FACILITIES, SAFETY SHOWER.  
Work Hygienic Practices:WASH THOROUGHLY AFT HNDLG.GOOD INDUSTRIAL HYG  
PRAC TO MIN SKIN/EYE CONTACT.  
Supplemental Safety and Health  
OTHER PRECAUT:LOW POT TO BIOCONCEN.AFT DIL W/LG AMT OF WATER & 2ND  
WASTE TREAT,MATL NOT EXPECTED TO CAUSE ADVERSE ENVIRO EFFECTS.

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:>212F,>100C  
Melt/Freeze Pt:M.P/F.P Text:NP  
Decomp Temp:  
Decomp Text:NP  
Vapor Pres:18  
Vapor Density:0.6  
Spec Gravity:1.08  
pH:6.0  
Viscosity:NP  
Evaporation Rate & Reference:NP  
Solubility in Water:COMPLETE  
Appearance and Odor:LIQUID, COLORLESS, ODORLESS  
Percent Volatiles by Volume:45-50  
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS,SODIUM HYPOCHLORITE(BLEACH),STRONG OXIDIZING  
AGENTS,BASES.CONTACT W/BASE LIBERATES FLAMM MATERIAL.  
Stability Condition t

o Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE(NON-COMBUSTIBLE). HAZ DECOMPO  
PROD:AMMONIA,SULFUR DIOXIDE, NITROGEN OXIDES (NOX),CHLORAMINE.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO  
NATIONAL/STATE/LOCAL LAWS. FLUSH TO SEWER W/LG AMTS OF WATER. NO  
SEC 313 TITLE III SARA/40CFR372 CHEMICALS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.