View NSN Online: https://aerobasegroup.de/nsn/6810-00-275-6010

WARD'S NATURAL SCIENCE -- METHYL ALCOHOL -- 6810-00-275-6010

Product ID:METHYL ALCOHOL MSDS Date:10/20/1992 FSC:6810 NIIN:00-275-6010 MSDS Number: BXCFK === Responsible Party === Company Name: WARD'S NATURAL SCIENCE Box:92912 **City:ROCHESTER** State:NY ZIP:14692-9012 Country:US Info Phone Num:716-359-2502 Emergency Phone Num:800-424-9300(CHEMTREC) Preparer's Name:ALE XANDER A. PICCIRILLI CAGE:EO227 === Contractor Identification === Company Name: WARD'S NATURAL SCIENCE ESTABLISHMENT INC. Box:92912 City:ROCHESTER State:NY ZIP:14692-9012 Country:US Phone:716-359-2502 CAGE:EO227 Company Name: WARDS NATURAL SCIENCE ESTABLISHMENT INC Address:5100 W HENRIETTA RD Box:92912 City:ROCHESTER State:NY ZIP:14692-9012 Country:US Phone:(716) 359-2502 CAGE:63759

Ingred Name: METHYL ALCOHOL (METHANOL) (SARA

III) CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:S,200PPM ACGIH TLV:S,200PPM/250STEL; 94 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:OSHA TWA 200PPM, 260MG/M3
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGEST:MAY BE FATAL.CANNOT BE MADE NON-POISONOUS.SWALLOWI
NG LIQ CAUSES INEBRIATION, HEADACHE, NAUSEA, VOMITING LEADING TO SEVERE ILLNESS, BLINDNESS & PERHAPS DEATH. EYE:LIQ CAUSES IRRIT. INHAL:BREATHI NG VAP MAY CAUSE DROWSINESS, NAU, VOMITING. SKIN:REPEATED CONTACT MAY IRRITATE SKIN.
Effects of Overexposure:FATAL IF INGESTED. INEBRIATION, HEADACHE, NAUSEA, VOMITING. SEVERE ILLNESS. BLINDNESS. DEATH. EYE/SKIN IRRITATION. DROWSINESS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

======= First

First Aid:INGEST:IF CONSC GIVE 1 OR 2 GLASSES OF WATER TO DRINK.INDUCE VOMIT BY PLACING FINGER DOWN THROAT.REPEAT TIL VOMIT FLUID IS CLEAR.CALL DR IMMED.NEVER GIVE ANYTHING BY MOUTH TO UNCONSC PERSON.INHAL:REMO VE TO FRESH AIR.NOT BREATH GIVE ARTI RESP(MOUTH-TO-MOUTH)BREATH DIFFI GIVE OXY BY TRAINED PERSONNEL.CALL DR.EYE:FLUSH W/PLENTY OF WATER FOR @LEAST 15MINS LIFTING EYELIDS.GET MED ATTN IMMED.(SUPPLEMEN)

====== F

Flash Point Method:TCC Flash Point:52.0F,11.1C Autoignition Temp:Autoignition Temp Text:385C Lower Limits:6. @79F Upper Limits:36.5 Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL (ABC), ALCOHOL TYPE FOAM. CLASS IB FLAMMABLE LIQUID. Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA & FULL PROT CLOTH.WATER MAY BE INEFFECTIVE.USE WATERSPRAY TO COOL FIRE-EXPO CNTNRS.USE ALCOHOL RESIST FOAM TI EXT LG FIRE/BLANKET SPILL Unusual F ire/Explosion Hazard:BURNS W/CLEAR ALMOST INVISIBLE FLAME-HARD TO SEE IN STRONG SUNLIGHT.METHANOL/WATER MIXTURE W/25% OR MORE METHANOL-FLAMM.AVOID WATER WATERSTREAMS THAT (SUPPLEMN)

Spill Release Procedures:ELIMINATE ALL IGN SOURCES.USE ABSORBENT MATLS TO SOAK UP SPILLS(SAND/EARTH/VERMICULITE).CAREFULLY SWEEP UP & REMOVE.SPILLS IN CRITICAL AREAS CAN BE DILUTED W/WATER TO REDUCE FIRE HAZ DURING CLEANUP.DO NO T FLUSH TO SEWER/DRAIN/WATERWAYS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA AWAY FRM STRONG OXIDIZERS & FIRE HAZ.KEEP OUT OF REACH OF CHILDREN. Other Precautions:USE EXPLOSIVE-RPOOF ELECTRICAL FIXTURES.CNTNRS SHOULD BE ELECTRICALLY GROUNDED/BONDED DURING MATL TRANSFER TO PREVENT STATIC SPARK.CORROSIVE TO LEAD & ALUMINUM.FOR LABORATORY USE

ONLY.NOT FOR DRUG/FOO D/HOUSEHOLD USE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NEEDED IN NORMAL LABORATORY HANDLING. IF MISTY CONDITONS PREVAIL WORK IN VENTILATION HOOD OR WEAR NIOSH-APPROVED RESPIRATOR AIR-SUPPLIED OR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHA:RECOMMENDED. MECHANICAL(GEN):YES. OTHER:ADEQUATE TO MAINTAIN BELOW EXPOSURE LIMIT.

Protective Gloves: RUBBER GLOVES

Eye Protection:CHEMICAL S

AFETY GLASSES

Other Protective Equipment:GOGGLES,SMOCK,APRON,EYEWASH STATION,SAFETY SHOWER,PROPER GLOVES,VENTILATION HOOD,FIRE EXTINGUISHER.

Work Hygienic Practices: WSH THOROUGHLY AFTER HANDLING. REMOVE & WAST CONTAMINATED CLOTHING.

Supplemental Safety and Health

EXPLO/FIRE HAZ:SPREAD FLAMING LIQ.VAP HEAVIER THAN AIR-MAY FLOW ALONG SURFACES TO DISTANT IGN SOURCES & FLASHBACK. 1STAID:SKIN:FLUSH W/WATER THEN WASH W/MILD SOAP/WATER.FOR ALL ROUTES:KEEP PATIENT WAR M & COVER EYES

TO EXCLUDE LIGHT.

HCC:F5 Boiling Pt:B.P. Text:148F,65C Melt/Freeze Pt:M.P/F.P Text:-144F,-98C Vapor Pres:96 @20C Vapor Density:1.11 Spec Gravity:0.7913 Evaporation Rate & amp; Reference:12.5% (N-BUTYL ACETATE=1) Solubility in Water:COMPLETE Appearance and Odor:CLEAR, COLORLESS LIQUID, ALCOHOL ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials
to Avoid:YES
STRONG OXIDIZING AGENTS. PARTICULARLY PERCHLORIC ACID & LEAD PERCHLORATE, SULFURIC & NITRIC ACIDS, CHROMIC ANHYDRIDE.
Stability Condition to Avoid:SPARKS, EXCESSIVE HEAT, SOURCES OF IGNITION, OPEN FLAME, STATIC CHARGE.
Hazardous Decomposition Products:THERMAL DECOMPOSITION OR BURNING WILL PRODUCE CARBON DIXOIDE &/OR CARBON MONOXIDE.

Waste Disposal Methods: DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO

FED/STATE/LOC LAWS.THESE DISPOSAL GUIDELINES ARE INTENDED FOR DISPOSAL OF CATALOG-SIZE QUANT ONLY.DISPOSE OF IN AN APPROVED INCINERATOR OR CONTRACT W/LIC ENSED SOLVENT WASTE DISPOSAL SERVICE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all I

iability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.