

MOBIL OIL CORP -- MOBIL 600 W CYLINDER OIL -- 9150-01-202-3604

===== Product Identification =====

Product ID:MOBIL 600 W CYLINDER OIL

MSDS Date:03/15/1994

FSC:9150

NIIN:01-202-3604

MSDS Number: BXCPR

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-7

37-4411/CHEMTREC 800-424-9300

Preparer's Name:ENV HEALTH + SAFETY DEPT.

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =====

=

Ingred Name:SEVERELY SOLVENT REFINED & SEVERELY HYDROTREATED MINERAL
BASE OILS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC CONTENT=0.075 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chron

ic:ACUTE: LOW HEALTH HAZARD. MINIMAL

IRRITATION ON CONTACT. INHALATION OF VAPORS OR MISTS WHEN SPRAYING
MAY CAUSE IRRITATION. SLIGHTLY TOXIC IF SWALLOWED. CHRONIC:
DERMATITIS. ACCIDENTAL RELEASE UNDER HI GH PRESSURE APPLICATIONS
MAY RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL
NECROSIS.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYES: MINIMAL IRRITATION. SKIN: IRR
ITATION,

SKIN DRYING ON PROLONGED CONTACT. INHALATION: IRRITATION OF NOSE
AND THROAT. INGESTION: DISCOMFORT, NAUSEA, DIARRHEA. INJECTION:
NECROSIS MAY BE EVIDENCED B Y DELAYED ONSET OF PAIN AND TISSUE
DAMAGE A FEW HOURS FOLLOWING PRESSURE INJECTION.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS DEFATTING
PROPERTIES, PROLONGED AND REPEATED SKIN CONTACT MAY AGGRAVATE AN
EXISTING DERMATITIS.

===== First Aid Measures =====

First Ai

d:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF
IRRITATION PERSISTS, SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, SEE DOCTOR. INHALATION: UNLIKELY ROUTE OF
EXPOSURE . INGESTION: DO NOT INDUCE VOMITING. SEE DOCTOR.
INJECTION: THIS IS A MEDICAL EMERGENCY. SEE DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:540F,282C

Lower Limits:0.6

Upper Limits:7

Extinguishing Media:

USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PERSONNEL. ELIM
INATE IGNITION SOURCES.

VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND EQUIPMENT. DIKE AND
CONTAIN. ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL
CONTAINER AND COVER. WASH AREA WITH SOAP AND
WATER.NRC,800-424-8802.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH
ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG
OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other P

recautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED
RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:MECHANICAL (GENERAL) VENTILATION.

Protective Gloves:NITRILE GLOVES.

Eye Protection:SPLASH GOGGLES IF MISTING.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE
EXPOSURE FROM PROLONGED OR REPEATED CONTAC

T. EYE BATH AND SAFETY
SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISCARD
CONTAMINATED SHOES

Supplemental Safety and Health

USED GASOLINE MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER WHEN
REPEATEDLY APPLIED TO MOUSE SKIN WITHOUT ANY EFFORT TO REMOVE THE
MATERIAL BETWEEN APPLICATIONS. THERE IS NO EVIDENCE OF A CAUSAL REL
ATIONSHIP BETWEEN SKIN CANCER IN HUMANSAND EXPOSURE TO USED MOTOR

OIL.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>600F,>316C
Melt/Freeze Pt:M.P/F.P Text:15.8F,-9.0C
Vapor Pres:1
Spec Gravity:0.901
Viscosity:375CS@104F
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIQUID;BROWN;MILD ODOR.
Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH HEAT.
Hazar
dous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.
DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or i
mplied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.