

METAL LUBRICANTS CO -- WINSOR LUBE L-245-X -- 9150-00-753-4667

=====
Product Identification
=====

Product ID:WINSOR LUBE L-245-X

MSDS Date:08/15/1994

FSC:9150

NIIN:00-753-4667

MSDS Number: BXFQW

=== Responsible Party ===

Company Name:METAL LUBRICANTS CO

Address:17050 LATHROP AVE

Box:8327

City:HARVEY

State:IL

ZIP:60426

Country:US

Info Phone Num:800-323-7755

Emergency Phone Num:800-255-3924

Prepare

r's Name:LAWRENCE COHEN

CAGE:10873

=== Contractor Identification ===

Company Name:FUCHS LUBRICANTS CO

Address:17050 LATHROP AVE

Box:8327

City:HARVEY

State:IL

ZIP:60426

Country:US

Phone:708-333-8900

CAGE:10873

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM SULFONATE

CAS:25619-56-1

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of

Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MODERATE IRRITANT TO SKIN AND EYES. CHRONIC: NO DATA AVAILABLE.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:INGESTION MAY CAUSE DIARRHEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES-IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES AND CALL A PHYSICIAN. SKIN CONTACT-FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. INHALATION-REMOVE TO FRESH AIR. CONSULT A PHYSICIAN IF DISCOMFORT PERSISTS. IF SWALLOWED-CONTACT A PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>399F,>204C
Extinguishing Media:DRY CHEMICAL OR CARBON DIOXIDE OR FOAM. WATER MAY CAUSE FROTHING. CLOSED CONTAINER EXPOSED TO FIRE MAY BE COOLED W/WATER
Fire Fighting Procedures:USE SUPPLIED BREATHING AIR AND PROTECTIVE CLOTHING. A SOLID STREAM OF WATER INTO HOT BURNING LIQUID CAN CAUSE FROTHING.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB WITH AN INERT MATERIAL SUCH AS SAND, SOIL OR VERMICULITE; SWEEP UP AND DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID SKIN AND EYE CONTACT. DO NOT SWALLOW.
Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE IF VENTILATION IS GOOD.
Ventilation:LOCAL IF NECESSARY TO MAINTAIN ALLOWABLE TWA OR TLV.
Protective Gloves:RUBBER.
Eye Protection:CHEMICAL SAFETY GOGGLES.
Other Protective Equipment:NONE.
Work Hygienic Practices:WASH AFTER HANDLING.
Supplemental Safety and Health D.O.T.: NOT REGULATED.

=====
Physical/Chemical
=====

mical Properties =====

HCC:V6

Vapor Pres:100 SUS

Solubility in Water: