

LHB INDUSTRIES -- ECO SURE, BLACK, 37038 (0674-390), 0672D899

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-331-6108
MSDS Date: 04/28/1995
MSDS Num: BXHBX
Product ID: ECO SURE, BLACK, 37038 (0674-390), 0672D899
MFN: 03
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: S
AINT LOUIS MO 63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 314-522-3141 OR 800-424-9300
Preparer's Name: GREGORY K. MCGOWAN
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-2787
Type/Grade/Class: TYPE I
Unit of Issue: PT
UI Container Qty: 0
Type of Container: METAL
=====

Ingredients

Cas: 108-88-3

RTECS #: XS5250000

Name: TOLUENE (SARA 313) (CERCLA)

% Wt: 15.24

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 200 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

% Wt: 12.82

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 1000 PPM

ACGIH TLV: 1000 PPM

Cas: 115-10-6

RTECS #: PM4780000

Name: DIM

ETHYL ETHER

% Wt: 7.12

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 110-12-3

RTECS #: MP3850000

Name: 5-METHYL-2-HEXANONE

% Wt: 6.48

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 50 PPM

ACGIH TLV: 50 PPM

Cas: 64742-95-6

RTECS #: ZE2190000

Name: AROMATIC 100

% Wt: 6.48

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 50 PPM

Cas: 64742-9

5-6

RTECS #: ZE2190000

Name: AROMATIC 150

% Wt: <3.24

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 5 PPM

Cas: 1330-20-7

RTECS #: ZE2100000

Name: XYLENE (SARA III) (CERCLA)

% Wt: <3.24

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 100 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Cas: 107-87-9

RTECS #: SA7875000

Name: 2-PENTANONE

% Wt: <3.24

Other REC Limits: NONE RECOMMENDED

OSHA

PEL: 200 PPM

ACGIH TLV: 200 PPM

Cas: 108-10-1

RTECS #: SA9275000

Name: 4-METHYL-2-PENTANONE

% Wt: <3.24

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 100 PPM

ACGIH TLV: 50 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Cas: 95-63-6

RTECS #: DC3325000

Name: 1,2,4-TRIMETHYLBENZENE (SARA III)

% Wt: <3.24

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 25 PPM

Cas: 71-36-3

Name:

N-BUTANOL (SARA III) (CERCLA)

% Wt: <3.24

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 50 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTE

NTS MAY BE HARMFUL OR FATAL. IN CONFINED AREAS VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITATION TO SKIN, EYES, THROAT AND RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. MAY CAUSE HEADACHES, NAUSEA AND VOMITING.

Signs And Symptoms Of Overexposure: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING GAIT, GIDDI NESS AND POSSI BLE NAUSEA.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

First Aid: SKIN OR CLOTHES: WASH WITH SOAP AND WATER. WASH CLOTHES BEFORE REUSE. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONTACT PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID . NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION IF NECESSARY. GET MEDICAL AID.

=====
H
andling and Disposal
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF IN ACCORD W/APPLICABLE FEDERAL, STATE & LOCAL REGS. DON'T PUNCTURE, INCINERATE (BURN) OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TOBURST. DISCARD EMPTY CAN IN TRASH PICK-UP. DO NOT PLACE IN COMPACTOR.

Ha

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE. DON'T STORE WHERE TEMPS >120F/48.9C. AVOID BREATH SPRAY, MIST, VAPOR. AVOID SKIN & EYE CONTACT

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL.

=====
Fire and Explosion Hazard Information
=====

Autoignition Temp Text: 662F

Lower Limits: 2.2%

Upper Limits: 18.0%

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. USE TO KEEP FIRE EXPOSED CONTNRS COOL. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING, VENTING OF CONTAINERS

Unusual Fire/Exp

losion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPS (ABOVE 120F) CONTAINERS MAY VENT, RUPTURE, BURST. AEROSOL CONTAINER. DO NOT EXPOSE TO TEMPERATURE ABOVE 120F.

=====
Control Measures
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Prot

ective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

HCC: V3

Vapor Pres: 70 @ 68F

Vapor Density: >1.522

Volatile Org Content %: 60

Spec Gravity: 1.188

Solubility in Water: INSOLUBLE
Appearance and Odor: BLACK/PAINT

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT
Hazardous Decomposition Products: CARBON MONOXIDE
Hazardous Polymerization Indicator: NO
=====

Toxicological Information
=====

=====
Ecological Information
=====

MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

=====
Other Information: VOC: 60%; 583 G/L
=====

Transportation Information
=====

Responsible Party Code: 0FTT5
Trans ID NO: 126044
Product ID: ECO SURE, BLACK, 37038 (0674-390), 0672D899
MSDS Prepared Date: 04/28/1995
Review Date: 06/15/1995
MFN: 3
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0
Type Of Container: METAL
=====

=====
Detail DOT Information
=====

DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

=====
Detail IMO Information
=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

=====
Detail IATA Information
=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passengers: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

=

HAZCOM Label

=====

Product ID: ECO SURE, BLACK, 37038 (0674-390), 0672D899

Cage: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CON

TENTS MAY BE HARMFUL OR FATAL. IN CONFINED AREAS VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITATION TO SKIN, EYES, THROAT AND RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. MAY CAUSE HEADACHES, NAUSEA AND VOMITING. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLV ENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA.

=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.