

NILES CHEMICAL PAINT CO -- 2345A GREEN PRIMER, PART A -- 8010-01-350-4742

=====
Product Identification
=====

Product ID:2345A GREEN PRIMER, PART A
MSDS Date:12/20/1994
FSC:8010
NIIN:01-350-4742
Kit Part:Y
MSDS Number: BXHDF
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT CO
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:616-683-3377
Emergency P
hone Num:219-236-5856
Preparer's Name:MIKE LICHATOWICH
CAGE:02388

==== Contractor Identification ====
Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 42%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BUTYL ALCOHOL (SARA 313) (CERCLA) (VAPOR PRESSURE 4.4 MM HG

@ 20C)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 27%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM (SKIN)
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYAMIDE/EPOXY ADDUCT
Fraction by Wt: 17%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 8%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMIDOAMINE-RESIN
CAS:68443-08-3
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY INGREDIENTS (MFR STATES UNIDENTIFIED INGREDIENTS NOT CONSIDERED HAZARDOUS UNDER FEDERAL HAZARD COMM REGS)
Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 3.24 LBS/GAL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:79.0F,26.1C
Lower Limits:1.0
Upper Limits:11.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:WEAR SCBA W/FULL FA

CPIECE (POSITIVE PRESSURE

MODE) & FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. VAPOR HEAVIER THAN AIR, TRAVEL ON GRND TO IGNIT SOURCE. NO HEAT/IGNIT. CLSD CNTNRS MAY EXPLODE W/HEAT. APP TO HOT SRFC REQUIRE SPCL PRECAUTIONS

=====
===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =
=====

HCC:F3

Boiling Pt:B.P. Text:242 TO 325F

Vapor Density:> AIR

Spec Gravity:1.398

Viscosity:100-112KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume:48.05

Corrosion Rate:MINIMAL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WILL SOFTEN POLYETHYLENE, OLYPROPYLENE, VC CONTAINERS, OXIDIZERS,
STRONG OXIDIZERS

St

ability Condition to Avoid:HIGH TEMPERATURES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of

this information to their particular situation.