

NILES CHEMICAL PAINT CO -- 2439B WHITE: COMP B -- 8010-01-350-4742

=====
Product Identification
=====

Product ID:2439B WHITE: COMP B
MSDS Date:12/20/1994
FSC:8010
NIIN:01-350-4742
Kit Part:Y
MSDS Number: BXHDG
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT CO
Address:225 FORT ST
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:616-683-3377 OR 219-236-5856
Emergency Phone Num:616-683-3377 OR 219-236-5856
Preparer's Name:MIKE LICHTOWICH
CAGE:02388

==== Contractor Identification ====

Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN
CAS:25068-38-6
RTECS #:KC2100000
Fraction by Wt: 49%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VM&P NAPHTHA (VAPOR PRESSURE 15 MM HG @ 3

7.7C)
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 24%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM;STEL 400 PPM

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 9%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYAMIDE
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY INGREDIENTS (MFR STATES UNIDENTIFIED
INGREDIENTS NOT CONSIDERED HAZARDOUS UNDER FEDERAL HAZARD COMM
REGS)
Fraction by Wt: BALANCE
Other REC Limits:
NONE RECOMMENDED

Ingred Name:VOC: 2.35 LBS/GAL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:50.0F,10.0C
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:WEAR SCBA W/FULL FACPIECE (POSITIVE PRESSURE
MODE) & FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO
PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.
Unusual Fire

/Explosion Hazard:KEEP CNTNR CLSD.VAPOR HEAVY,TRAVEL ON
GRND TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR EXPLODE W/HEAT.APPLIC
TO HOT SRFCS REQ SPCL CAUTN.DECOMP PRODUCT-HEALTH HZD.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:285F,141C

Vapor Density:> AIR

Spec Gravity:1.149

Viscosity:76 - 89 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume:38.26

Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HIGH TEMPERATURES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America
in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.