

ENERGIZER POWER SYSTEMS -- ENERGIZER RECHARGEABLE POWER SYSTEMS BATTERY --
6140-01-165-2073

=====
Product Identification
=====

Product ID:ENERGIZER RECHARGEABLE POWER SYSTEMS BATTERY

MSDS Date:11/29/1994

FSC:6140

NIIN:01-165-2073

MSDS Number: BXJXR

=== Responsible Party ===

Company Name:ENERGIZER POWER SYSTEMS

Address:US HIGHWAY 441N

City:ALACHUA

State:FL

ZIP:32615

Country:US

Info Phone Num:904-46

2-3911 OR 216-835-7368

Emergency Phone Num:904-462-3911

Preparer's Name:JOANN RAULERSON

CAGE:EO263

=== Contractor Identification ===

Company Name:ENERGIZER POWER SYSTEM, DIV. OF EVEREADY BATTERY

Address:US HIGHWAY 441N

Box:City:ALACHUA

State:FL

ZIP:32615

Country:US

Phone:440-835-7368

CAGE:EO263

Box:UNKNOW

CAGE:ENER1

=====
Composition/Information on Ingredients
=====

Ingred Name:CADMIUM OXIDE (SARA III) THE CADMIUM INGREDIENTS (1, 2 &
3) TOTAL 13 TO 22%

CAS:1306-19-0

RTEC

S #:EV1925000
Fraction by Wt: 13-22%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 MG (CD)/M3 DUST
ACGIH TLV:0.01 MG(CD)/M3; 9394

Ingred Name:CADMIUM HYDOXIDE
CAS:21041-95-2
Fraction by Wt: SEE #1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 MG/M3 (AS CD)
ACGIH TLV:0.01 MG/M3 (AS CD)

Ingred Name:CADMIUM HYDROXIDE
CAS:21041-95-2
Fraction by Wt: SEE #1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG CD/M3
ACGIH TLV:0.05 MG CD/M3

Ingred Name:COBALT (SARA 313) COBALT INGREDIENTS (4, 5 & 6) TOTAL 0.5 TO 2%.
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 0.5-2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.02 MG/M3; A3; 9495

Ingred Name:COBALT HYDROXIDE
CAS:21041-93-0
RTECS #:GG0904500
Fraction by Wt: SEE #4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3 (CO)
ACGIH TLV:0.05 MG/M3 (CO)

Ingred Name:COBALT OXIDE
CAS:1307-96-6
RTECS #:GG2800000
Fraction by Wt: SEE #4%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NICKEL (SARA 313) (CERCLA) THE NICKE

L INGREDIENTS (7, 8 &
9) TOTAL 20 TO 32%.

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 20-32%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9495

Ingred Name:NICKEL OXIDE

CAS:1313-99-1

RTECS #:QR8400000

Fraction by Wt: SEE #7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3 AS NI

ACGIH TLV:1 MG/M3 AS NI

Ingred Name:NICKEL HYDROXIDE (SARA 313) (CERCLA)

CAS:12054-48-7

RTECS #:QR7040000

Fraction by Wt: SEE #7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG(NI)/M3

ACGIH TLV:0.1 MG(NI)/M3; 9495

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: 0-4%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM HYDROXIDE (CERCLA)

CAS:1310-73-2

RTECS #:WB4900000

Fraction by Wt: 0-4%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:C 2 MG/M3; 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===

KEL OXIDES, CADMIUM, CADMIUM OXIDES & COBALT OXIDE
Unusual Fire/Explosion Hazard:MFR GAVE NO INFORMATION ON MSDS.

===== Accidental Release Measures =====

Spill Release Procedures:MFR GAVE NO INFORMATION ON MSDS.
Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, WELL VENTILATED AREA.
ELEVATED TEMPERATURES CAN RESULT IN SHORTENED BATTERY LIFE.
DO NOT

OBSTRUCT SAFETY RELEASE VENTS ON BATTERIES.

Other Precautions:IF SOLDERING OR WELDING IS REQUIRED, USE OF TABBED
BATTERIES IS RECOMMENDED. IF THIS CANNOT BE DONE, CONSULT YOUR
EVEREADY BATTERY COMPANY REPRESENTATIVE FOR PROPER PRECAUTIONS TO
PREVENT SEAL DAMAGE OR SHORT CIRCUIT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY UNDER NORMAL CONDITIONS.

Ventilation:NOT NECESSARY UNDER NORMAL CONDITIONS.

Protective G

oggles:NOT NECESSARY UNDER NORMAL CONDITIONS.

Eye Protection:NOT NECESSARY UNDER NORMAL CONDITIONS.

Other Protective Equipment:MFR GAVE NO INFORMATION ON MSDS. WEAR SAFETY
GLASSES & NEOPRENE OR RUBBER GLOVES WHEN HANDLING LEAKING & OPEN
BATTERIES.

Work Hygienic Practices:MFR:? HMIS:USE GOOD INDUSTRIAL HYGIENE
PRACTICES. DO NOT OBSTRUCT SAFETY RELEASE VENTS ON BATTERIES.

Supplemental Safety and Health

BATTERY IS CAPEABLE OF HIGH SHORT CERCUIT CURRENT & BATTERY MAY BECOME
HOT ENOUGH

TO BURN IF SHORTED FOR MORE THAN A SHORT PERIOD. -

BATTERY IS MADE TO BE RECHARGED. USE RECOMMENDED CHARGER. IMPROPER
CHARGING MAY RESULT IN DAMAGE TO BATTERY &/OR BURNS TO USER. -

DURING CHARGING BATTERIES EVOLVE EXPOLSIVE HYDROGEN.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Appearance and Odor:MFR GAVE NO INFORMATION ON MSDS.

===== Stability and Reactivity Data =====

Stability Indicator/Material

s to Avoid: YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: NICKEL, NICKEL OXIDES, CADMIUM,
CADMIUM OXIDES, & COBALT OXIDE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF I/A/W ALL APPLICABLE FEDERAL, STATE
AND LOCAL REGULATIONS. THIS BATTERY, AS A WASTE, IS REGULATED BY
THE RESOURCE CONSERVATION AND RECOVERY ACT [RCRA] AS A D006
[CADMIUM
] HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.