

P-T TECHNOLOGIES INC -- PF-145HP

=====
MSDS Safety Information
=====

FSC: 6800
NIIN: 13-780-0044
MSDS Date: 10/21/1994
MSDS Num: BXKCH
Product ID: PF-145HP
MFN: 01
Responsible Party
Cage: 0JVH6
Name: P-T TECHNOLOGIES INC
Address: 108 4TH AVENUE, SOUTH
City: SAFETY HARBOR FL 34695
Info P
Phone Number: 800-441-7874/813-726-4644
Emergency Phone Number: 813-726-4644/800-441-7874
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 0JVH6
Name: P-T TECHNOLOGIES INC
Address: 108 4TH AVENUE, SOUTH
City: SAFETY HARBOR FL 34695
Phone: 813-726-4644

=====
Item Description Information
=====

Item Manager: S9G
Item Name: CLEANING COMPOUND,SOLVENT
Specification Number: UNKNOWN
Unit of Issue: BX
UI Container Qty: 6 X 1 GALLONS
Type of Container: CANS

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

=
LD50 LC50 Mixture: UNKNOWN
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: EYE:MAY CAUSE IRRIT,DOES NOT INJURE EYE.
SKIN:PROLONG/REPEAT CONTACT MAY CAUSE DEFATTING OR DRYNESS.CONTD DRYNESS MAY
CAUSE DERM. INHAL:EXCESSIVE INHAL OF VAP CAN CAUSE IRRIT OF RESP
TRACT,NAUSEA,DIZZ ,HEADACHE. INGEST:HAS LOW ORDER OF ACUTE ORAL
TOXICITY.INGEST OF LG QYANT MAY CAUSE NAU,VOMIT,GI IRRIT.IF ASPIRATED(SUP)

Signs An

d Symptions Of Overexposure: EYE IRRITATION. DERMATITIS, SKIN DRYNESS
& DEFATTING. RESP TRACT IRRIT, NAUSEA, DIZZINESS, HEADACHE.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYE:FLUSH W/WATER FOR 15MINS. IRRIT PERSISTS CONTACT PHYSICIAN.

SKIN:WASH THOROUGHLY W/SOAP/WATER. REMOVE CONTAMIN CLOTHING. INHAL:GET TO
FRESH AIR. IF BREATHING IS DIFFICULT SEE PHYSICIAN. INGEST:DO N OT INDUCE
VOMITING. PRODUCT CONTAINS HYDROCARBON. CONSULT PHYSICIAN.

=====

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE IGN SOURCES.CONTAIN. RECOVER FREE PRODUCT.
ABSORB W/SUITABLE CHEM ABSORBENT FOR DISPOSAL VIA INCINERATION OR BURIAL IN
APPROVED LANDFILL. OBSERVE LOCAL, STATE AND FEDERAL REGULATIONS. REMOVE FR OM
WATER SPILL BY SKIMMING/SUITABLE ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: OBSERVE LOCAL, STA
TE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: USE PROPER GROUNDING PROCEDURES. STORAGE
TEMP:AMBIENT. KEEP AWAY FROM HEAT SOURCES, OPEN FLAMES & OTHER IGNITION
SOURCES.

Other Precautions: KEEP OUT OF REACH OF CHILDREN. PHOTOCHEMICALLY REACTIVE
MATERIAL PRESENT:YES, <80% BY VOL OF PHOTOCHEM REACTIVE MATL.

=====

Fire and Explosion Hazard Information

=====

Flash Point Met

hod: TCC

Flash Point Text: 145F,63C

Autoignition Temp Text: 830F

Lower Limits: 1.8 @77F

Upper Limits: 11.7 @77F

Extinguishing Media: COMBUSTIBLE LIQUID, EXTINGUISH WITH CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures: CLASS B FIRE PROCEDURES.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

=====
Control Measures
=====

Respiratory Protection: NONE SPECIFIED BY MANUFACTURER.

Vent

ilation: NORMAL RM VENTI IS ADEQUATE.USE FANS/OTHER MECHANICAL VENTI IN ENCLOSED AREAS WHERE LG QUANTITIES OF PRODUCT ARE USED.

Protective Gloves: SOLVENT RESISTANT GLOVES.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH CONTAMIN CLOTHING PRIOR TO REUSE. WASH HANDS AFTER HANDLING.

Supplemental Safety and Health: HEALTH HAZ:INTO LUNGS MAY CAUSE INJURY.

=====
Physical/Che
mical Properties
=====

HCC: V4

B.P. Text: 360F,182C

Vapor Pres: 1 @20C

Vapor Density: >1

Spec Gravity: 0.86

Evaporation Rate & Reference: 11.9(N-BUTYL ACETATE=100)

Solubility in Water: NON-SOLUBLE.

Appearance and Odor: COLORLESS LIQUID WITH CHARACTERISTIC ODOR.

Percent Volatiles by Volume: 100

=====
Reactivity Data
=====

Stability Indicato

r: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER HOWEVER AVOID ALL IGNITION SOURCES.

Materials To Avoid: STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
=====
MSDS Transport Information
=====
=====

=====
=====
Regulatory Information
=====
=====

=====
=====
Other Information
=====
=====

=====
=====
Transportation Information
=====
=====

Responsible Party Cage: 0JVH6
Trans ID NO: 137355
Product ID: PF-145HP
MSDS Prepared Date: 10/21/1994
Review Date: 08/16/1995
MFN: 1
Net Unit Weight: 6 X 7.2 LBS
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: BX
Container QTY: 6 X 1 GALLONS
Type Of Container: CANS
Additional Data: PER MSDS:DOT PROPER SHIPPING NAME/HAZ CLASS/ID NO:NONE
SPECIFIED BY MANUFACTURER.

=====
=====
Detail DOT Information
=====
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====
=====

=====
=====
Detail IMO Information
=====
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====
=====

=====
=====
Detail IATA Information
=====
=====

=====
IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

HAZCOM Label
=====

Product ID:

PF-145HP

Cage: 0JVH6

Company Name: P-T TECHNOLOGIES INC

Street: 108 4TH AVENUE, SOUTH

City: SAFETY HARBOR FL

Zipcode: 34695

Health Emergency Phone: 813-726-4644/800-441-7874

Label Required IND: Y

Date Of Label Review: 08/16/1995

Status Code: C

Label Date: 08/16/1995

Year Procured: 1995

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Moderate

Reactivity Hazard: None

Hazard And Precautions: EYE:MAY

CAUSE IRRIT,DOES NOT INJURE

EYE.SKIN:PROLONG/REPEAT CONTACT MAY CAUSE DEFATTING/DRYNESS.CONTD DRYNESS
MAY

CAUSE DERM.INHAL:EXCESSIVE INHAL OF VAP CAN CAUSE IRRIT OF RESP

TRACT,NAU,DIZZ,HEAD.IN GEST:HAS LOW ORDER OF ACUTE ORAL TOXICITY.INGEST OF LG

QUANT MAY CAUSE NAU,VOMIT,GI IRRIT.ASPIRATED INTO LUNGS MAY CAUSE INJURY.USE

PROPER GROUNDING PROCEDURES.KEEP AWAY FRM HEAT SOURCES/OPN FLAMES/OT HER
IGN

SOURCES.1ST AID:EYE:FLUSH W/WATER 15MINS.IRRIT PERSISTS CONTACT

PHYSICIAN.SKIN:WASH

WELL W/SOAP/WATER.REMOVE CONTAMIN CLOTH.INHAL:GET TO
FRESH AIR.DIFF BREATH SEE PHYSICIAN.INGEST:DO NOT INDUCE VOMIT.MATL CONTAINS
HYDROCARBON.CONSULT PHYSICIAN

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information t
o have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
par
ticular situation regardless of similarity to a corresponding Department
of Defense or other government situation.