

E M SCIENCE DIV OF E M INDUSTRIES INC -- LX0323 LITHANE -- 6505-00-137-7743

=====  
Product Identification  
=====

Product ID:LX0323 LITHANE

MSDS Date:03/01/1991

FSC:6505

NIIN:00-137-7743

MSDS Number: BXNWJ

=== Responsible Party ===

Company Name:E M SCIENCE DIV OF E M INDUSTRIES INC

Address:480 DEMOCRAT RD

Box:70

City:GIBBSTOWN

State:NJ

ZIP:08027-0070

Country:US

Info Phone Num:800-222-0342/609-354-920

0

Emergency Phone Num:800-222-0342/609-354-9200

CAGE:63612

=== Contractor Identification ===

Company Name:E M SCIENCE DIV OF E M INDUSTRIES INC

Address:480 DEMOCRAT ROAD

Box:70

City:GIBBSTOWN

State:NJ

ZIP:08027

Country:US

Phone:800-222-0342/609-423-6300

CAGE:63612

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LITHIUM CARBONATE

CAS:554-13-2

RTECS #:OJ5800000

Fraction by Wt: 100%

=====  
Hazards Identification  
=====

LD50 LC50 M

ixture:ORAL LD50 (MOUSE): 531 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HARMFUL BY INGESTION. POSSIBLY HARMFUL BY OTHER ROUTES. INHALATION OF DUST CAUSES IRRITATION OF UPPER RESPIRATORY TRACT. CONTACT W/SKIN/EYES CAUSES IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HARMFUL BY INGESTION. POSSIBLY HARMFUL BY OTHER ROUTES. INHALATION OF DUST CAUSES IRRITATION OF UPPER REPIRATORY TRACT. CONTACT W/SKIN/EYES CAUSES IRRITATION.

=====  
===== First Aid Measures =====

First Aid:SKIN/EYES: IMMEDIATELY FLUSH THOROUGHLY W/LARGE AMOUNTS OF WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. INGESTION: IF CONSCIOUS, GIVE WATER FREELY. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:USE ANY SUITABLE MEDIA FOR ADJACENT MATERIAL.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA. WEAR SUITABLE PROTECTIVE EQUIPMENT. REMOVE ANY IGNITION SOURCES UNTIL AREA IS DETERMINED TO BE FREE FROM EXPLOSION/FIRE HAZARDS. CONTAIN & ELIMINATE SOURCE SAFELY. TAKE UP & CONTAINERIZE FOR PROPER DISPOSAL.

=====  
===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. STORE IN A COOL, DRY AREA. TRANSFER/HANDLE IN APPROVED HOOD/W/ADEQUATE VENTILATION.

Other Precautions:DON'T BREATHE DUST, GET IN EYES, ON SKIN/CLOTHING, TAKE INTERNALLY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IF WORKPLACE EXPOSURE LIMIT OF PRODUCT/ANY COMPONENT IS EXCEEDED.

Protective Gloves:NEOPRENE/EQUIV

ALENT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:EYE WASH & SAFETY EQUIPMENT

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:1144.4F

Spec Gravity:2.1

Solubility in Water:SLIGHT

Appearance and Odor:WHITE, ODORLESS POWDER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACIDS, FLUORINE.

Stability Condition to Avoid:MOISTURE.

Hazardous Decomposition Products:LITHIUM.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.