

METCO INC, SUB OF THE PERKIN-ELMER CORP -- METCO 58NS, SP 9837 -- 3439-01-380-7146

=====
Product Identification
=====

Product ID:METCO 58NS, SP 9837

MSDS Date:08/05/1994

FSC:3439

NIIN:01-380-7146

MSDS Number: BXPWL

=== Responsible Party ===

Company Name:METCO INC, SUB OF THE PERKIN-ELMER CORP

Address:1101 PROSPECT AVENUE

Box:1006

City:WESTBURY

State:NY

ZIP:11590-0201

Country:US

Info Phone Num:516-

334-1300

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:39918

=== Contractor Identification ===

Company Name:METCO INC, SUB OF THE PERKIN-ELMER CORP

Address:1101 PROSPECT AVENUE

Box:City:WESTBURY

State:NY

ZIP:11590-2724

Country:US

Phone:516-334-1300

CAGE:39918

=====
Composition/Information on Ingredients
=====

Ingred Name:COPPER (SARA 313) (CERCLA)

CAS:7440-50-8

RTECS #:GL5325000

Fraction by Wt: 59%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.

2 MG/M3 FUME; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NICKEL (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 36%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9495

Ingred Name:INDIUM
CAS:7440-74-6
RTECS #:NL1050000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.1 MG/M3; 9495

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:COPPER:INHAL/SKIN/EYE HAZ.IRRIT UPPER
RESP TRACT & NASAL MUC MEMB.DISCOLORATION OF HAIR & SKIN.IRRIT EYE.
NICKEL:INHAL/SKIN HAZ.INHAL MAY CAUSE CANCER OF LUNG & NASAL
SINUSES,DERM. INDIUM:NO REPORTED HUMAN ILLNESS FRM INDUSTRIAL
EXPOSURES.

Explanation of Carcinogenicity:PER MSDS:NICKEL IS FOUND TO BE POTENTIAL
CARCINOGEN IN IARC & LISTED IN NTP.

Effects of Overexposure:UPPER RESP T
RACT & NASAL MUCOUS MEMBRANES
IRRIT. DISCOLORATION OF HAIR & SKIN. EYE IRRIT. CANCERS OF LUNG &
NASAL SINUSES. DERMATITIS.

Medical Cond Aggravated by Exposure:CONSULT A PHYSICIAN. TARGET
ORGANS:COPPER:RESP TRACT, SKIN, EYE; NICKEL:RESP TRACT,SKIN;
INDIUM:NONE.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER FOR @LEAST 15-20MINS OPENING EYELIDS. IRRIT
PERSISTS CONSULT PHYSICIAN. SKIN:WASH W/SOAP/WATER. INHAL:EXPO TO
FRESH

AIR. CONSULT PHYSICIAN IF IRRIT/RESP DISTRESS PERSISTS.
INGEST:CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE CLASS D FIRE EXTINGUISHER.

Fire Fighting Procedures:TREAT AS METALLIC FIRE. USE NIOSH/MSAH
APPROVED SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE
CLOTHING IF INVOLVED IN FIRE.

Unusual Fire/Explosion Hazard:FINE METAL DUSTS FLAMM AND MAY EXPLO WHEN
EXPO TO HEAT/FLAME/STRONG OXIDIZER
S.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM LOOSE POWDER ONLY W/VACUUMS EQUIPPED
W/HEPA FILTRATION. VACUUMS APPROPRIATE FOR USE W/METALLIC DUSTS
SHOULD BE UTILIZED. WIPE AREA CLEAN. DO NOT USE WATER FOR CLEAN UP
OPERATIONS. DO NOT SWEEP. AVOID GENERATING AIRBORNE DUST.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:ST

ORE AWAY FRM INCOMPATIBLES.STORE

CNTNRS IN WELL-VENTILATED CLEAN COOL DRY AREA.STORE IN MANNER TO
MIN PUNCTURES & BREAKAGE OF CNTNRS.

Other Precautions:AVOID INGEST/INHAL/EXCESSIVE SKIN CONTACT. AVOID
CONTACT OF POWDER W/WATER & OXIDIZERS. GOGG:LENS SHADES:COMBUST
SPRAY SHADE #5,PLASMA SPRAY UP TO 40KW SHADE #9,40-60KW SHADE
#10,>60KW SHADE #11.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A RESPIRATOR APPROVED BY NIOSH W/FILTER

CARTRIDGES APPROVED FOR DUST/FUMES/MISTS SHOULD BE WORN @ALL TIMES
DURING THERMAL SPRAY PROCESS TO PROTECT OPERATOR FRM EXPO TO
DUST/FUMES.RESP MAY ALSO BE WORN WHEN PROD HNDLG GENERATES DUST.

Ventilation:PRODUCT SHOULD BE USED WITH APPROPRIATE LOCAL EXHAUST
VENTILATION PROVIDED.

Protective Gloves:ALUMINIZED-PLASMA SPRAY;RUBB-OTHER.

Eye Protection:GOGGLES. (SEE OTHER PRECAUTIONS)

Other Protective Equipment:EAR PROT FOR EXCESS NOISE LEVEL.ALUMINIZED
APRON FOR PLASMA SPRAY.OT

HER APPRO PROT CLOTH AS
NECESSARY.EYEWASH.WASH FACIL
Work Hygienic Practices:WASH WELL AFTER HANDLING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Melt/Freeze Pt:M.P/F.P Text:2000F,1093C
Spec Gravity:3.7
Solubility in Water:NEGATIVE
Appearance and Odor:POWDER, NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, ACIDS, SULFUR, NI(NO3)2, COMBUSTIBLES

Stability Condition to Avoid:AVOID CONTACT OF POWDER WITH WATER &
OXIDIZERS.

Hazardous Decomposition Products:OZONE & NITRIC OXIDE ARE FORM BY
PLASMA FLAME(SIMILAR TO WELDING FUMES).THIS ACTION IS INDEPENDENT
OF METAL POWDER.

===== Disposal Considerations =====

Waste Disposal Methods:EMPTY PROD CNTNRS,PROD WASTE & CLEANING MEDIA
SHOULD BE STORED & DISPOSED OF ACCORDING TO APPROPRIATE
LOC/STATE/FED REGULATORY GUIDELINES. CONTAINS CO/NI:SUB
TO
REPORTING RQMTS OF SARA SEC313;NI:LIST ED IN HAZ AIR POLLUTANTS EPA
CLEAN AIR ACT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify
and
assume responsibility for the suitability of this information to their
particular situation.