

SPRAYON PRODUCTS DIV SHERWIN-WILLIAMS CO -- KRYLON 1303/1303A CRYSTAL CLEAR --
8010-00-963-4058

===== Product Identification =====

Product ID:KRYLON 1303/1303A CRYSTAL CLEAR

MSDS Date:08/20/1994

FSC:8010

NIIN:00-963-4058

MSDS Number: BXQFT

=== Responsible Party ===

Company Name:SPRAYON PRODUCTS DIV SHERWIN-WILLIAMS CO

Address:31500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139-5000

Country:US

Info P

Phone Num:800-777-2966

Emergency Phone Num:216-292-7400

CAGE:09800

=== Contractor Identification ===

Company Name:SAX ARTS & CRAFTS SUB OF BEATRICE COMPANIES INC

Address:2405 S CALHOUN RD

Box:City:NEW BERLIN

State:WI

ZIP:53151

Country:US

Phone:262-784-6880

CAGE:26290

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

===== Composition/Information on Ingredi

ents =====

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9495

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:V M & P NAPHTHA
CAS:64742-89-8
Fraction by Wt: 22%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PETROLEUM HYDROCARBON,
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSH
A PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/125STEL;9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLEN

ES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 13%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 11%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:750PPM/1000STEL;9495

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOLATILE ORGANIC CONTENT = 92%

RTECS #:9999999VO

Frac

tion by Wt: 92%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-IRRITATION TO EYES, SKIN &
RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME
OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS & POSSIBLY DEATH.
CHRONI

C-PROLONGED &/OR REPEATED OVEREXPOSURE MAY CAUSE PERIPHERAL
NEUROPATHY, ADVERSE EFFECTS TO LIVER, URINARY, BLOOD FORMING, CVS,
CNS OR REPRODUCTIVE SYSTEMS

Explanation of Carcinogenicity:NO INGREDIENT IN THESE PRODUCTS IS AN
NTP, IARC OR OSHA LISTED CARCINOGEN. SOME MAY BE LISTED BY
CALIFORNIA.

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA & LOSS OF
COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR
SPRAY MIST.

Medical Cond Aggravated by Exposure:NONE G

ENERALLY RECOGNIZED.

=====
First Aid Measures
=====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.
EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE
CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE. INHALED:REMOVE FROM
EXPOSURE. A ID OR RESTORE BREATHING AS NEEDED. KEEP WARM & QUIET.
SWALLOWED:GET IMMEDIATE MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Me
thod:PMCC
Flash Point:1
Evaporation Rate & Reference:>1 (ETHER)
Appearance and Odor:MFR GAVE NO INFORMATION ON MSDS.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
MFR GAVE NO INFORMATION ON MSDS.
Stability Condition to Avoid:NONE KNOWN.
Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE & CARBON
MONOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====
Disposal Considerations
=====

Waste Disposal Methods:WASTE FROM THESE PRODUCTS MAY BE HAZARDOUS UNDER
RCRA (40CFR261) & MUST BE TESTED TO DETERMINE RCRA WASTE NUMBERS. DO
NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF I/A/W FEDERAL,
STATE & LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or
implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.